

13.5' POWER CORD & AIR PRODUCTS FROM GROTE


ULTRALINK™

**CRUSH
RESISTANT**

**ALL
WEATHER**

**SAE J560™
STANDARD**

**SAE J2394™
STANDARD**

FEATURES & BENEFITS

- Rubber air lines are resistant to gasoline, diesel fuel, oil, and other chemicals
- Tractor ends of the hoses include swivel fittings, providing easy and quick installation
- Premium high-strength spiral wrap protects the cable and air lines from chaffing and kinking

POWER CORD SPECIFICATIONS

PLUG: SAE J560
CABLE: SAE J2394 (ABS)
CORD: 1/8 GA, 2/10 GA, 4/12 GA
OPERATING RANGE:
-55°F TO 190°F / -48°C TO 87°C

AIR LINE SPECIFICATIONS

DOT FMVSS-106
SAE J1402

81-3135
3-IN-1 ULTRALINK™ POWER CORD AND AIR ASSEMBLY, 13.5', BLACK AIR LINES W/ANODIZED GRIPS

The ULTRALINK Power Cord is the backbone of Grote's 3-in-1 system! This premium power cord is constructed utilizing Grote's crush resistant plug, so frequent replacement of the plug is no longer a consideration. Our plug stands up to the harshest environments and provides maximum reliability, while delivering improved performance, longer wear and superior conductivity.

PLUG DESIGN

Crush-resistant, weather-tight elastomeric material
Solid brass, nickel-plated pins


87174
**ULTRALINK™ PREMIUM STRAIGHT ABS POWER CORD,
13.5' 1/8, 2/10, 4/12 GA, GREEN**

- ULTRALINK power cords exceed minimum legal lamp power delivery requirements for single or double trailer configurations
- Zinc die-cast plugs are filled with elastomeric material that resists crushing and acts as potting to seal solid brass terminals from moisture
- Adhesive bonds cable to plug, eliminating need for supporting spring and preventing moisture from entering the back of the plug
- Corrosion resistant solid brass terminals provide superior current capacity with minimal voltage drop
- Advanced polymer jacketing material provides complete sealing and abrasion protection between -55°F and 190°F


81-0113
**RUBBER AIR HOSE, EPDM,
13.5', BLACK**

- 3/8" SAE J1402 Type A, EPDM rubber hose
- Meets or exceeds all DOT FMVSS No. 106 – Brake Hoses, 49 CFR 571.106
- Designed for operating pressure up to 225 psi
- Includes swivel fitting for the tractor-end connection
- These rugged elastomeric hoses are resistant to gasoline, diesel fuel, oil and other chemicals


CRUSH RESISTANT

Grote's ULTRALINK's crush-resistant design can survive being run over by a heavy duty vehicle while conventional hollow core designs are permanently deformed and rendered useless.


EZ-FIND

SCAN FOR TECH SPECS,
RELATED PRODUCTS
AND MORE

**FOR MORE INFORMATION
VISIT OUR WEBSITE.
GROTE.COM**