

REFERENCE GUIDE

ELECTRICAL CONNECTION AND ACCESSORIES

BRANCHEMENTS ÉLECTRIQUES
ET ACCESSOIRES

CONEXIONES ELÉCTRICAS
Y ACCESORIOS

Grote®



WWW.GROTE.COM

MODEL NUMBER INDEX
INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO



MODEL NUMBER INDEX
INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
00870.....	77, 184	81-0012-H.....	21	81-0112-SS.....	25	81-0612.....	6	81-2306.....	30	82-0860.....	11
00872.....	77, 184	81-0012-HB.....	21	81-0112-RGR.....	25	81-1012-100B.....	31	81-2308.....	30	82-0861.....	11
01061.....	180	81-0012-HR.....	21	81-0112-RSS.....	25	81-1012-100BL.....	31	81-2309.....	30	82-0950.....	14, 144
01062.....	181	81-0012-R.....	21	81-0113-08B.....	24	81-1012-100G.....	31	81-2312.....	7	82-1000.....	16
01063.....	181	81-0015.....	21	81-0113-08R.....	24	81-1012-100R.....	31	81-2315.....	7	82-1001.....	12
01063-NA.....	181	81-0015-40.....	21	81-0113-100B.....	24	81-1012-100Y.....	31	81-2412.....	7	82-1002.....	10
351044.....	16	81-0015-40B.....	21	81-0113-100R.....	24	81-1012-500B.....	31	81-2415.....	7	82-1005.....	10
43402.....	15	81-0015-40BC...	20	81-0115.....	25	81-1012-500BL.....	31	81-3112.....	26	82-1010.....	13
43942.....	15	81-0015-40C.....	20	81-0115-25.....	24	81-1012-500G.....	31	81-3112-GRP.....	26	82-1011.....	13
44170.....	106	81-0015-40H.....	21	81-0115-B.....	25	81-1012-500R.....	31	81-3115.....	26	82-1012.....	13
68170.....	110	81-0015-40HB.....	21	81-0115-BGB.....	25	81-1012-500Y.....	31	81-3115-GRP.....	26	82-1016.....	13
68380.....	110	81-0015-40CGH..	20	81-0115-BSS.....	25	81-1014-1000B.....	31	81-3120.....	26	82-1018.....	13
68680.....	113	81-0015-40HGH..	21	81-0115-GB.....	25	81-1014-1000BL..	31	81-3212.....	26	82-1019.....	12
81-0001.....	22	81-0015-HGH.....	21	81-0115-GR.....	25	81-1014-1000G.....	31	81-3212-GRP.....	26	82-1020.....	13
81-0001-38B.....	22	81-0015-40HR.....	21	81-0115-GRB.....	25	81-1014-1000R.....	31	81-3215.....	26	82-1021.....	13
81-0001-38BS...	22	81-0015-40R.....	21	81-0115-R.....	25	81-1014-1000Y.....	31	81-3215-GRP.....	26	82-1022.....	13
81-0001-38R.....	22	81-0015-40RC....	20	81-0115-RGR.....	25	81-1014-100B.....	31	81-3215N.....	26	82-1023.....	13
81-0001-38RS...	22	81-0015-B.....	21	81-0115-RSS.....	25	81-1014-100BL.....	31	81-3312.....	27	82-1025.....	13
81-0001-B.....	22	81-0015-BC.....	20	81-0115-SS.....	25	81-1014-100G.....	31	81-3312-GRP.....	27	82-1027.....	13
81-0001-BS.....	22	81-0015-C.....	20	81-0115-SPR.....	25	81-1014-100R.....	31	81-3315.....	27	82-1028.....	15
81-0001-C.....	23	81-0015-H.....	21	81-0116-08BP...	24	81-1014-100Y.....	31	81-3315-GRP.....	27	82-1029.....	15
81-0001-CB.....	23	81-0015-HB.....	21	81-0116-100BP...	24	81-1018-100B.....	31	81-3412.....	27	82-1030.....	15
81-0001-CR.....	23	81-0015-HR.....	21	81-0117-100BP...	24	81-1034-250B.....	31	81-3412-GRP.....	27	82-1031.....	15
81-0001-CS.....	23	81-0015-R.....	21	81-0120.....	25	81-1038-100B.....	31	81-3415.....	27	82-1032.....	15
81-0001-CRS.....	23	81-0015-RC.....	20	81-0120-GB.....	25	81-1038-100BL.....	31	81-3415-GRP.....	27	82-1033.....	15
81-0001-CBS.....	23	81-0020.....	21	81-0120-GR.....	25	81-1038-100G.....	31	81-3512.....	27	82-1034.....	15
81-0001-90CRS...	23	81-0020-B.....	21	81-0120-GRB.....	25	81-1038-100R.....	31	81-3512-GRP.....	27	82-1035.....	15
81-0001-90CBS...	23	81-0020-BC.....	20	81-0124.....	23	81-1038-100Y.....	31	81-3515.....	27	82-1036.....	15
81-0001-R.....	22	81-0020-C.....	20	81-0125.....	23	81-1038-500B.....	31	81-3515-GRP.....	27	82-1038.....	15
81-0001-RS.....	22	81-0020-R.....	21	81-0126.....	24	81-1038-500BL.....	31	82-0115.....	109	82-1039.....	15
81-0001-S.....	22	81-0020-RC.....	20	81-0126T.....	24	81-1038-500G.....	31	82-0216.....	102	82-1040.....	13
81-0001-SB.....	23	81-0038-250.....	25	81-0128.....	29	81-1038-500R.....	31	82-0302.....	104	82-1041.....	14, 147
81-0001-SBB.....	23	81-0054.....	21	81-0128-14.....	29	81-1038-500Y.....	31	82-0303.....	104	82-1041V.....	14, 147
81-0001-SBR.....	23	81-0100-100.....	24	81-0129.....	28	81-1058-250B.....	31	82-0304.....	104	82-1042.....	14, 147
81-0001-SBBS...	23	81-0101-08.....	24	81-0130.....	28	81-1516-100B.....	31	82-0307.....	107	82-1042V.....	14, 147
81-0001-SBRS...	23	81-0101-100.....	24	81-0131.....	28	81-1532-500B.....	31	82-0308.....	107	82-1043.....	10
81-0001-SR.....	23	81-0102-08.....	24	81-0132.....	29	81-1532-100B.....	31	82-0309.....	105	82-1044.....	12
81-0008.....	21	81-0102-100.....	24	81-0133.....	29	81-2012-S.....	7	82-0310.....	105	82-1050.....	10, 12
81-0008-B.....	21	81-0103-25.....	24	81-0134.....	29	81-2015.....	7	82-0311.....	107	82-1051.....	15
81-0008-R.....	21	81-0110-08B.....	24	81-0135.....	28	81-2015-40.....	7	82-0312.....	107	82-1052.....	15
81-0011.....	22	81-0110-08R.....	24	81-0136.....	29	81-2015-S.....	7	82-0313.....	107	82-1055.....	11
81-0011-38B.....	22	81-0110-100B.....	24	81-0137.....	28	81-2112.....	7	82-0315.....	102	82-1055NB.....	11
81-0011-38R.....	22	81-0110-100R.....	24	81-0138.....	28	81-2115.....	7	82-0402.....	106	82-1056.....	12
81-0011-45B.....	22	81-0111.....	24	81-0139.....	28	81-2212.....	7	82-0456.....	108	82-1058.....	10
81-0011-45R.....	22	81-0112.....	25	81-0140.....	28	81-2212-V.....	7	82-0458.....	108	82-1059.....	10
81-0011-B.....	22	81-0112-100B.....	24	81-0141.....	6	81-2215.....	7	82-0465.....	108	82-1060.....	10
81-0011-R.....	22	81-0112-100R.....	24	81-0142.....	6	81-2215-DS.....	7	82-0600.....	103	82-1061.....	12
81-0011-SB.....	22	81-0112-B.....	25	81-0145.....	28	81-2215-V.....	7	82-0850.....	11	82-1062.....	12
81-0011-R.....	22	81-0112-BGB.....	25	81-0146.....	28	81-2300.....	30	82-0851.....	14, 147	82-1063.....	12
81-0012.....	21	81-0112-BSS.....	25	81-0147.....	28	81-2301.....	30	82-0852.....	14, 147	82-1901.....	104
81-0012-GH.....	21	81-0112-GB.....	25	81-0149.....	24	81-2303VM.....	30	82-0853.....	11	82-1902.....	104
81-0012-CGH.....	20	81-0112-GR.....	25	81-0410.....	6	81-2303.....	30	82-0855.....	11	82-1903.....	104
81-0012-B.....	21	81-0112-GRB.....	25	81-0412.....	6	81-2304.....	30	82-0856.....	11	82-1904.....	104
81-0012-C.....	20	81-0112-R.....	25	81-0610.....	6	81-2305.....	30	82-0859.....	11	82-1905.....	104

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
82-1906.....	104	82-2151.....	103	82-2210.....	117	82-2355.....	116	82-5706.....	74, 160	82-5826-500.....	72
82-1907.....	104	82-2152.....	103	82-2211.....	123	82-2356.....	116	82-5707.....	74, 160	82-5827.....	72
82-1908.....	104	82-2154.....	12	82-2212.....	121	82-2357.....	116	82-5708.....	74, 160	82-5827-250.....	72
82-1909.....	104	82-2155.....	100, 152	82-2213.....	118	82-2358.....	116	82-5709.....	74, 160	82-5827-500.....	72
82-1910.....	104	82-2156.....	101	82-2215.....	129	82-2359.....	116	82-5710.....	74, 160	82-5828.....	72
82-1911.....	104	82-2157.....	100	82-2216.....	116	82-5500.....	70	82-5711.....	74, 160	82-5828-250.....	72
82-1912.....	104	82-2158.....	101	82-2217.....	116	82-5501.....	70	82-5712.....	74, 160	82-5828-500.....	72
82-1913.....	105	82-2159.....	108	82-2218.....	119	82-5502.....	70	82-5713.....	74, 160	82-5901.....	71
82-1914.....	105	82-2160.....	129	82-2219.....	122	82-5503.....	70	82-5714.....	74, 160	82-5901-500.....	71
82-1915.....	105	82-2161.....	129	82-2220.....	103	82-5504.....	70	82-5715.....	74, 160	82-5902.....	71
82-1916.....	105	82-2162.....	129	82-2221.....	102	82-5507.....	70	82-5716.....	74, 160	82-5904.....	71
82-2100.....	106	82-2163.....	129	82-2222.....	102	82-5508.....	70	82-5721.....	75, 161	82-5905.....	71
82-2102.....	106	82-2164.....	121	82-2224.....	102	82-5509.....	70	82-5722.....	74, 160	82-5907.....	71
82-2103.....	100, 152	82-2165.....	121	82-2225.....	102	82-5510.....	70	82-5723.....	74, 160	82-5908.....	71
82-2104.....	100, 152	82-2166.....	121	82-2226.....	102	82-5511.....	70	82-5724.....	75, 161	82-6010.....	134
82-2105.....	106	82-2167.....	129	82-2227.....	102	82-5512.....	70	82-5725.....	74, 160	82-6011.....	134
82-2106.....	103	82-2168.....	129	82-2230.....	109	82-5514.....	70	82-5726.....	74, 160	82-6700.....	74, 160
82-2107.....	106	82-2169.....	129	82-2231.....	108	82-5515.....	70	82-5730.....	75, 161	82-6701.....	74, 160
82-2108.....	103	82-2170.....	117	82-2232.....	108	82-5519.....	70	82-5731.....	75, 161	82-6703.....	74, 160
82-2110.....	103	82-2171.....	117	82-2233.....	100, 152	82-5520.....	70	82-5732.....	75, 161	82-6704.....	74, 160
82-2111.....	102	82-2172.....	117	82-2234.....	108	82-5521.....	70	82-5733.....	74, 160	82-6706.....	74, 160
82-2112.....	103	82-2173.....	117	82-2235.....	101	82-5522.....	70	82-5734.....	75, 161	82-6707.....	74, 160
82-2114.....	102	82-2174.....	117	82-2236.....	106	82-5524.....	70	82-5735.....	75, 161	82-6709.....	74, 160
82-2115.....	104	82-2176.....	116	82-2238.....	109	82-5525.....	70	82-5736.....	75, 161	82-6710.....	74, 160
82-2116.....	102	82-2177.....	116	82-2241.....	118	82-5526.....	70	82-5737.....	75, 161	82-6712.....	74, 160
82-2117.....	102	82-2178.....	116	82-2246.....	121	82-5527.....	70	82-5738.....	75, 161	82-6713.....	74, 160
82-2118.....	102	82-2179.....	117	82-2247.....	116	82-5590.....	70	82-5739.....	75, 161	82-6715.....	74, 160
82-2119.....	102	82-2180.....	117	82-2248.....	116	82-5591.....	70	82-5740.....	75, 161	82-6716.....	74, 160
82-2120.....	102	82-2181.....	117	82-2249.....	116	82-5600.....	73	82-5741.....	75, 161	82-6717.....	74, 160
82-2121.....	102	82-2182.....	117	82-2250.....	116	82-5601.....	73	82-5742.....	75, 161	82-6718.....	74, 160
82-2122.....	102	82-2183.....	117	82-2251.....	116	82-5602.....	73	82-5743.....	74, 160	82-6719.....	74, 160
82-2123.....	102	82-2184.....	117	82-2301.....	129	82-5603.....	73	82-5744.....	75, 161	82-6720.....	74, 160
82-2124.....	102	82-2185.....	117	82-2302.....	129	82-5604.....	73	82-5745.....	75, 161	82-6721.....	74, 160
82-2125.....	103	82-2186.....	117	82-2303.....	130	82-5605.....	73	82-5753.....	74, 160	82-6722.....	74, 160
82-2127.....	103	82-2187.....	117	82-2304.....	130	82-5606.....	73	82-5759-1500.....	76, 146	82-6723.....	74, 160
82-2128.....	103	82-2188.....	117	82-2305.....	130	82-5607.....	73	82-5760.....	76, 146	82-6725.....	74, 160
82-2130.....	105	82-2189.....	117	82-2306.....	101	82-5609.....	73	82-5760-1200.....	76, 146	82-6726.....	74, 160
82-2131.....	105	82-2190.....	117	82-2311.....	131	82-5610.....	73	82-5761.....	76, 146	82-6727.....	75, 161
82-2132.....	105	82-2191.....	117	82-2312.....	131	82-5611.....	73	82-5761-500.....	76, 146	82-6728.....	75, 161
82-2133.....	105	82-2192.....	117	82-2313.....	131	82-5612.....	73	82-5762.....	76, 146	82-6730.....	75, 161
82-2134.....	105	82-2193.....	117	82-2314.....	131	82-5614.....	73	82-5822.....	72	82-6731.....	75, 161
82-2135.....	105	82-2194.....	117	82-2332.....	131	82-5615.....	73	82-5822-250.....	72	82-6732.....	75, 161
82-2136.....	105	82-2195.....	116	82-2334.....	131	82-5619.....	73	82-5822-500.....	72	82-6733.....	74, 160
82-2137.....	105	82-2196.....	116	82-2338.....	131	82-5620.....	73	82-5823.....	72	82-6734.....	75, 161
82-2140.....	12	82-2197.....	116	82-2340.....	117	82-5621.....	73	82-5823-250.....	72	82-6735.....	75, 161
82-2141.....	12	82-2198.....	116	82-2341.....	117	82-5622.....	73	82-5823-500.....	72	82-6736.....	75, 161
82-2142.....	11	82-2199.....	116	82-2342.....	117	82-5623.....	73	82-5824.....	72	82-6737.....	75, 161
82-2144.....	11, 14, 147	82-2200.....	116	82-2343.....	117	82-5624.....	73	82-5824-250.....	72	82-6738.....	75, 161
82-2145.....	10	82-2201.....	116	82-2344.....	117	82-5700.....	74, 160	82-5824-500.....	72	82-6739.....	75, 161
82-2146.....	12	82-2203.....	109	82-2350.....	117	82-5701.....	74, 160	82-5825.....	72	82-6740.....	75, 161
82-2147.....	12	82-2204.....	109	82-2351.....	117	82-5702.....	74, 160	82-5825-250.....	72	82-6741.....	75, 161
82-2148.....	12	82-2207.....	121	82-2352.....	117	82-5703.....	74, 160	82-5825-500.....	72	82-6742.....	75, 161
82-2149.....	12	82-2208.....	117	82-2353.....	117	82-5704.....	74, 160	82-5826.....	72	82-6743.....	74, 160
82-2150.....	101	82-2209.....	121	82-2354.....	117	82-5705.....	74, 160	82-5826-250.....	72	82-6744.....	75, 161



PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
82-6745.....	75, 161	82-9183.....	143	82-9542.....	141	82-ANM-I-15A ..	119	82-ANT-I-10A ...	122	82-FMX-M-20A ..	124
82-6753.....	74, 160	82-9184.....	143	82-9543.....	144	82-ANM-I-20A ..	119	82-ANT-I-15A ...	122	82-FMX-M-25A ..	124
82-7014.....	150	82-9216.....	143	82-9544.....	144	82-ANM-I-25A ..	119	82-ANT-I-20A ...	122	82-FMX-M-30A ..	124
82-7025.....	150	82-9217.....	143	82-9545.....	139	82-ANM-I-30A ..	119	82-ANT-I-25A ...	122	82-FMX-M-40A ..	124
82-7025-R.....	150	82-9218.....	136	82-9546.....	139	82-ANM-I-3A ..	119	82-ANT-I-30A ...	122	82-FMXLP-20A ...	124
82-7053.....	150	82-9219.....	136	82-9547.....	139	82-ANM-I-5.....	119	82-ANT-I-5A ...	122	82-FMXLP-25A ...	124
82-7072.....	150	82-9220.....	136	82-9552.....	135	82-ANM-I-5A ..	119	82-ANTI-7.5A ..	122	82-FMXLP-30A ...	124
82-9047.....	134	82-9221.....	136	82-9553.....	135	82-ANMI-7.5A..	119	82-ANX-20A....	123	82-FMXLP-40A ...	124
82-9048.....	134	82-9317.....	138	82-9554.....	135	82-ANR-1A.....	120	82-ANX-30A....	123	82-FMXLP-50A ...	124
82-9050.....	134	82-9318.....	138	82-9555.....	135	82-ANR-10A....	120	82-ANX-40A....	123	82-FMXLP-60A ...	124
82-9051.....	134	82-9319.....	138	82-9556.....	135	82-ANR-15A....	120	82-ANX-50A....	123	82-FSA-10A-G....	128
82-9053.....	134	82-9428.....	139	82-9557.....	135	82-ANR-20A....	120	82-ANX-60A....	123	82-FSA-15A-G....	128
82-9054.....	134	82-9429.....	139	82-9558.....	135	82-ANR-25A....	120	82-ANX-70A....	123	82-FSA-1A-G.....	128
82-9056.....	134	82-9430.....	139	82-9595.....	141	82-ANR-2A.....	120	82-ANX-80A....	123	82-FSA-20A-G....	128
82-9057.....	134	82-9431.....	139	82-9596.....	141	82-ANR-30A....	120	82-ASST-180 ...	118,	82-FSA-25A-G....	128
82-9058.....	134	82-9432.....	139	82-9597.....	140	82-ANR-35A....	120	119, 120, 127		82-FSA-2A-G.....	128
82-9059.....	134	82-9433.....	139	82-9613.....	140	82-ANR-3A.....	120	82-ASST-43...118, 126		82-FSA-30A-G....	128
82-9060.....	134	82-9434.....	139	82-9614.....	145	82-ANR-40A....	120	82-ASST-44...120, 126		82-FSA-3A-G.....	128
82-9061.....	134	82-9435.....	139	82-9620.....	141	82-ANR-4A....	120	82-ASST-45.....	125	82-FSA-5A-G.....	128
82-9062.....	134	82-9436.....	139	82-9623.....	142	82-ANR-5A....	120	82-ASST-53 ...	120,	82-FSA-9-G.....	126
82-9063.....	134	82-9437.....	139	82-9640.....	134	82-ANR-6T....	120	123, 127		82-FSO-7-G.....	126
82-9095.....	134	82-9438.....	139	82-9641.....	130	82-ANR-7.....	120	82-ASST-64 ...	118,	82-MGGA-80A ...	128
82-9096.....	134	82-9439.....	139	82-9642.....	130	82-ANR-7.5A ...	120	123, 126		82-MGGA-100A ..	128
82-9097.....	134	82-9440.....	139	82-9647.....	130	82-ANR-7P....	120	82-ASST-80M ...	118,	82-MGGA-125A ..	128
82-9098.....	134	82-9448.....	135	82-9648.....	130	82-ANR-I-10A ...	121	126		82-MGGA-150A ..	128
82-9099.....	134	82-9463.....	135	82-9649.....	130	82-ANR-I-15A ...	121	82-ASST-80R ...	120,	82-MGGA-175A ..	128
82-9100.....	134	82-9512.....	139	82-9650.....	130	82-ANR-I-20A ...	121	126		82-MGGA-200A ..	128
82-9124.....	141	82-9513.....	139	82-9651.....	130	82-ANR-I-25A ...	121	82-BLM-I-304 ...	130	82-MGGA-225A ..	128
82-9125.....	141	82-9514.....	139	82-9652.....	130	82-ANR-I-30A ...	121	82-BLM-I-306 ...	130	82-MGGA-250A ..	128
82-9126.....	140	82-9515.....	139	82-9653.....	130	82-ANR-I-3A ...	121	82-BLM-I-310 ...	130	82-MGGA-300A ..	128
82-9130.....	142	82-9516.....	139	82-9654.....	130	82-ANR-I-40A ...	121	82-BLR-I-304 ...	130	82-MGGA-FB	128
82-9131.....	142	82-9517.....	139	82-9655.....	130	82-ANR-I-5.....	121	82-BLR-I-306 ...	130	82-PUL-01	128
82-9132.....	142	82-9518.....	139	82-AGA-6.....	126	82-ANR-I-5A ...	121	82-BLR-I-310 ...	130	82-PUL-07	128
82-9133.....	140	82-9519.....	139	82-AGC-60....	126	82-ANRI-7.5A ...	121	82-FLB-40A	125	83-1932.....	42
82-9134.....	140	82-9520.....	139	82-AGW-5.....	126	82-ANS-10A....	119	82-FLB-60A	125	83-1933.....	42
82-9135.....	140	82-9521.....	139	82-AGX-5.....	126	82-ANS-15A....	119	82-FLB-70A	125	83-1934.....	42
82-9164.....	138	82-9522.....	139	82-ANK-10A....	123	82-ANS-20A....	119	82-FLD-80A	125	83-1935.....	42
82-9165.....	138	82-9523.....	138	82-ANK-15A....	123	82-ANS-25A....	119	82-FLF-20A....	125	83-1937.....	42
82-9166.....	138	82-9524.....	138	82-ANK-5A....	123	82-ANS-30A....	119	82-FLF-30A....	125	83-1938.....	42
82-9167.....	138	82-9525.....	138	82-ANK-7.5A ...	123	82-ANS-3A.....	119	82-FLF-40A....	125	83-1939.....	42
82-9168.....	138	82-9527.....	138	82-ANM-10A....	118	82-ANS-5A.....	119	82-FLF-50A....	125	83-1940.....	42
82-9169.....	138	82-9528.....	138	82-ANM-15A....	118	82-ANS-7.....	119	82-FLF-60A....	125	83-1941.....	42
82-9170.....	138	82-9529.....	139	82-ANM-20A....	118	82-ANS-7.5A ...	119	82-FLM-100A ...	125	83-1943.....	43
82-9171.....	138	82-9530.....	139	82-ANM-25A....	118	82-ANS-7P....	119	82-FLM-120A ...	125	83-1944.....	43
82-9172.....	138	82-9531.....	139	82-ANM-2A.....	118	82-ANS-7T....	119	82-FLM-60A....	125	83-1945.....	43
82-9173.....	138	82-9532.....	139	82-ANM-30A....	118	82-ANS-I-5.....	119	82-FLM-80A....	125	83-1946.....	43
82-9174.....	138	82-9533.....	138	82-ANM-35A....	118	82-ANT-10A....	122	82-FLS-30A	125	83-1947.....	43
82-9175.....	138	82-9534.....	138	82-ANM-3A.....	118	82-ANT-15A....	122	82-FLS-40A	125	83-1951.....	43
82-9176.....	138	82-9535.....	138	82-ANM-4A....	118	82-ANT-20A....	122	82-FMX-20A....	124	83-1952.....	43
82-9177.....	138	82-9536.....	138	82-ANM-5A....	118	82-ANT-25A....	122	82-FMX-25A....	124	83-1953.....	43
82-9178.....	138	82-9537.....	138	82-ANM-7.....	118	82-ANT-30A....	122	82-FMX-30A....	124	83-1954.....	43
82-9179.....	138	82-9538.....	139	82-ANM-7.5A ..	118	82-ANT-5A.....	122	82-FMX-40A....	124	83-1955.....	43
82-9180.....	138	82-9539.....	139	82-ANM-8P....	118	82-ANT-7.....	122	82-FMX-50A....	124	83-1956.....	43
82-9181.....	138	82-9540.....	145	82-ANM-8T....	118	82-ANT-7.5A ...	122	82-FMX-60A....	124	83-2102.....	47
82-9182.....	138	82-9541.....	141	82-ANM-I-10A ..	119	82-ANT-7P....	122	82-FMX-M-15A ..	124	83-2104.....	47

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
83-2105.....	47	83-2412.....	40	83-3102.....	47	83-6018-3.....	80	83-6120.....	81	83-6562.....	64, 173
83-2132.....	50	83-2413.....	40	83-3103.....	47	83-6019.....	80	83-6121.....	81	83-6563.....	64, 173
83-2134.....	50	83-2414.....	40	83-3104.....	47	83-6019C.....	81	83-6122.....	81	83-6564.....	64, 173
83-2150.....	38	83-2415.....	40	83-3110.....	47	83-6019-3.....	80	83-6123.....	81	83-6565.....	64, 173
83-2150-3.....	38	83-2416.....	40	83-3111.....	47	83-6020.....	80	83-6163.....	81	83-6566.....	64, 173
83-2180.....	46	83-2417.....	40	83-3112.....	47	83-6020-3.....	80	83-6500.....	92, 175	83-6567.....	64, 173
83-2187.....	52	83-2430.....	41	83-3150.....	36	83-6021.....	80	83-6501.....	92, 175	83-6568.....	64
83-2190.....	46	83-2432.....	41	83-3150-3.....	36	83-6021C.....	81	83-6502.....	70, 169	83-6569.....	65, 173
83-2191.....	52	83-2434.....	41	83-3182.....	56	83-6021-3.....	80	83-6503.....	55, 164	83-6570.....	63
83-2204.....	47	83-2435.....	41	83-3187.....	56	83-6022.....	81	83-6505.....	90, 170	83-6600.....	82
83-2205.....	47	83-2447.....	48	83-3191.....	56	83-6023.....	81	83-6506.....	82	83-6650.....	171
83-2206.....	47	83-2448.....	48	83-3350.....	36	83-6025.....	80	83-6507.....	82	83-6651.....	171
83-2207.....	47	83-2449.....	48	83-3350-3.....	36	83-6025C.....	81	83-6508.....	92, 175	83-6652.....	171
83-2208.....	47	83-2455.....	48	83-3382.....	56	83-6025-3.....	80	83-6509.....	85, 176	83-6653.....	171
83-2209.....	48	83-2456.....	48	83-3387.....	52	83-6026.....	80	83-6510.....	173	83-6654.....	171
83-2210.....	48	83-2457.....	48	83-3391.....	52	83-6026-3.....	80	83-6511.....	172	83-6655.....	171
83-2213.....	48	83-2458.....	48	83-3550.....	36	83-6027.....	81	83-6512.....	172	83-6656.....	171
83-2216.....	48	83-2501.....	40	83-3550-3.....	36	83-6028.....	80	83-6513.....	176	83-6657.....	171
83-2217.....	50	83-2502.....	49	83-3582.....	56	83-6028-3.....	80	83-6514.....	82	83-6658.....	171
83-2218.....	50	83-2504.....	49	83-3587.....	53	83-6029.....	80	83-6515.....	76, 154, 176	83-6659.....	171
83-2219.....	51	83-2505.....	49	83-3591.....	53	83-6029C.....	81	83-6516.....	64, 173	83-6660.....	171
83-2220.....	51	83-2507.....	49	83-4150.....	40	83-6029-3.....	80	83-6518.....	173	83-6661.....	171
83-2221.....	51	83-2510.....	40	83-4150-3.....	40	83-6030.....	84	83-6519.....	59, 172	83-6990.....	94, 176
83-2222.....	51	83-2511.....	40	83-4350.....	40	83-6030-3.....	82	83-6520.....	165	83-6991.....	94, 176
83-2223.....	52	83-2512.....	40	83-4350-3.....	40	83-6031.....	84	83-6521.....	63	83-6992.....	94, 176
83-2224.....	52	83-2513.....	40	83-4550.....	40	83-6031-3.....	82	83-6522.....	63	83-6993.....	94, 176
83-2225.....	53	83-2532.....	51	83-4550-3.....	40	83-6032.....	84	83-6524.....	59, 172	83-6998.....	94
83-2226.....	53	83-2534.....	51	83-4999.....	91	83-6032-3.....	82	83-6525.....	92, 175	83-6999.....	94
83-2227.....	54	83-2540.....	49	83-5000.....	91	83-6033.....	84	83-6527.....	85, 176	83-7000.....	94
83-2250.....	54	83-2560.....	54	83-5001.....	91	83-6033-3.....	82	83-6528.....	85, 176	83-7001.....	94
83-2251.....	54	83-2561.....	54	83-5002.....	91	83-6034-3.....	82	83-6530.....	167	83-7002.....	94
83-2302.....	48	83-2580.....	46	83-5003.....	91	83-6035-3.....	82	83-6532.....	169	83-7003.....	96
83-2303.....	48	83-2583.....	55	83-5004.....	91	83-6036-3.....	82	83-6533.....	91	83-7004.....	96
83-2304.....	48	83-2587.....	53	83-6000.....	80	83-6037.....	81	83-6535.....	83, 166	83-7005.....	96
83-2305.....	48	83-2590.....	46	83-6000-3.....	80	83-6040.....	81	83-6536.....	65, 166	83-7006.....	97
83-2308.....	48	83-2591.....	53	83-6001.....	80	83-6041.....	81	83-6537.....	88, 168	83-7007.....	96
83-2332.....	51	83-2600.....	57	83-6001C.....	81	83-6042.....	82	83-6538.....	58, 165	83-7008.....	96
83-2334.....	51	83-2602.....	46	83-6001-3.....	80	83-6043.....	82	83-6539.....	45, 164	83-7009.....	96
83-2340.....	48	83-2608.....	57	83-6004.....	80	83-6045.....	83	83-6540.....	57, 165	83-7010.....	96
83-2380.....	46	83-2609.....	58	83-6004-3.....	80	83-6046.....	83	83-6542.....	43, 58, 164	83-7011.....	96
83-2383.....	55	83-2610.....	59	83-6005.....	80	83-6048.....	83	83-6543.....	139, 170	83-7012.....	96
83-2387.....	52	83-2612.....	44	83-6005-3.....	80	83-6049.....	83	83-6544.....	138, 170	83-7014.....	96
83-2388.....	52	83-2614.....	44	83-6006.....	80	83-6052.....	83	83-6545.....	91, 169	83-7015.....	29
83-2390.....	46	83-2618.....	44	83-6006-3.....	80	83-6060.....	84	83-6546.....	65, 166	83-7016.....	29
83-2391.....	52	83-2624.....	36	83-6007.....	80	83-6061.....	84	83-6547.....	170	83-7017.....	29
83-2394.....	54	83-2625.....	36	83-6007C.....	81	83-6062.....	84	83-6548.....	170	83-7018.....	96
83-2395.....	54	83-2626.....	36	83-6007-3.....	80	83-6063.....	84	83-6549.....	64, 166	83-7019.....	96
83-2396.....	54	83-2896.....	53	83-6012.....	81	83-6104.....	81	83-6550.....	167	83-7020.....	97
83-2398.....	54	83-2898.....	53	83-6013.....	81	83-6105.....	81	83-6552.....	170	83-7021.....	97
83-2399.....	52	83-2904.....	55	83-6016.....	80	83-6107.....	81	83-6553.....	170	83-7022.....	97
83-2400.....	54	83-2929.....	42	83-6016C.....	81	83-6108.....	81	83-6554.....	57, 165	83-7023.....	97
83-2401.....	54	83-2930.....	42	83-6016-3.....	80	83-6116.....	81	83-6555.....	58, 165	83-7024.....	97
83-2402.....	54	83-2931.....	42	83-6017.....	80	83-6117.....	81	83-6556.....	59, 164	83-7025.....	97
83-2408.....	40	83-3100.....	47	83-6017-3.....	80	83-6118.....	81	83-6559.....	82	83-7026.....	97
83-2410.....	40	83-3101.....	47	83-6018.....	80	83-6119.....	81	83-6561.....	16, 177	83-7027.....	97

MODEL NUMBER INDEX

INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO



MODEL NUMBER INDEX

INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
83-7028	97	83-8052	97	84-1075	110	84-2048	62	84-2220	51	84-2418	39
83-7029	95	83-8100	96	84-1076	131	84-2049	62	84-2221	51	84-2420	39
83-7029-3	95	83-8101	96	84-1077	131	84-2050	62	84-2222	51	84-2421	39
83-7034	96	83-8102	96	84-1078	131	84-2052	62	84-2223	52	84-2422	39
83-7036	96	83-8103	96	84-1079	131	84-2053	62	84-2224	52	84-2423	38
83-7037	96	83-8104	96	84-1080	131	84-2075	63	84-2225	53	84-2424	38
83-7038	96	83-8105	96	84-1081	111	84-2076	63	84-2226	53	84-2425	38
83-7039	96	83-8106	96	84-1082	111	84-2078	63	84-2228	52	84-2426	38
83-8000	94	83-8107	96	84-1083	111	84-2079	63	84-2250	54	84-2427	38
83-8000-3	94	83-8108	96	84-1084	112	84-2081	62	84-2251	54	84-2428	39
83-8000-S	94	83-9000	95	84-1085	112	84-2082	62	84-2301	52	84-2429	39
83-8001	94	83-9001	95	84-1086	112	84-2104	47	84-2302	52	84-2430	39
83-8001-3	94	83-9002	95	84-1090	113	84-2105	47	84-2303	48	84-2431	39
83-8001-S	94	83-9003	95	84-1091	113	84-2108	47	84-2304	48	84-2432	39
83-8002	94	83-9004	95	84-1092	113	84-2114	46	84-2305	48	84-2433	39
83-8002-3	94	83-9007	95	84-1093	131	84-2132	50	84-2308	48	84-2434	39
83-8002-S	94	83-9008	95	84-1094	131	84-2134	50	84-2310	48	84-2435	39
83-8003	94	83-9009	95	84-1937	42	84-2136	50	84-2314	46	84-2436	39
83-8003-3	94	83-9010	95	84-1938	42	84-2138	50	84-2321	52	84-2437	39
83-8003-S	94	83-9011	95	84-1939	42	84-2139	50	84-2322	52	84-2438	45
83-8004	94	84-1000	111	84-1940	42	84-2140	47	84-2332	51	84-2439	39
83-8004-3	94	84-1003	110	84-1941	42	84-2151	41	84-2334	51	84-2440	39
83-8005-3	94	84-1004	111	84-1943	43	84-2170	46	84-2336	51	84-2441	38
83-8007	94	84-1006	112	84-1944	43	84-2171	54	84-2338	51	84-2442	38
83-8007-3	94	84-1007	111	84-1945	43	84-2172	54	84-2340	48	84-2443	38
83-8007-S	94	84-1008	110	84-1946	43	84-2173	54	84-2377	55	84-2447	39
83-8008	94	84-1009	112	84-1947	43	84-2180	46	84-2378	55	84-2448	39
83-8008-250	94	84-1030	112	84-1953	43	84-2181	55	84-2380	46	84-2449	48
83-8009-3	94	84-1031	110	84-1954	43	84-2183	55	84-2381	55	84-2455	44
83-8010	94	84-1032	110	84-2000	62	84-2185	54	84-2382	55	84-2456	48
83-8011	94	84-1034	111	84-2001	62	84-2186	52	84-2383	55	84-2457	48
83-8013	94	84-1035	112	84-2002	62	84-2187	52	84-2384	55	84-2458	48
83-8014	94	84-1036	112	84-2003	62	84-2188	52	84-2387	52	84-2459	61
83-8014-3	94	84-1037	111	84-2004	62	84-2189	53	84-2388	54	84-2460	39
83-8018	94	84-1038	111	84-2005	62	84-2190	46	84-2389	53	84-2462	61
83-8030	94	84-1039	112	84-2006	62	84-2191	52	84-2390	46	84-2463	61
83-8030-3	94	84-1040	113, 131	84-2007	62	84-2192	53	84-2391	52	84-2464	61
83-8030-3200	94	84-1041	113, 131	84-2008	62	84-2194	54	84-2392	53	84-2465	61
83-8031	94	84-1042	112	84-2009	62	84-2196	52	84-2394	54	84-2466	61
83-8031-3	94	84-1048	111	84-2011	63	84-2198	52	84-2395	54	84-2467	61
83-8031-1900	94	84-1049	112	84-2013	63	84-2204	47	84-2396	54	84-2468	61
83-8032	94	84-1051	111	84-2023	63	84-2205	47	84-2397	54	84-2469	61
83-8032-3	94	84-1052	110	84-2024	63	84-2206	47	84-2398	54	84-2470	61
83-8032-1100	94	84-1054	110	84-2025	63	84-2207	47	84-2399	52	84-2471	61
83-8033	94	84-1056	112	84-2026	63	84-2208	47	84-2400	54	84-2472	61
83-8033-3	94	84-1057	112	84-2027	63	84-2209	48	84-2401	54	84-2473	61
83-8033-800	94	84-1060	110	84-2028	63	84-2210	48	84-2402	54	84-2474	61
83-8034	94	84-1062	110	84-2029	63	84-2211	48	84-2408	38	84-2475	61
83-8034-3	94	84-1064	112	84-2033	62	84-2212	48	84-2410	38	84-2476	61
83-8034-550	94	84-1067	112	84-2034	62	84-2213	48	84-2412	38	84-2477	61
83-8035	94	84-1068	111	84-2035	63	84-2215	48	84-2413	38	84-2478	61
83-8035-3	94	84-1069	110	84-2036	63	84-2216	48	84-2414	38	84-2479	61
83-8036-3	94	84-1071	111	84-2037	63	84-2217	50	84-2415	38	84-2480	60
83-8037-3	94	84-1072	111	84-2041	63	84-2218	50	84-2416	38	84-2481	60
83-8051	97	84-1073	111	84-2047	62	84-2219	51	84-2417	38	84-2482	60

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
84-2483	60	84-2702	56	84-3001	50	84-4005	89	84-4511	41	84-6103-3	89
84-2484	60	84-2703	56	84-3002	50	84-4005-3	89	84-4513	41	84-6103-48	89
84-2485	60	84-2704	56	84-3003	50	84-4005-48	89	84-4550	41	84-6104	89
84-2486	60	84-2705	49	84-3004	50	84-4006	89	84-4624	41	84-6104-3	89
84-2487	60	84-2707	49	84-3005	50	84-4006-3	89	84-4625	41	84-6104-48	89
84-2488	60	84-2709	49	84-3006	50	84-4006-48	89	84-4997	145	84-6105	89
84-2489	60	84-2740	49	84-3007	50	84-4007	91	84-4998	145	84-6105-3	89
84-2490	60	84-2750	36	84-3008	50	84-4008	91	84-4999	145	84-6105-48	89
84-2491	60	84-2803	44	84-3009	50	84-4009	91	84-5000	145	84-6106	89
84-2492	60	84-2804	44	84-3010	50	84-4010	91	84-5002	145	84-6106-3	89
84-2493	60	84-2805	44	84-3011	50	84-4011	91	84-5003	145	84-6106-48	89
84-2494	61	84-2806	44	84-3012	50	84-4013	91	84-5004	145	84-6107	89
84-2495	61	84-2807	44	84-3013	50	84-4015	88	84-5005	145	84-6107-3	89
84-2501	38	84-2809	44	84-3014	50	84-4015-3	88	84-5006	87	84-6107-48	89
84-2502	49	84-2810	44	84-3015	50	84-4015-48	88	84-5006-3	87	84-7003	96
84-2504	49	84-2811	44	84-3016	50	84-4016	88	84-5006-48	87	84-7004	96
84-2505	49	84-2813	44	84-3017	50	84-4016-3	88	84-5007	87	84-7005	96
84-2507	49	84-2814	45	84-3018	50	84-4016-48	88	84-5007-3	87	84-7007	96
84-2509	49	84-2815	45	84-3019	50	84-4017	88	84-5007-48	87	84-7008	96
84-2510	38	84-2816	45	84-3020	50	84-4017-3	88	84-5008	87	84-7009	96
84-2511	38	84-2818	45	84-3021	50	84-4017-48	88	84-5008-3	87	84-7010	96
84-2512	38	84-2822	45	84-3022	50	84-4018	88	84-5008-48	87	84-7011	96
84-2513	38	84-2823	45	84-3100	47	84-4018-3	88	84-5009	87	84-7012	96
84-2514	46	84-2824	45	84-3101	47	84-4018-48	88	84-5009-3	87	84-7014	96
84-2518	39	84-2825	45	84-3102	47	84-4019	88	84-5009-48	87	84-7018	96
84-2520	39	84-2826	45	84-3110	47	84-4019-3	88	84-5010	91	84-7019	96
84-2521	39	84-2827	45	84-3111	47	84-4019-48	88	84-5011	91	84-7020	96
84-2532	51	84-2897	53	84-3112	47	84-4020	88	84-5012	91	84-7021	96
84-2534	51	84-2899	55	84-3150	36	84-4020-3	88	84-5013	91	84-7022	96
84-2536	51	84-2900	55	84-3182	56	84-4020-48	88	84-5014	91	84-7023	96
84-2537	51	84-2901	55	84-3187	53	84-4021	88	84-5015	91	84-7033	97
84-2538	51	84-2902	53	84-3191	53	84-4021-3	88	84-5016	91	84-7034	97
84-2540	49	84-2903	121	84-3350	36	84-4021-48	88	84-5019	91	84-7035	97
84-2550	36	84-2904	55	84-3382	56	84-4030	90	84-5020	91	84-8000	96
84-2580	46	84-2905	55	84-3387	52	84-4031	90	84-5021	91	84-8001	96
84-2581	55	84-2906	55	84-3391	52	84-4032	90	84-5022	91	84-8002	96
84-2582	55	84-2907	55	84-3550	36	84-4150	40	84-5023	91	84-8003	96
84-2583	55	84-2909	49	84-3582	56	84-4350	40	84-5024	91	84-8004	96
84-2587	53	84-2910	49	84-3587	53	84-4388	53	84-5025	91	84-8005	96
84-2590	46	84-2911	49	84-3591	53	84-4408	41	84-5029	87	84-8006	96
84-2591	53	84-2912	49	84-4000	89	84-4410	41	84-5030	87	84-8007	96
84-2592	46	84-2913	49	84-4000-3	89	84-4412	41	84-5031	87	84-8008	96
84-2612	44	84-2915	55	84-4000-48	89	84-4413	41	84-5032	87	84-8050	97
84-2614	44	84-2916	125	84-4001	89	84-4414	41	84-5033	87	84-8051	97
84-2618	44	84-2917	125	84-4001-3	89	84-4415	41	84-5034	87	84-8052	97
84-2624	37	84-2918	125	84-4001-48	89	84-4416	41	84-5035	87	84-9047	134
84-2625	37	84-2919	125	84-4002	89	84-4430	41	84-6010	134	84-9048	134
84-2626	37	84-2929	42	84-4002-3	89	84-4432	41	84-6011	134	84-9050	134
84-2627	37	84-2930	42	84-4002-48	89	84-4436	41	84-6100	89	84-9051	134
84-2628	37	84-2931	42	84-4003	89	84-4437	41	84-6100-3	89	84-9053	134
84-2629	37	84-2940	49	84-4003-3	89	84-4439	41	84-6100-48	89	84-9054	134
84-2630	37	84-2941	49	84-4003-48	89	84-4440	41	84-6101	89	84-9056	134
84-2631	37	84-2942	49	84-4004	89	84-4447	41	84-6101-3	89	84-9057	134
84-2632	37	84-2980	46	84-4004-3	89	84-4448	41	84-6101-48	89	84-9058	134
84-2701	56	84-3000	50	84-4004-48	89	84-4510	41	84-6103	89	84-9059	134

MODEL NUMBER INDEX

INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO



MODEL NUMBER INDEX

INDEX DES NUMÉROS DE PIÈCES • INDICE POR NÚMERO DE MODELO

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
84-9060	134	84-9169	137	84-9230-R	150	84-9274	149	84-9421	148	84-9512	139
84-9061	134	84-9170	137	84-9231	150	84-9275	149	84-9422	158	84-9513	139
84-9062	134	84-9171	137	84-9232	150	84-9276	146	84-9423	158	84-9514	139
84-9063	134	84-9172	137	84-9233	150	84-9277	146	84-9424	158	84-9515	139
84-9080 . . . 154, 174		84-9173	137	84-9233-R	150	84-9278	146	84-9425	156	84-9516	139
84-9082 . . . 154, 174		84-9174	137	84-9234	150	84-9279	146	84-9426	157	84-9517	139
84-9084 . . . 154, 174		84-9175	137	84-9234-R	150	84-9280	144	84-9427	158	84-9518	139
84-9085 . . . 154, 174		84-9176	137	84-9235	150	84-9281	144	84-9428	139	84-9519	139
84-9087 . . . 154, 174		84-9177	137	84-9236	150	84-9285	159	84-9429	139	84-9520	139
84-9088 . . 76, 155, 174		84-9178	137	84-9236-R	150	84-9286	159	84-9430	139	84-9521	139
84-9089 . . . 155, 174		84-9179	137	84-9237	150	84-9287	159	84-9431	139	84-9522	139
84-9090 . . . 155, 174		84-9180	137	84-9237-R	150	84-9288	159	84-9432	139	84-9523	138
84-9095	134	84-9181	137	84-9238	150	84-9289	143	84-9433	139	84-9524	138
84-9096	134	84-9182	137	84-9238-R	150	84-9290	155	84-9434	139	84-9525	138
84-9097	134	84-9183	143	84-9239	151	84-9304	148	84-9435	139	84-9527	138
84-9098	134	84-9184	143	84-9240	151	84-9305	148	84-9436	139	84-9528	138
84-9099	134	84-9185	143	84-9241	150	84-9306	148	84-9437	139	84-9529	139
84-9100	134	84-9186 . . . 143, 177		84-9242	150	84-9307	148	84-9438	139	84-9530	139
84-9101	135	84-9192	136	84-9242-R	150	84-9308	135	84-9439	139	84-9531	139
84-9103	135	84-9193	136	84-9243	150	84-9309	135	84-9440	139	84-9532	139
84-9105	135	84-9196	136	84-9244	150	84-9310	135	84-9442	135	84-9533	138
84-9106	135	84-9197	136	84-9244-R	150	84-9311	135	84-9443	135	84-9534	138
84-9108	135	84-9198	136	84-9245	150	84-9317	139	84-9445	143	84-9535	138
84-9109	135	84-9199	136	84-9245-R	150	84-9318	139	84-9448	135	84-9536	138
84-9110	135	84-9200	136	84-9246	150	84-9319	139	84-9449 . . . 65, 173		84-9537	138
84-9111	135	84-9201	136	84-9247	150	84-9320	159	84-9450	63	84-9538	139
84-9112	135	84-9202	136	84-9248	150	84-9321	144	84-9456	144	84-9539	139
84-9113	135	84-9203	136	84-9249	151	84-9322	144	84-9459	62	84-9540	145
84-9114	135	84-9204	136	84-9249-R	151	84-9323	153	84-9460	62	84-9541	141
84-9115	135	84-9205	136	84-9250	151	84-9324	153	84-9461	136	84-9542	141
84-9124	141	84-9206	136	84-9250-R	151	84-9325	153	84-9463	135	84-9543	144
84-9125	141	84-9207	136	84-9251	151	84-9326	153	84-9464	151	84-9544	144
84-9126	140	84-9208	136	84-9251-R	151	84-9327	153	84-9465	151	84-9545	139
84-9130	142	84-9209	136	84-9252	151	84-9328	153	84-9467	149	84-9546	139
84-9131	142	84-9210	136	84-9252-R	151	84-9331	146	84-9470	149	84-9547	138
84-9133	140	84-9211	136	84-9253	151	84-9361	150	84-9472	146	84-9548	135
84-9134	140	84-9216	143	84-9253-R	151	84-9361-R	150	84-9473	149	84-9550	146
84-9135	140	84-9217	143	84-9254	151	84-9365	150	84-9476	146	84-9551	144
84-9136	153	84-9218	136	84-9254-R	151	84-9365-R	150	84-9477	146	84-9552	135
84-9137	153	84-9219	136	84-9255	151	84-9367	150	84-9480	159	84-9553	135
84-9138	153	84-9220	136	84-9255-R	151	84-9367-R	150	84-9481	159	84-9554	135
84-9139	153	84-9221	136	84-9256	151	84-9371	150	84-9482	144	84-9555	135
84-9140	153	84-9222	136	84-9256-R	151	84-9371-R	150	84-9484	146	84-9556	135
84-9141	153	84-9223	136	84-9257	151	84-9372	150	84-9485	144	84-9557	135
84-9142	153	84-9224	150	84-9257-R	151	84-9375	150	84-9487	144	84-9558	135
84-9143	153	84-9225	150	84-9258	151	84-9375-R	150	84-9496	146	84-9559	151
84-9150	153	84-9225-R	150	84-9258-R	151	84-9376	150	84-9500-R	150	84-9561	90
84-9151	153	84-9226	150	84-9259	151	84-9377	151	84-9503	150	84-9562	90
84-9152	153	84-9226-R	150	84-9260	151	84-9377-R	151	84-9503-R	150	84-9563	90
84-9153	153	84-9227	150	84-9260-R	151	84-9382	151	84-9504	151	84-9564	90
84-9164	137	84-9228	150	84-9261	151	84-9388	151	84-9504-R	151	84-9565	90
84-9165	137	84-9228-R	150	84-9261-R	151	84-9401	149	84-9505	151	84-9566	90
84-9166	137	84-9229	150	84-9262	151	84-9402	149	84-9506	151	84-9567	146
84-9167	137	84-9229-R	150	84-9263	151	84-9403	149	84-9510	150	84-9571	150
84-9168	137	84-9230	150	84-9264	151	84-9420	148	84-9510-R	150	84-9572	150

PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE	PART #	PAGE
84-9576	151	84-9653	134	87052	5	87-6006	68	88-2931	42	88-9002	69
84-9577	151	84-9654	134	87100	5	87-6007	68	88-3100	47	88-9006	69
84-9579	149	84-9655	134	87101	4	87-6010	68	88-3101	47	88-9007	69
84-9580	141	84-9656	160	87103	4	87-6011	68	88-3102	47	88-9010	69
84-9581	141	84-9657	160	87104	4	87-7000	69	88-3110	47	88-9011	69
84-9582	148	84-9660	156	87105	4	87-7001	69	88-3111	47	88-9013	69
84-9583	148	84-9661	156	87110	5	87-7002	69	88-3150	36	88-9014	69
84-9584	148	84-9662	160	87111	5	87-7003	69	88-3350	36	89-3000	68
84-9585	148	84-9664	157	87112	5	87-7006	69	88-3387	52	89-3002	68
84-9586	148	84-9665	157	87113	5	87-7007	69	88-3391	52	89-4000	68
84-9587	148	84-9671	140	87170	4	87-7010	69	88-3550	36	89-4002	68
84-9593	143	84-9672	140	87171	4	87-7011	69	88-3587	53	89-4007	68
84-9599	143	84-9674	160	87172	4	87-7012	69	88-3591	53	89-5000	68
84-9600	151	84-9680	144	87173	4	87-7013	69	88-4000	89	89-5001	68
84-9601	151	84-9681	144	87180	4	87-7014	69	88-4001	89	89-5002	68
84-9602	151	84-9682	144	87181	4	87-8000	69	88-4002	89	89-5006	68
84-9603	151	84-9683	144	87182	5	87-8001	69	88-4003	89	89-5007	68
84-9604	151	84-9684	144	87190	4	87-8002	69	88-4004	89	89-5010	68
84-9605	151	84-9685	159	87191	4	87-8003	69	88-4005	89	89-5011	68
84-9606	151	84-9690	148	87192	4	87-8006	69	88-4006	89	89-6000	68
84-9607	151	84-9691	148	87193	4	87-8007	69	88-4150	40	89-6001	68
84-9608	151	84-9692	148	87-0000	71	87-8010	69	88-4350	40	89-6002	68
84-9610	142	84-9693	148	87-0002	71	87-8011	69	88-4550	40	89-6006	68
84-9611	142	84-9694	148	87-1000	95	87-8012	69	88-5000	68	89-6007	68
84-9612	143	84-9695	148	87-1001	95	87-8013	69	88-5002	68	89-6010	68
84-9613	145	85-6018	80	87-1002	95	87-8014	69	88-5007	68	89-6011	68
84-9614	145	85-6019	80	87-1007	95	87-9000	69	88-6000	68	89-7000	69
84-9615	145	85-6020	80	87-1008	95	87-9001	69	88-6001	68	89-7001	69
84-9616	145	85-6021	80	87-2000	71	87-9002	69	88-6002	68	89-7002	69
84-9618	140	85-6023	81	87-2001	71	87-9003	69	88-6006	68	89-7006	69
84-9621	144	85-6025	80	87-2002	71	87-9006	69	88-6007	68	89-7007	69
84-9622	144	85-6026	80	87-2007	71	87-9007	69	88-6010	68	89-7010	69
84-9624	142	85-6028	80	87-2010	69	87-9010	69	88-6011	68	89-7011	69
84-9626	144	85-6029	80	87-2012	69	87-9011	69	88-7000	69	89-7012	69
84-9627	144	85-6030	82	87-2015	69	87-9012	69	88-7001	69	89-8000	69
84-9628	144	85-6031	82	87-2016	71	88-2002	62	88-7002	69	89-8001	69
84-9629	159	85-6032	82	87-2017	69	88-2081	62	88-7006	69	89-8002	69
84-9630	144	85-6033	82	87-2018	71	88-2082	62	88-7007	69	89-8006	69
84-9631	144	85-6034	82	87-2020	71	88-2180	46	88-7010	69	89-8007	69
84-9632	144	85-6035	82	87-3000	68	88-2303	48	88-7011	69	89-8010	69
84-9633	144	85-6036	82	87-3002	68	88-2304	48	88-7012	69	89-8011	69
84-9634	144	85-6040	81	87-4000	68	88-2305	48	88-7013	69	89-8012	69
84-9635	136	85-6041	81	87-4002	68	88-2379	55	88-8000	69	89-9000	69
84-9636	136	85-6042	82	87-4007	68	88-2380	46	88-8001	69	89-9001	69
84-9637	136	85-6043	82	87-5000	68	88-2383	55	88-8002	69	89-9002	69
84-9640	134	85-6060	84	87-5001	68	88-2387	52	88-8003	69	89-9006	69
84-9641	134	85-6061	84	87-5002	68	88-2390	46	88-8006	69	89-9007	69
84-9642	134	85-6062	84	87-5006	68	88-2391	52	88-8007	69	89-9010	69
84-9647	134	85-6063	84	87-5007	68	88-2580	46	88-8010	69	89-9011	69
84-9648	134	85-6104	81	87-5010	68	88-2612	44	88-8011	69	920273	16
84-9649	134	85-6120	81	87-5011	68	88-2614	44	88-8012	69	99170	16, 177
84-9650	134	85-6163	81	87-6000	68	88-2618	44	88-8013	69	99170-1	16, 177
84-9651	134	87020	5	87-6001	68	88-2929	42	88-9000	69	99180	16, 177
84-9652	134	87023	5	87-6002	68	88-2930	42	88-9001	69		

01

POWER CORDS

CORDONS D'ALIMENTATION

CABLES DE ENERGÍA


- 4 ABS Power Cords
- 5 Non-ABS Power Cords
- 6 RV Power Cords
- 7 ISO Cords
- 7 Lift Gate Cables

GROTE ULTRALINK™ POWER CORDS

SUPERIOR CORDS THAT PROVIDE MAXIMUM RELIABILITY IN THE HARSHTEST ENVIRONMENTS

PLUG DESIGN

- Solid brass nickel-plated pins
- Crush resistant weather-tight elastomeric material



CABLE-TO-PLUG SEAL

Wire jacket is molded into the plug sealing it from the elements and eliminating the need for a spring



CRUSH RESISTANT

Grote's UltraLink's crush-resistant design can survive being run over by a heavy duty vehicle while conventional hollow core designs are permanently deformed and rendered useless.



- Grote UltraLink Power Cords exceed minimum legal lamp power delivery requirements for single or double trailer configurations.
- UltraLink zinc die-cast plugs are filled with elastomeric material that resists crushing and acts as potting to seal solid brass terminals from moisture.
- A special adhesive bonds the cable to the plug, eliminating the need for a supporting spring and preventing moisture from entering the back of the plug.
- Coiled versions have excellent recoil memory, plus chemical and abrasion resistance.
- Solid brass terminals are corrosion resistant, and provide superior current capacity with minimal voltage drop.
- Premium ABS cords' advanced polymer jacketing material provides complete sealing and abrasion protection between -55°F and 190°F.
- Grote UltraLink Power Cords meet SAEJ560, J2394 (ABS cords), and J2222 (coiled cord versions).

Grote's Got It!

ABS POWER CORDS



87105



87100



87101



87190



87171

ULTRALINK™

- UltraLink™ power cords exceed minimum legal lamp power delivery requirements for single or double trailer configurations
- Zinc die-cast plugs are filled with elastomeric material that resists crushing & acts as potting to seal solid brass terminals from moisture
- Provides excellent recoil memory, chemical, and abrasion resistance
- Adhesive bonds cable to plug, eliminating need for supporting spring and preventing moisture from entering the back of the plug
- Solid brass terminals are corrosion resistant, and provide superior current capacity with minimal voltage drop
- Advanced polymer jacketing material provides complete sealing and abrasion protection between -55°F and 190°F (Premium Versions)

COILED PREMIUM ABSULTRALINK™

PART #	LENGTH	LEADS	JACKET MATERIAL & GAUGE	JACKET	PACK
87104	15'	12"	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87105	20'	12" & 36"	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1

COILED ABSULTRALINK™

PART #	LENGTH	LEADS	JACKET MATERIAL & GAUGE	JACKET	PACK
87100	12'	12"	ABS, 1/8, 2/10, 4/12 GA	Green	1
87101	15'	12"	ABS, 1/8, 2/10, 4/12 GA	Green	1
87170	15'	12" & 48"	ABS, 1/8, 2/10, 4/12 GA	Green	1

STRAIGHT PREMIUM ABSULTRALINK™

PART #	LENGTH	JACKET MATERIAL & GAUGE	JACKET	PACK
87190	7'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87191	8'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87192	9'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87171	12'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87172	15'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1
87173	20'	Premium ABS, 1/8, 2/10, 4/12 GA	Green	1

UltraLink™

SEE PAGE 3 TO LEARN MORE ABOUT THE BENEFITS OF USING GROTE'S SUPERIOR ULTRALINK CABLES.

ULTRALINK™

- UltraLink™ power cords exceed minimum legal lamp power delivery requirements for single or double trailer configurations
- Zinc die-cast plugs are filled with elastomeric material that resists crushing & acts as potting to seal solid brass terminals from moisture
- Adhesive bonds cable to plug, eliminating need for supporting spring and preventing moisture from entering the back of the plug
- Solid brass terminals are corrosion resistant, and provide superior current capacity with minimal voltage drop

COILED NON-ABS, 1/10, 6/12 GAULTRALINK™

PART #	LENGTH	LEADS	JACKET MATERIAL & GAUGE	JACKET	PACK
87020	12'	12"	Non ABS, 1/10, 6/12 GA	Black	1
87023	15'	12"	Non ABS, 1/10, 6/12 GA	Black	1
87180	15'	12" & 72"	Non ABS, 1/10, 6/12 GA	Black	1
87181	15'	12" & 48"	Non-ABS, 1/10, 6/12 GA	Black	1

COILED NON-ABS, 1/12, 6/14 GAULTRALINK™

PART #	LENGTH	LEADS	JACKET MATERIAL & GAUGE	JACKET	PACK
87110	12'	12"	Non ABS, 1/12, 6/14 GA	Black	1
87111	15'	12"	Non ABS, 1/12, 6/14 GA	Black	1
87112	15'	12" & 72"	Non ABS, 1/12, 6/14 GA	Black	1
87113	15'	12" & 48"	Non ABS, 1/12, 6/14 GA	Black	1

STRAIGHT NON-ABSULTRALINK™

PART #	LENGTH	JACKET MATERIAL & GAUGE	JACKET	PACK
87052	12'	Non-ABS, 1/10, 6/12 GA	Black	1
87182	15'	Non-ABS, 1/10, 6/12 GA	Black	1

NON-ABS POWER CORDS



87020



87180



87111



87052



87182

Did You Know?



ONE OF THE MOST COMMON CAUSES OF ELECTRICAL FAILURE IS CORROSION!

Grote's Ultra-Seal corrosion preventive sealant is a key part of protecting any plug and socket connection.

- Ultra-Seal provides an economical and reliable protection from dirt, salt, water and other harmful chemicals that can cause costly downtime.
- See page 16 for Ultra-Seal products

POWERCOILS



81-0612



81-0412

- Commonly used in recreational vehicle (R.V.) applications (boat, snowmobile, utility trailers)
- Cords are manufactured with extremely flexible material and can withstand extreme temperatures. Rated at -65°C (-85°F)
- Ultra violet and harmful chemical resistant
- Extended springs for superior plug support

6-WAY

PART #	LENGTH	LEADS	STYLE	GAUGE	JACKET	PACK
81-0610	10'	12"	Coiled	6/14 GA	Black	1
81-0612	12'	12"	Coiled	6/14 GA	Black	1

4-WAY

PART #	LENGTH	LEADS	STYLE	GAUGE	JACKET	PACK
81-0410	10'	12"	Coiled	4/14 GA	Black	1
81-0412	12'	12"	Coiled	4/14 GA	Black	1

POWER CORD/GLADHAND SUPPORT HOLDER



81-0141



81-0142

- Provides protection & easy storage of electrical cables and air lines when not in use
- High impact material designed to withstand all elements

PART #	DESCRIPTION	PACK SIZE
81-0141	3 Function – 1 power cord and 2 gladhands	1
81-0142	4 Function – 2 power cord and 2 gladhands	1

- Most commonly used for tanker, reefer, and live-bottom trailer applications, these cables are perfectly suited to deliver auxiliary power for any trailer or equipment need
- These cables can provide power for up to six additional circuits
- Heavy duty die-cast, ISO plugs
- Inverted male ground pin to prevent improper connection
- 1/8, 2/10, 4/12 Gauge 100% copper cable
- Yellow ABS cable meets SAE J2222 specifications; Plug and socket meet SAE J560
- Excellent recoil memory
- Replacement plug and socket also available (82-1044, 82-1043)

Specifications

Plug: SAE J560

Cable: SAE J222 (Coiled)

Cord: 1/8 GA, 2/10 GA, 4/12 GA

PART #	DESCRIPTION
81-2012-S	ISO Auxiliary, Straight Cord 12', Yellow
81-2015	ISO Auxiliary, Coiled Cord 15', w/12" Leads, Yellow
81-2015-40	ISO Auxiliary, Coiled Cord 15', w/40" Leads, Yellow
81-2015-S	ISO Auxiliary, Straight Cord 15', Yellow

- Ideal for lift gates, roll-tops, and remote battery-charging applications
- Available in single pole, single-to-dual pole, dual pole, and dual pole with vertical pins
- Die-cast zinc plugs
- External ground – 4 gauge
- Fine stranded copper wire provides maximum flexibility
- Temperature rating -65°C to (-85°F); Single Pole
- 200 AMP carrying capacity

Specifications

Cord: 4 GA, 200A (Carrying Capacity)

Copper Stranding: Fine

Operating Range: -40°F to 174°F / -40°C to 79°C

PART #	DESCRIPTION
81-2112	Lift Gate, Coiled Cord, Single Pole, 12', w/12" Leads, Green
81-2115	Lift Gate, Coiled Cord, Single Pole, 15', w/12" Leads, Green
81-2212	Lift Gate, Coiled Cord, Dual Pole, 12', w/12" Leads, White/Black
81-2212-V	Lift Gate, Coiled Cord, Dual Pole Vertical Pins, 12', w/12" , White/Black
81-2215	Lift Gate, Coiled Cord, Dual Pole, 15', w/12" Leads, White/Black
81-2215-DS	Lift Gate, Coiled Cord, Dual & Single Pole, 15', w/12" Leads, White/Black
81-2215-V	Lift Gate, Coiled Cord, Dual Pole Vertical Pins, 15', w/12" Leads, White/Black
81-2312	Lift Gate, Straight Cord, Single Pole, 12', Green
81-2315	Lift Gate, Straight Cord, Single Pole, 15', Green
81-2412	Lift Gate, Straight Cord, Dual Pole, 12', White/Black
81-2415	Lift Gate, Straight Cord, Dual Pole, 15', White/Black

ISO AUXILIARY CABLES



81-2015

81-2015-S



LIFT GATE CABLES



81-2215

81-2215-V

81-2115

81-2312

81-2415

02

TRAILER CONNECTORS

CONNECTEURS
POUR REMORQUES

CONECTORES PARA
TRAILERS Y REMOLQUES

- 10 Trailer Sockets
- 11 Nose Boxes & Socket Breakers
- 12 Trailer Plugs
- 16 Junction Boxes
- 16 Corrosion Preventive Sealant

GROTE'S TRAILER CONNECTORS AND
COMMUNICATION PRODUCTS ENSURE
SUFFICIENT POWER IS DELIVERED
TO THE ENTIRE VEHICLES LIGHTING
AND SAFETY SYSTEM.



HEAVY DUTY 7 POLE SOCKETS

SAE
INTERNATIONAL
SAE J560™
STANDARD



82-1002

- Die-cast housing for superior corrosion resistance
- Solid brass pin terminals for best conductivity
- Meets and exceeds SAE J560 specifications
- Terminals accept 16-10 gauge wires; 8 gauge ground wire
- Sloped socket barrel allows for moisture drainage
- 40 AMP @ 6-28V DC
- 2, 1/2" mounting holes
- Circuit identification on the back of the socket
- Female ground pin for (ISO) to prevent improper connections



82-2145



82-1043

#	COLOR	CIRCUITS	RECOMMENDED WIRE GAUGE
1	White	Ground Return	8 GA
2	Black	Clearance, Side Marker and Identification Lamps	12 GA
3	Yellow	Left Turn Signal & Hazard Signal	12 GA
4	Red	Stop Lamps & Anti-Lock Devices	10 GA
5	Green	Right Turn Signal & Hazard Signal	12 GA
6	Brown	Tail, Rear Clearance, Marker and License Plate Lamps	12 GA
7	Blue	Auxiliary Circuit/ABS	10 GA

SOCKET #	MATERIAL	TERMINALS	PART #
7	Zinc Die-Cast	Enclosed, split pin	82-1002
7	Zinc Die-Cast	Exposed, solid pin	82-1005
7	Nylon	Enclosed, solid pin	82-2145
7	Nylon	ISO Socket	82-1043

7 POLE R.V. SOCKETS



82-1058

- Made of lightweight, high impact nylon
- Socket lid has a slot for proper drainage, tin plated copper alloy terminals
- 82-1060 fits Ford style and universal mount brackets
- Easy twist-in and lock assembly for factory installed brackets & hitches
- Fits GM and Nissan trucks and SUV's



82-1060



82-1059

NO.	COLOR	CIRCUIT	RECOMMENDED WIRE GAUGE
1	White	Ground Return	10 GA
2	Blue	Electric Brake	12 GA
3	Green	Tail, License, Running Lights	14 GA
4	Black	Battery Charge	10 GA
5	Red	Stop & Left Hand Turn Signal	14 GA
6	Brown	Stop & Right Hand Turn Signal	14 GA
7	Yellow	Auxiliary Circuit	14 GA

SOCKET #	MATERIAL	DESCRIPTION	PART #
7	Nylon	R.V. Socket Only	82-1058
7	Nylon	R.V. Socket Only	82-1060*
7	Nylon	R.V. Plug & Socket Kit (includes 82-1056 & 82-1058)	82-1050
7	Nylon	Twist-In & Lock Socket	82-1059*

* See page 12 for Harness Adapters

COMBINATION 7 WAY & 4 POLE SOCKETS

- Combines an R.V. 7 way and 4 pole flat socket connection into one part (not to be used simultaneously)
- Easy snap-in assembly designed for truck and sport utility vehicles and when hauling multiple trailers
- Eliminates the need for an adapter; mounting bracket included
- Will plug into any Ford or GM vehicle built after 2001 (selected Nissan models 2004+)

PLUG #	MATERIAL	DESCRIPTION	PART #
7	Nylon	7 Way R.V. and 4 Pole Flat w bracket	82-1055
7	Nylon	7 Way R.V. and 4 Pole Flat	82-1055NB



82-1055NB



82-1055

PLUG AND SOCKET BOOT

PLUG / SOCKET #	DESCRIPTION	PART #
7	Plug Boot – complete protection	82-2142
7	Socket Boot – complete protection	82-2144



82-2142



82-2144

7- WAY SOCKET BREAKERS

- Heavy duty die-cast material; Meets SAE J560 specifications

PART #	RATED	DESCRIPTION
82-0855	20 AMP	Split Pin, Metal Breakers
82-0856	30 AMP	Split Pin, Metal Breakers
82-0853		Split Pin, Without Breakers



82-0855

SAE
INTERNATIONAL
SAE J560™
STANDARD

NOSEBOXES

- Fits standard mounting hole patterns
- Includes mounting hardware, grommet and gasket

PART #	DESCRIPTION	DIMENSIONS	MATERIAL
82-0861	Deep Nose Box	3 1/2"	Nylon
82-0859	Deep Nose Box	3 1/8"	Die-Cast
82-0860	Low Profile Nose Box	1 7/8"	Die-Cast
82-0850*	Low Profile Nose Box	1 7/8"	Die-Cast

* Includes 20A Split-Pin Socket Breaker



82-0860



82-0850



82-0861



82-0859

HEAVY DUTY 7 POLE PLUGS

SAE
INTERNATIONAL
SAE J560™
STANDARD



- Die-cast housing for superior corrosion resistance
- Meets and exceeds SAE J560 specifications
- Plated steel cable guard prevents cable chafing
- Circuit identification on the back of the plug insert
- Male ground pin for (ISO) to prevent improper connection with standard 7 pole plugs

PLUG #	MATERIAL	DESCRIPTION	PART #
7	Zinc Die-Cast	Plug only	82-1001
7	Nylon	Plug only	82-2140
7	Zinc Die-Cast	Plug w/Guard Spring	82-1019
7	Stainless Steel	Guard Spring only	82-2141
7	Die-Cast	ISO plug w/Guard Spring	82-1044

7 POLE R.V. PLUGS



- Made of lightweight, high impact nylon

PLUG #	MATERIAL	DESCRIPTION	PART #
7	Nylon	R.V. Plug Only	82-1056
7	Nylon	R.V. Plug & Socket Kit (includes 82-1056 & 82-1058)	82-1050

STEP-DOWN R.V. ADAPTERS



- Provides 6 & 7 pole trailer plug to allow 4, 5 and 6 pole conversion
- Made of lightweight, nylon material for superior corrosion resistance
- Ideal for boat trailers, campers and utility vehicles

PLUG#	MATERIAL	DESCRIPTION	PART #
7	Nylon	7 Way RV to 4 Pole Flat	82-2146
7	Nylon	7 Way RV to 5 Pole Flat	82-2148
7	Nylon	7 Way RV to 6 Pole Round, Ctr Pin, Brake	82-2149
7	Nylon	7 Way RV to 6 Pole Round, Ctr Pin, Auxiliary	82-2154
6	Nylon	6 Pole Round to 4 Pole Flat	82-2147

* See page 10 for Socket Connectors

ADAPTERS



* See page 10 for Socket Connectors

82-1063 | T CONNECTOR (FOR 5TH WHEEL & BUMPER MOUNT SOCKET)

- Plug & play without splicing into existing OEM harness
- Fits GM & Ford trucks/SUV's; Chrysler trucks/SUV's w/ 82-1062 adapter

82-1062 | RECTANGULAR-TO-ROUND HARNESS ADAPTER

- Adapter for OEM harnesses
- Mates w/ Grote socket # 82-1060, 82-1055, 82-1059, T-Connector #82-1063

82-1061 | HARNESS EXTENSION ADAPTER

- Adapter mates with socket # 82-1060, 82-1055
- 4' harness extension plugs into existing socket & splices into OEM harness

HEAVY DUTY 6 POLE SOCKETS



- Die-cast housing for superior corrosion resistance
- Solid brass pin terminals for best conductivity
- Terminals accepts up to 12 gauge wires
- 2, 1/2" mounting holes; Stainless steel spring
- Circuit identification on the back of the socket

SOCKET #	MATERIAL	TERMINALS	PART #
6	Zinc Die-Cast	Enclosed, split pin	82-1016

PLUG/SOCKET #	DESCRIPTION	PART #
6	Socket Boot – Complete protection	82-1012

NO.	COLOR	CIRCUITS
1	White	Ground Return
2	Brown	Tail Lights
3	Yellow	Left Turn
4	Red	Stop
5	Green	Right Turn
6	Blue	Auxiliary Circuit

HEAVY DUTY 6 POLE PLUGS



- Die-cast housing for superior corrosion resistance
- Plated steel cable guard prevents cable chafing
- Circuit identification on the back of the plug insert

PLUG #	MATERIAL	DESCRIPTION	PART #
6	Zinc Die-Cast	Plug only	82-1011
6	Zinc Die-Cast	Plug with Guard Spring	82-1010

HEAVY DUTY 4 POLE SOCKETS



SOCKET #	MATERIAL	TERMINALS	PART #
4	Zinc Die-Cast	Enclosed, split pin	82-1020

PLUG & SOCKET KIT	MATERIAL	TERMINALS	PART #
4	Zinc Die-Cast	Enclosed, split pin	82-1040

(includes 82-1020 & 82-1021)

NO.	COLOR	CIRCUITS
1	White	Ground Return
2	Green	Right Turns & Brake Lights
3	Yellow or Red	Left Turn & Brake Lights
4	Brown	Tail Lights

HEAVY DUTY 4 POLE PLUGS



PLUG #	MATERIAL	DESCRIPTION	PART #
4	Zinc Die-Cast	Plug with Guard Spring	82-1022
4	Zinc Die-Cast	Plug	82-1021
4	Stainless Steel	Guard Spring	82-1023

MOLDED CONNECTOR ASSEMBLIES

- PVC sleeve provides ultimate protection; Split pin terminals
- 20 AMP @ 12-24V DC

DESCRIPTION	PART #
2 Pole Molded Connector Assembly	82-1027
4 Pole Molded Connector Assembly	82-1025



LIFT GATE – CHARGING PLUGS & SOCKETS



- Designed for lift gate applications and as an alternative power source
- Solid brass pin terminals for best conductivity
- 2, 1/2" mounting holes; stainless steel spring
- Terminals accepts 4 gauge cable
- 200 AMP heavy die-cast construction

SOCKET

PART #	SOCKET #	DESCRIPTION	MATERIAL
82-1041	2	Socket – Dual Pole	Zinc Die-Cast
82-0851	1	Socket – Single Pole	Zinc Die-Cast
82-2144		Socket Boot	Rubber

PLUG

PART #	PLUG #	DESCRIPTION	MATERIAL
82-1042	2	Plug & Guard Spring – Dual Pole	Zinc Die-Cast
82-0852	1	Plug & Guard Spring – Single Pole	Zinc Die-Cast

PLUG & SOCKET COMBO

PART #	PLUG/SOCKET#	DESCRIPTION	MATERIAL
82-0950	1	Plug & Socket – Single Pole	Zinc Die-Cast

DUMP TRUCK & TARP TRAILER PLUGS & SOCKETS



VERTICAL PIN

- Designed for dump truck, tarp and grain trailer applications; also alternative power source
- Solid brass pin terminals for best conductivity
- 2, 1/2" mounting holes; stainless steel spring
- Terminals accepts 4 gauge cable(s)
- 200 AMP heavy die-cast construction
- Vertical pin plug/socket = set screw termination

SOCKET

PART #	SOCKET #	DESCRIPTION	MATERIAL
82-1041V	2	Socket – Dual Pole	Zinc Die-Cast
82-2144		Socket Boot	Rubber


PLUG

PART #	PLUG #	DESCRIPTION	MATERIAL
82-1042V	2	Plug & Guard Spring – Dual Pole	Zinc Die-Cast

MOLDED TRAILER CONNECTORS



- Automotive, marine, recreational and truck applications
- PVC wire
- Operating temperature 105°C (221°F)
- Weather resistant molded head
- Male = vehicle end, female = trailer end



PLUG #	GAUGE	CONNECTOR HEAD	LENGTH	WIRE COLORS	CONNECTOR END	PART #
6	16	Square	12"	White, Yellow, Brown, Green, Blue, Black	Male & Female	82-1028
5	16	Flat	12"	White, Yellow, Brown, Green, Blue	Male & Female	82-1029
4	18	Square	12"	White, Yellow, Brown, Green	Male & Female	82-1036
4	16	Flat	12"	White, Yellow, Brown, Green	Male & Female	82-1030
4	16	Flat	6"	White, Yellow, Brown, Green (blunt cut)	Female	82-1031
4	16	Flat	6"	White, Yellow, Brown, Green (blunt cut)	Male	82-1032
3	16	Flat	12"	White, Yellow, Brown	Male & Female	82-1033
2	16	Flat	12"	White, Yellow	Male & Female	82-1034
2	16	Flat	24"	White, Red	Male & Female	82-1038
2	12	Flat	12"	White, Black	Male & Female	82-1039
2	10	Flat	12"	White, Black	Male & Female	82-1035

MOUNTING BRACKETS



- Can accommodate from 4 pole up to 9 pole socket requirements
- Made of anti-corrosive steel, painted black

PLUG #	MATERIAL	DESCRIPTION	PART #
4, 5, 6	Steel	4, 5 and 6 pole socket bracket	43942
7, 9	Steel	7 and 9 pole socket bracket	43402
4, 6, 7	Steel	4, 6 and 7 pole socket bracket	82-1052

PROTECTIVE CAP – 7 POLE PLUGS

- Protective cap for 7 pole plugs
- Heavy duty glass-filled plastic housing
- Spring-loaded for secure locking
- Keeps plugs clean when not in use
- Protects the electrical contacts from dirt and moisture
- 2 mounting holes

PART #	MATERIAL	DESCRIPTION	PLUG #
82-1051	Plastic	Protective cap for 7 pole plugs	7



SEVEN TERMINAL JUNCTION BOX



- Corrosion resistant molded cover and housing
- Two-bolt mounting 7 3/8" (18.73) centre to centre
- Access slot grommets included, four open-four closed
- 7, #10-32 studs

82-1000

DRI-SEAL CIRCUIT BOX



- Entrances stay dry by using the new "push-in" choke seals and threaded fittings – comes with 4 choke seals
- 18 brass circuit studs and full hardware; entry from 4 sides
- All components are corrosion resistant
- Numbered label for fast circuit I.D.
- No tools: easy access by 4 wing nut fasteners (retained in the cover)
- Ample area for wire and cable – 1 cable entrance fitting

351044

7-WAY SYSTEM CHECKER



- Solid brass pin
- LED light source
- Lexan housing

920273

CLEANING BRUSH – 7 POLE PLUGS & SOCKETS



- Engineered to properly fit 7 pole plugs and sockets
- Removes any unwanted corrosion build up
- Easily stored in a tool box or maintenance kit
- Stainless steel bristles and heavy duty plastic housing

PART #	MATERIAL	DESCRIPTION	PLUG / SOCKET #
83-6561	Plastic	Plastic housing w/ steel bristles	7

ULTRA-SEAL CORROSION PREVENTIVE SEALANT DISPLAY



- Prevents rust and corrosion
- Added tackifiers improve adhesion and resistance to washout
- Operating range -40°C (-40°F) to 150°C (302°F)
- Ideal for heavy-duty, automotive, agricultural, marine, industrial and recreational applications

PART #	DESCRIPTION
99170-1	Display (includes 12 - 4 oz. tubes # 99170)
99170	4 oz. Tube
99180	8 oz. Tub with applicator

G24/7

ONLINE CUSTOMER SERVICE PLATFORM

For existing customers, this **COMPLIMENTARY SERVICE** is an innovative way to place orders, track order status and view all your Grote® product activity. From the convenience of your computer or mobile device, you can now access previously unavailable information that will help you more successfully manage your business and inventory.



NEW FEATURES

- Pay invoices online any time; easy credit card processing
- Reprint packing lists and invoices
- Order entry online by customer part number
- Upload from Microsoft® Excel
Customers can also upload items from Microsoft Excel to create orders
- Refer and reorder using "My List"
The user can create a list of products for future reference or to reorder
- E-mail notification
When a new order is created and when an order is shipped, unlimited recipients can receive an instant e-mail notification.



USING G24/7, YOU CAN QUICKLY & EASILY

- Track the status of current orders
- Check the status of backorders
- Check for substitutions, replacements for obsolete parts
- Check Grote inventory availability
- Confirm ship dates
- Link to shipping carrier
- View invoice information
- Track credits
- View weight and packaging information
- View previously placed orders
- View product technical information
- Reprint packing lists and invoices



CONTACT US

CALL US AT 1-800-268-5612, OR CHECK OUT OUR G24/7 ONLINE CUSTOMER SERVICE PLATFORM AT SHOP.GROTE.COM

03

AIR PRODUCTS

PRODUITS D’AIR

PRODUCTOS DE AIRE

- 20 Coiled Air
- 22 Gladhands
- 24 Seals and Airline Accessories
- 25 Rubber Air Lines
- 26 Power Cord & Air Assemblies
- 28 Suspension Products
- 30 EZ Claw® Suspension System
- 31 Air Brake Tubing

GROTE CARRIES AN EXTENSIVE LINE OF AIR PRODUCTS REQUIRED FOR OPTIMUM SYSTEM PERFORMANCE.

FROM POWER CORD AND AIR ASSEMBLIES TO SEALS AND SCREENS, OUR AIR PRODUCTS ARE DESIGNED AND MANUFACTURED TO MEET OR EXCEED THE TOUGHEST INDUSTRY STANDARDS.

- Grote’s 3-IN-1 Ultralink™ Power Cord and Air Assemblies are proudly made in North America
- Our hoses are designed to withstand harsh conditions including extreme temperatures and harmful chemicals, our “Low Temperature” products are even more rugged
- We offer tightly coiled air tubing assemblies that provide excellent recoil memory, while minimizing sagging or kinking to ensure a long service life
- Grote’s exclusive EZ Claw System is the premier automatic suspension system for protecting power cords, airlines, and hydraulic hoses
- We go the extra mile, with heavy gauge steel springs to provide superior cable support, thread sealant added to all brass connectors for a leak-free seals, and high quality 1/2" NPT DOT brass fittings that come standard on all models
- Remember: when it comes to air products, Red = Emergency; Blue = Service





THE GROTE ADVANTAGE

Grote’s coiled air hoses are designed to withstand harsh conditions including extreme temperatures and harmful chemicals. The tightly coiled tubing provides excellent recoil memory while minimizing sagging or kinking.



Extremely flexible air tubing has **excellent recoil memory** even under extreme temperatures



Brass handle for **easy coupling and uncoupling**



Swivel fittings, extra-long spring and thread sealant provide **additional strain relief** and ensure an **air tight connection**

LOW TEMPERATURE COILED AIR



- Low temperature, double-jacketed coils remain flexible in extremely cold temperatures
- Operating temperature of -65°C (-85°F) to 104°C (220°F)
- Nylon Hose meets SAE J844, DOT FMVSS (49 CFR 571.106) & FMCSA (393.45) specifications
- Includes a swivel fitting for the tractor-end connection
- Brass handle enables a solid grip for coupling/uncoupling hoses



PART #	COLOR	WORKING LENGTH	LEADS	PACK
12'				
81-0012-C	Red & Blue	12'	6"	2
81-0012-CGH*	Red & Blue	12'	6"	2
15'				
81-0015-C	Red & Blue	15'	12"	2
81-0015-RC	Red	15'	12"	1
81-0015-BC	Blue	15'	12"	1
81-0015-CGH*	Red & Blue	15'	12"	2
81-0015-40C	Red & Blue	15'	12" & 40"	2
81-0015-40RC	Red	15'	12" & 40"	1
81-0015-40BC	Blue	15'	12" & 40"	1
20'				
81-0020-C	Red & Blue	20'	12"	2
81-0020-RC	Red	20'	12"	1
81-0020-BC	Blue	20'	12"	1

* Includes Red & Blue Gladhands

- Nylon Hose meets SAE J844, DOT FMVSS (49 CFR 571.106) & FMCSA (393.45) specifications
- Operating temp: -40°C (-40°F) to 104°C (220°F), Brass handle for solid grip (coupling/uncoupling)

PART #	COLOR	WORKING LENGTH	LEADS	PACK
12'				
81-0012-H	Red & Blue	12'	6"	2
81-0012-HR	Red	12'	6"	1
81-0012-HB	Blue	12'	6"	1
15'				
81-0015-H	Red & Blue	15'	12"	2
81-0015-HR	Red	15'	12"	1
81-0015-HB	Blue	15'	12"	1
81-0015-HGH*	Red & Blue	15'	12"	2
81-0015-40H	Red & Blue	15'	12" & 40"	2
81-0015-40HR	Red	15'	12" & 40"	1
81-0015-40HB	Blue	15'	12" & 40"	1
81-0015-40HGH*	Red & Blue	15'	12" & 40"	2

COILED AIR WITH BRASS HANDLE



* Includes Red & Blue Gladhands

- Nylon Hose meets SAE J844, DOT FMVSS (49 CFR 571.106) & FMCSA (393.45) specifications
- Operating temp: -40°C (-40°F) to 104°C (220°F), Swivel fittings on both ends for easy hook-up

PART #	COLOR	WORKING LENGTH	LEADS	PACK
8'				
81-0008	Red & Blue	8'	6"	2
81-0008-R	Red	8'	6"	1
81-0008-B	Blue	8'	6"	1
12'				
81-0012	Red & Blue	12'	6"	2
81-0012-R	Red	12'	6"	1
81-0012-B	Blue	12'	6"	1
81-0012-GH*	Red & Blue	12'	6"	2
15'				
81-0015	Red & Blue	15'	12"	2
81-0015-R	Red	15'	12"	1
81-0015-B	Blue	15'	12"	1
81-0015-GH*	Red & Blue	15'	12"	2
81-0015-40	Red & Blue	15'	12" & 40"	2
81-0015-40R	Red	15'	12" & 40"	1
81-0015-40B	Blue	15'	12" & 40"	1
20'				
81-0020	Red & Blue	20'	12"	2
81-0020-R	Red	20'	12"	1
81-0020-B	Blue	20'	12"	1

COILED AIR



* Includes Red & Blue Gladhands

- 54" air hose w/ 1/4" NPT male brass connectors, Nylon 1/4" tubing meets SAE J844 Type A spec
- Includes swivel fittings & heavy duty springs on both ends for easy installation, added strain relief

PART #	DESCRIPTION	PACK
81-0054	54", 5th wheel air hose with dual swivel and springs	1

5TH WHEEL SLIDER HOSE



GLADHANDS



STANDARD & ANGLED

- Meets or exceed SAE J318 standards
- Aluminum castings with powder-coated steel clasp plates (service and emergency)
- Permanent clamp screws; Includes a large face rubber seal
- Polarized emergency and service gladhands
- Replacement seals available in rubber or polyethylene
- Port “A” comes standard as unplugged – 38° gladhands

PART #	MATERIAL	DESCRIPTION	COLOR	SCREEN	PACK
81-0001	Aluminum	Universal	—	No	1
81-0001-S	Aluminum	Universal	—	Yes	1
81-0001-R	Aluminum	Emergency	Red	No	1
81-0001-RS	Aluminum	Emergency	Red	Yes	1
81-0001-B	Aluminum	Service	Blue	No	1
81-0001-BS	Aluminum	Service	Blue	Yes	1
81-0001-38R	Aluminum	38° Emergency	Red	No	1
81-0001-38RS	Aluminum	38° Emergency	Red	Yes	1
81-0001-38B	Aluminum	38° Service	Blue	No	1
81-0001-38BS	Aluminum	38° Service	Blue	Yes	1

OEM-SPEC PREMIUM GLADHANDS



STANDARD & ANGLED

GROTE’S HIGHEST QUALITY, PROFESSIONAL-GRADE GLADHANDS

PROVIDES SUPERIOR PROTECTION FROM CORROSION, BLOCKED AIR LINES AND COSTLY DOWNTIME!


- Available in standard, shutoff, 38° and our new 45° swingers
- All Grote gladhands meet or exceed SAE J1318 standards and are polarized for easy identification (emergency and service)

PART #	MATERIAL	DESCRIPTION	COLOR	SCREEN	PK
81-0011	Aluminum/SS	Universal, Polyseal	Grey	Yes	10
81-0011-B	Aluminum/SS	Service, Polyseal	Blue	Yes	10
81-0011-R	Aluminum/SS	Emergency, Polyseal	Red	Yes	10
81-0011-38B	Aluminum/SS	38° Service, Polyseal	Blue	Yes	10
81-0011-38R	Aluminum/SS	38° Emergency, Polyseal	Red	Yes	10
81-0011-45B	Aluminum/SS	45° Service, Polyseal	Blue	Yes	1
81-0011-45R	Aluminum/SS	45° Emergency, Polyseal	Red	Yes	1
81-0011-SB	Aluminum/SS	Service Shutoff, Polyseal	Blue	Yes	1
81-0011-SR	Aluminum/SS	Emerg. Shutoff, Polyseal	Red	Yes	1

- Cast iron construction for extreme durability
- Polyurethane seals provides a reliable seal and longer service life
- Meets or exceeds J1318 standards

PART #	DESCRIPTION	COLOR	SCREEN	PK
81-0001-C	Universal, Polyseal	Black	No	1
81-0001-CR	Emergency, Polyseal	Red	No	1
81-0001-CB	Service, Polyseal	Blue	No	1
81-0001-CS	Universal, Painted, Polyseal	Black	Yes	1
81-0001-CRS	Emergency, Painted, Polyseal	Red	Yes	1
81-0001-CBS	Service, Painted, Polyseal	Blue	Yes	1
81-0001-90CRS	Emergency, 90° Swinger, S/S Plate, Polyseal	Grey	Yes	1
81-0001-90CBS	Service, 90° Swinger, S/S Plate, Polyseal	Grey	Yes	1

CAST IRON PREMIUM GLADHANDS



HANDLE STYLE – SURFACE MOUNT

- Meets or exceed SAE J318 standards
- Shut-off arm, surface mount
- 3/8" port, full-face rubber seals

PART #	MATERIAL	DESCRIPTION	COLOR	SCREEN	PACK
81-0001-SR	Aluminum	Shut-Off, Emergency	Red	No	1
81-0001-SB	Aluminum	Shut-Off, Service	Blue	No	1

SHUTOFF GLADHANDS



KNOB STYLE – BULKHEAD

- Meets or exceed SAE J318 standards
- Low-profile knob, 3/8" port, full face rubber seal

PART #	MATERIAL	DESCRIPTION	COLOR	SCREEN	PACK
81-0001-SBR	Aluminum	Shut-Off, Emergency	Red	No	1
81-0001-SBB	Aluminum	Shut-Off, Service	Blue	No	1
81-0001-SBRs	Aluminum	Shut-Off, Emergency	Red	Yes	1
81-0001-SBBS	Aluminum	Shut-Off, Service	Blue	Yes	1

SHUTOFF GLADHANDS



GLADHANDLES

- Provides strain relief and prevents kinking of the air coil
- Anodized coating provides superior corrosion resistance
- Allows user to couple/uncouple with ease
- Includes thread sealant on the male end

PART #	MATERIAL	FEATURES	COLOR	PACK
81-0125	Aluminum	Anodized	Red & Blue	2
81-0124	Rubber	Thermo-Elastomeric	Red & Blue	2



GLADHAND ACCESSORIES



PART #	DESCRIPTION	PACK
81-0126	Dummy Gladhand with 18" Stainless Steel Cable	1
81-0126T	Dummy Gladhand with 18" Stainless Steel Cable and Heavy Duty Eyelet	1

GLADHAND LOCK



- Prevents unwanted connection to tractors/trailers
- Made of glass filled nylon; Includes 2 keys – keyed alike

PART #	DESCRIPTION	PACK
81-0149	Gladhand Lock	1

SEALS AND SCREENS




- Seals resist oil, chemicals, ozone
- Improved wear resistance lengthens service life
- Retail and bulk pack options

PART #	MATERIAL	FEATURES	COLOR	PACK
PROTECTIVE DUST FLAP				
81-0103-25	Polyurethane	Protective Dust Flap*	Grey	25
81-0102-100	Rubber	Protective Dust Flap*	Black	100
81-0102-08	Rubber	Protective Dust Flap*	Black	8
LARGE FACE WITH BUILT-IN FILTER SCREEN				
81-0113-100R	Polyurethane	w/ Built-In Filter Screen	Red	100
81-0113-08R	Polyurethane	w/ Built-In Filter Screen	Red	8
81-0113-100B	Polyurethane	w/ Built-In Filter Screen	Blue	100
81-0113-08B	Polyurethane	w/ Built-In Filter Screen	Blue	8
LARGE FACE				
81-0110-100R	Polyurethane	Large Face	Red	100
81-0110-08R	Polyurethane	Large Face	Red	8
81-0110-100B	Polyurethane	Large Face	Blue	100
81-0110-08B	Polyurethane	Large Face	Blue	8
81-0111	Polyurethane	Large Face	2 Red/2 Blue	4
81-0116-100BP	Polyurethane	Large Face	Black	100
81-0116-08BP	Polyurethane	Large Face	Black	8
SMALL FACE				
81-0112-100R	Polyurethane	Small Face	Red	100
81-0112-100B	Polyurethane	Small Face	Blue	100
81-0117-100BP	Polyurethane	Small Face	Black	100
DOUBLE LIP				
81-0101-100	Rubber	Double Lip	Black	100
81-0101-08	Rubber	Double Lip	Black	8
SINGLE LIP				
81-0100-100	Rubber	Single Lip	Black	100
FILTER SCREEN				
81-0115-25	Stainless Steel	Filter Screen	–	25

* Recommend to use a filter screen at all times

RUBBER AIR LINES



81-0112-RGR



81-0112-BGB



81-0115



81-0115-GRB

- 3/8" SAE J1402 Type A, EPDM rubber hose; UV and ozone resistant
- Meets or exceeds all DOT FMVSS No. 106 – Brake Hoses, 49 CFR 571.106
- Designed for operating pressure up to 225 psi; Minimum burst pressure = 900 psi
- Includes a swivel fitting for the tractor-end connection
- Rugged elastomeric hose is resistant to gasoline, diesel fuel, oil, and other chemicals
- O.D. 3/4" (3/8" Hose); O.D. 7/8" (1/2" Hose)
- Available in Black, Red, Blue for easy identification of emergency and service lines
- Aluminum grips provide easy coupling/uncoupling
- Bulk rubber hose and spring guard available to make custom hoses
- Red and Blue bulk hose available upon request

PART #	HOSE COLOR	GRIP COLOR	WORKING LENGTH	PACK
12'				
81-0112-R	Red	–	12'	1
81-0112-B	Blue	–	12'	1
81-0112-RGR	Red	Red	12'	1
81-0112-BGB	Blue	Blue	12'	1
81-0112	Black	–	12'	1
81-0112-GRB	Black	Red & Blue	12'	2
81-0112-GR	Black	Red	12'	1
81-0112-GB	Black	Blue	12'	1
81-0112-SS	Black	Black w/Single Spring	12'	1
81-0112-RSS	Red	Red w/Single Spring	12'	1
81-0112-BSS	Blue	Blue w/Single Spring	12'	1
15'				
81-0115-R	Red	–	15'	1
81-0115-B	Blue	–	15'	1
81-0115-RGR	Red	Red	15'	1
81-0115-BGB	Blue	Blue	15'	1
81-0115	Black	–	15'	1
81-0115-GRB	Black	Red & Blue	15'	2
81-0115-GR	Black	Red	15'	1
81-0115-GB	Black	Blue	15'	1
81-0115-SS	Black	Black w/Single Spring	15'	1
81-0115-RSS	Red	Red w/Single Spring	15'	1
81-0115-BSS	Blue	Blue w/Single Spring	15'	1
20'				
81-0120	Black	–	20'	1
81-0120-GRB	Black	Red & Blue	20'	2
81-0120-GR	Black	Red	20'	1
81-0120-GB	Black	Blue	20'	1

- -40°C (-40°F) to 93°C (200°F)

PART #	NOMINAL INSIDE DIA	NOMINAL OUTSIDE DIA	WORKING PRESSURE	MIN BEND RADIUS	WEIGHT (LB/FT)	LENGTH
81-0038-250	.375"	.75"	Min. Burst 900	2.25"	0.17	250'
81-0012-250	.5"	.88"	Min. Burst 900	3.00"	0.20	250'

PART #	DESCRIPTION	PACK
81-0115-SPR	3/8" x 1/2" Reusable or Field Attachable Fitting w/Spring Guard	2

BULK RUBBER AIR HOSE, SPRING GUARD



81-0038-250

81-0115-SPR

ULTRALINK™ POWER CORD & AIR ASSEMBLIES

Connect and Protect your trailer and equipment with Grote’s **3-in-1** and **4-in-1 Ultralink™ Power Cord & Air Assemblies** featuring rugged straight rubber air line hoses and Grote’s crush-resistant **UltraLink™ Power Cords**. The 4-in-1 Ultralink™ also features high-performance auxiliary power cables.

CRUSH RESISTANT



UltraLink’s crush-resistant design can survive being run over by a heavy duty vehicle while conventional hollow core designs are permanently deformed and rendered useless.

PLUG DESIGN



Solid brass, nickel-plated pins
Crush-resistant, weather-tight elastomeric material

The **UltraLink™ Power Cord** is the backbone of Grote’s **3-in-1** and **4-in-1** systems! This premium power cord is constructed utilizing Grote’s crush-resistant plug, so frequent replacement of the plug is no longer a consideration. Our plug stands up to the harshest environments and provides maximum reliability, while delivering improved performance, longer wear, and superior conductivity.

3-IN-1



81-3215



81-3115



81-3215-GRP



81-3212

ULTRALINK™ POWER CORD & AIR ASSEMBLIES

- Our rubber air lines are resistant to gasoline, diesel fuel, oil, and other chemicals
- The tractor ends of the hoses include swivel fittings, providing easy and quick installation
- Premium high-strength spiral wrap protects the cable and air lines from chaffing and kinking
- Assemblies with easy-coupling rubber gladhandles include a premium EZ Claw® “Self-Adjusting Sling”

POWER CORD SPECIFICATIONS

Plug: SAE J560

Cable: J2394 (ABS)

Cord: 1/8 GA, 2/10 GA, 4/12 GA

Operating Range: -55°F to 190°F / -48°C to 87°C

AIR LINE SPECIFICATIONS

DOT FMVSS-106

SAE J1402

PART #	HOSE COLOR	WORKING LENGTH	GRIPS	PACK
Black Air Lines				
81-3112	Black	12'	Anodized	1
81-3112-GRP	Black	12'	Rubber	1
81-3115	Black	15'	Anodized	1
81-3115-GRP	Black	15'	Rubber	1
81-3120	Black	20'	Anodized	1
Red & Blue Air Lines				
81-3212	Red & Blue	12'	Anodized	1
81-3212-GRP	Red & Blue	12'	Rubber	1
81-3215	Red & Blue	15'	Anodized	1
81-3215-GRP	Red & Blue	15'	Rubber	1
81-3215N	Red & Blue	15'	No Grips	1

ULTRALINK™ POWER CORD & AIR ASSEMBLIES

- Our rubber air lines are resistant to gasoline, diesel fuel, oil, and other chemicals
- The tractor ends of the hoses, include swivel fittings, providing easy and quick installation
- Premium high-strength spiral wrap protects the cable and air lines from chaffing and kinking
- All assemblies come with easy-coupling gladhandles and a premium EZ Claw® “Self-Adjusting Sling”

POWER CORD SPECIFICATIONS

Plug: SAE J560

Cable: J2394 (ABS)

Cord: 1/8 GA, 2/10 GA, 4/12 GA

Operating Range: -55°F to 190°F / -48°C to 87°C

AIR LINE SPECIFICATIONS

DOT FMVSS-106

SAE J1402

PART #	STYLE/HOSE COLOR	WORKING LENGTH	GRIPS	PACK
Single Pole				
81-3312	Single Pole, Black	12'	Anodized	1
81-3312-GRP	Single Pole, Black	12'	Rubber	1
81-3315	Single Pole, Black	15'	Anodized	1
81-3315-GRP	Single Pole, Black	15'	Rubber	1
Dual Pole				
81-3412	Dual Pole, Black	12'	Anodized	1
81-3412-GRP	Dual Pole, Black	12'	Rubber	1
81-3415	Dual Pole, Black	15'	Anodized	1
81-3415-GRP	Dual Pole, Black	15'	Rubber	1
ISO Auxiliary				
81-3512	ISO Auxiliary, Black	12'	Anodized	1
81-3512-GRP	ISO Auxiliary, Black	12'	Rubber	1
81-3515	ISO Auxiliary, Black	15'	Anodized	1
81-3515-GRP	ISO Auxiliary, Black	15'	Rubber	1

4-IN-1



81-3515



81-3315-GRP



81-3415-GRP



81-3412-GRP


TRACKER BAR SPRING REPLACEMENT KIT



- Complete replacement kit in one convenient part
- Includes a heavy duty spring and cover; 3 hose holder and large tracker bar snap clip

PART #	DESCRIPTION	LENGTH	PACK SIZE
81-0135	Single Spring	16"	1
81-0147	Single Spring w 81-0129	20"	1
81-0145	Dual Spring	16"	1
81-0146	Dual Spring	25"	1

HOSE HOLDERS



- Designed to route and suspend air coils, hoses and electrical cables
- Provides excellent kink protection

PART #	DESCRIPTION	PACK SIZE
81-0137	2 Hose holder – ¾" x 2, Eyelet Bolt	1
81-0138	3 Hose holder – ¾" x 3, U-Bolt	1
81-0139	4 Hose holder – ¾" x 4, Adjustable Bolt	1

CABLE CLAMP HOLDER



- Cable clamp & clip designed to support power cords and rubber air lines, including 3 in 1 assemblies
- Includes a heavy duty rubber insulated clamp and steel snap clip

PART #	DESCRIPTION	PACK SIZE
81-0129	Cable Clamp Holder	1

SNAP CLIP



- Stainless steel construction
- Ideal for use with a tracker bar

PART #	DESCRIPTION	PACK SIZE
81-0140	Snap Clip – Large	1

POGO STICKS



- Designed for nylon, rubber air hoses and heavy-duty ABS cables
- Internal heavy duty spring
- Includes a 7/16" mounting bolt, 3 hose holder, eyebolt & nut

PART #	MATERIAL	LENGTH	PACK SIZE
81-0130	Chrome	40"	1
81-0131	Zinc dichromate	40"	1

TENDER SPRINGS



- Heavy duty springs provide superior support
- Designed for under trailer applications
- Double loop ends

PART #	DESCRIPTION	PACK SIZE
81-0136	24", Includes 2 hose holder	1

SUSPENDER SPRINGS



- Heavy duty springs provide superior support
- Outside diameter exceeds 1"
- Double loop ends

PART #	DESCRIPTION	PACK SIZE
81-0132	12", Tandem and airline support	1
81-0133	14 ½", Straight cable assemblies	1
81-0134	25", HD application incl. ABS power cords	1

HOSE HANGER CLAMPS



- Quality material designed for low temperatures
- Ultra Violet (U.V.) and impact resistant

PART #	DESCRIPTION	PACK SIZE
83-7015	2 Hose holder – 3/8" x 2	25
83-7016	2 Hose holder – 1/2" x 2	25
83-7017	2 Hose holder – 3/8" and 1/2"	25

DRAIN VALVES



- 200 PSI maximum working pressure

PART #	FEATURES	PACK SIZE
81-0128	Drain Valve, 60" Stainless Steel Cable; 1/4" NPTF Male Thread	1
81-0128-14	Drain Valve with Uncrimped Loop (Ready-to-Install), 60" Stainless Steel Cable; 1/4" NPTF Male Thread	1

EZ CLAW®



EVERY EZ CLAW® PRODUCT IS RUGGED, LIGHTWEIGHT, AND BUILT TO LAST

The EZ Claw System is the premier automatic suspension system for protecting power cords, airlines, and hydraulic hoses.

Easy to install, the system is designed to prevent chaffing, crimping, and unplanned disconnects for the life of your truck.

Connect and protect your power cords and hoses with ease, while preventing the costly maintenance and downtime that can come with unreliable tracker bars and springs.



81-2300

EZ CLAW TENSIONER



81-2301

81-2302VM

EZ CLAW MOUNTING BRACKETS



81-2306

EZ CLAW SLING



81-2303

EZ CLAW HOSE & CABLE BLOCK

Travel Length: Up to 84"	Bracket Plating: Zinc (ASTM B633)
Travel Range: Full 90°	Bracket Painting: Powder-coated
Support Strength: 25, 30 & 40 lbs	Sling Strength: 500 lb Rating
Corrosion Rating: ASTM F1941 & B117	Sling Resistance: Moisture, Chemicals and UV
Bracket Cut: Laser (Accurate to 0.001")	Sling Material: Polyester & Stainless Steel
Bracket Welding: Robotic (Accurate to 0.041")	Cable Block Material: Polymer & Stainless Steel

BUILDING YOUR EZ CLAW SYSTEM IS AS EZ AS 1-2-3!

1. CHOOSE YOUR EZ CLAW TENSIONER

PART #	DESCRIPTION	SUPPORTS AND PROTECTS	WEIGHT
81-2300	EZ Claw Tensioner, 25 LB	12'-15' 3-in-1's & Straight Cords and Hoses	5 lbs
81-2309	EZ Claw Tensioner, 30 LB	12'-15' 4-in-1's & Straight Cords and Hoses, 20' 3-in-1's	5 lbs
81-2305	EZ Claw Tensioner, 40 LB	Hydraulic Lines	5.4 lbs

2. CHOOSE YOUR EZ CLAW MOUNTING BRACKET

PART #	DESCRIPTION	IDEAL APPLICATION	TRUCK TYPE	MOUNT SIZE
81-2301	EZ Claw Flange Mount Bracket	Back of Cab / Headache Rack	Sleeper	8" x 8.25"
81-2302VM	EZ Claw Versa Mount Bracket	Back of Cab / Headache Rack	Day Cab	5" x 8.25"
81-2304	EZ Claw Top Mount Bracket	Tool Box or Top of Headache Mount	any w/ Rack or Box	5" x 8.25"

HAVE A FREIGHTLINER M2?

PART #	DESCRIPTION	SPECIFIC APPLICATION
81-2308	EZ Claw Freightliner M2 Adapter Bracket	Rear Cab Installations on M2 Cabs w/o Air Fairing

WHICH BRACKET IS RIGHT FOR YOU?

PART #	MAKE	MODEL	SLEEPER	DAY CAB	PART #	MAKE	MODEL	SLEEPER	DAY CAB
81-2301	FREIGHTLINER	COLUMBIA	✓	✓	81-2302VM	MACK	ALL	✓	✓
	FREIGHTLINER	CASCADIA	✓			VOLVO	ALL	✓	✓
	INTERNATIONAL	ALL	✓			FREIGHTLINER	CASCADIA		✓
	PETERBILT	ALL	✓	✓		INTERNATIONAL	ALL		✓
	KENWORTH	ALL	✓	✓					

3. CHOOSE YOUR EZ CLAW HOLDER


PART #	DESCRIPTION	IDEAL APPLICATION	SUPPORT DIAMETER	MATERIAL
81-2306	EZ Claw Sling	3-in-1's, 4-in-1's, Hydraulic Lines	Up to 2" bundle or hose	UV-Protected Polyester
81-2303	EZ Claw Hose & Cable Block	Straight Cords and Hoses	3 x 3/8" (cord or hose)	Polymer + Stainless Steel

AIR BRAKE TUBING – BULK



- UV and ozone resistant nylon material; available in multiple lengths & colors
- Resistant to gasoline, diesel fuel and other road chemicals
- Meets or exceeds SAE J844 (Type A – non-reinforced & Type B – reinforced)
- Meets or exceeds SAE J844, DOT FMVSS (49 CFR 571.106) & FMCSA (393.45)
- Meets or exceeds DOT requirements for use with compression fittings
- Operates at up to 150 psi in air brake systems; Operating range: -40°F to 200°F

PART #	OUTSIDE DIAMETER	COLOR	TYPE	LENGTH
1/8"				
81-1018-100B	1/8"	Black	A	100'
5/32"				
81-1532-100B	5/32"	Black	A	100'
81-1532-500B	5/32"	Black	A	500'
1/4"				
81-1014-1000B	1/4"	Black	A	1000'
81-1014-100B	1/4"	Black	A	100'
81-1014-1000BL	1/4"	Blue	A	1000'
81-1014-100BL	1/4"	Blue	A	100'
81-1014-1000G	1/4"	Green	A	1000'
81-1014-100G	1/4"	Green	A	100'
81-1014-1000R	1/4"	Red	A	1000'
81-1014-100R	1/4"	Red	A	100'
81-1014-100Y	1/4"	Yellow	A	100'
5/16"				
81-1516-100B	5/16"	Black	A	100'
3/8"				
81-1038-500B	3/8"	Black	B	500'
81-1038-100B	3/8"	Black	B	100'
81-1038-500BL	3/8"	Blue	B	500'
81-1038-100BL	3/8"	Blue	B	100'
81-1038-500G	3/8"	Green	B	500'
81-1038-100G	3/8"	Green	B	100'
81-1038-500R	3/8"	Red	B	500'
81-1038-100R	3/8"	Red	B	100'
81-1038-500Y	3/8"	Yellow	B	500'
81-1038-100Y	3/8"	Yellow	B	100'
1/2"				
81-1012-500B	1/2"	Black	B	500'
81-1012-100B	1/2"	Black	B	100'
81-1012-500BL	1/2"	Blue	B	500'
81-1012-100BL	1/2"	Blue	B	100'
81-1012-500G	1/2"	Green	B	500'
81-1012-100G	1/2"	Green	B	100'
81-1012-500R	1/2"	Red	B	500'
81-1012-100R	1/2"	Red	B	100'
81-1012-500Y	1/2"	Yellow	B	500'
81-1012-100Y	1/2"	Yellow	B	100'
5/8"				
81-1058-250B	5/8"	Black	B	250'
3/4"				
81-1034-250B	3/4"	Black	B	250'



81-1014-100B



81-1038-100BL



81-1012-500R

04

TERMINALS & CONNECTORS

COSSES
ET CONNECTEURS

TERMINALES
Y CONECTORES

- 35 Technical information
- 36 Heat Shrinkable Connectors
- 37 Sealed Multiple Wire Heat Shrink Connectors
- 40 Crystal Clear Heat Shrink Connectors
- 42 Crimp, Solder & Seal Lead Free Terminals
- 44 Solder & Seal Lead Free Terminals
- 46 Butt Connectors
- 47 Ring Terminals
- 51 Spade Terminals
- 52 Quick Disconnects
- 54 Bullet & Receptacle Connectors
- 55 Specialty Connectors & Adapters
- 57 Assortment Kits
- 60 Deutsch Terminals & Tools
- 62 Weather Pack & Metri-Pack OEM Terminals & Connectors

POWER DELIVERY DEPENDS SO MUCH ON THE TYPE OF CONNECTIONS MADE. POOR CONNECTIONS LEAD TO DOWNTIME AND REDUCED PRODUCTIVITY, NOT TO MENTION FRUSTRATION AND DELAY.

GROTE'S EXTENSIVE LINE OF TERMINALS & CONNECTORS ENSURE THE BEST POSSIBLE CONNECTIONS FOR ANY REPAIR TYPE, INSTALLATION OF NEW EQUIPMENT AND GENERAL MAINTENANCE TO ENSURE THE EQUIPMENT PERFORMS AT OPTIMAL LEVELS AT ALL TIMES.





*Connect & Protect with
Grote's wide selection of
terminals & connectors.*

GROTE TERMINALS & CONNECTORS

All Grote terminals and connectors are constructed of copper, and are electro tin-plated to ensure maximum electrical conductivity after crimping unless otherwise stated. Vinyl insulation sleeve provides good dielectric strength and withstands the pressure of crimping. All terminals are color coded by wire range for easy wire identification.



FEATURES & BENEFITS

- Maximum electrical conductivity after crimping
- Funnel edged barrel for fast, easy insertion of wire
- Maximum holding power
- Tin plating prevents corrosion
- Wire range clearly stamped on neck of terminal


- Retail and bulk packaging options
- No master pack minimums
- Trilingual and colorful labeling
- Resealable, reusable and recyclable clamshells
- Installation instructions included



STANDARD STUD	SIZE	STUD DIA.	HOLE DIA.	
●	#0	.060"	.094"	2.39mm
●	#1	.073"		
●	#2	.086"		
●	#3	.099"	.120"	3.02mm
●	#4	.112"		
●	#5	.125"	.146"	3.71mm
●	#6	.138"		
●	#8	.164"	.173"	4.39mm
●	#10	.190"	.198"	5.03mm
●	#12	.216"	.265"	6.75mm
●	#14	.242"		
●	1/4"	.250"		
●	5/16"	.312"	.328"	8.33mm
●	3/8"	.375"	.390"	9.92mm
●	7/16"	.437"	.453"	11.51mm
●	1/2"	.500"	.515"	13.10mm
●	5/8"	.625"	.656"	16.67mm
●	3/4"	.750"	.781"	19.84mm
●	7/8"	.875"	.906"	23.02mm
●	1"	1.000"	1.031"	26.19mm


Uninsulated Butted Seam Terminal

- Constructed of electrolytic (ETP) copper
- Wire Range: 8 – 4/0 AWG
- Continuous Operating Temperature Range: 75°C (167°F)
- Voltage Rating: 300V / 600V




Uninsulated Brazed Seam Terminal

- Constructed of electrolytic (ETP) copper
- Wire Range: 22 – 10 AWG
- Continuous Operating Temperature Range: 75°C (167°F)
- Voltage Rating: 300V / 600V




Pre-insulated Funnel Entry Vinyl Terminal

- Vinyl insulation sleeve withstands the pressure of crimping
- Color coded for easy identification
- Wire Range: 22 – 4/0 AWG
- Continuous Operating Temperature Range: 75°C (167°F)
- Voltage Rating: 300V / 600V



Pre-insulated Funnel Entry Nylon Terminal

- Nylon insulation sleeve provides high dielectric strength
- Color coded for easy identification
- Wire Range: 22 – 10 AWG
- Continuous Operating Temperature Range: 105°C (221°F)
- Voltage Rating: 300V / 600V



TERMINAL & CONNECTOR IDENTIFICATION

Polyvinyl Chloride (PVC) and Nylon insulated connectors are color coded for quick wire identification.

WIRE SIZE (AWG)	STUD SIZE	TAB SIZE	BULLET/SNAP PLUG SIZE
24-22	#4	.110"	.157"
22-18	#6	.187"	.180"
22-16	#8	.250"	.195"
16-14	#10	.375"	
12-10	1/4"		
8	5/16"		
6	3/8"		
4	1/2"		
2	3/4"		
1			
1/0			
2/0			
3/0			
4/0			
250MCM			

HEAT SHRINKABLE

TERMINALS & CONNECTORS

FEATURES & BENEFITS


- Protects splices from water, corrosion, salt and moisture, provides strain relief
- Protects against added vibration in rugged environments
- Seamless butt connectors and brazed seam rings & spades prevent opening of connector barrel
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job
- Completely insulates and protects electrical connections
- UL listed

OPERATING TEMPERATURES:

Polyolefin: -55°C (-67°F) to 110°C (230°F)

SHRINK RATIOS:

Polyolefin: 3:1



HEAT SHRINKABLE BUTT CONNECTORS – POLYOLEFIN

22-8 GAUGE



PART #	GAUGE	COLOR	PACK
88-3150	22-18	Red	1000
83-3150-3	22-18	Red	300
83-3150	22-18	Red	100
84-3150	22-18	Red	15
88-3350	16-14	Blue	1000
83-3350-3	16-14	Blue	300
83-3350	16-14	Blue	100
84-3350	16-14	Blue	15
88-3550	12-10	Yellow	500
83-3550-3	12-10	Yellow	200
83-3550	12-10	Yellow	50
84-3550	12-10	Yellow	15
84-2750	8	Red	10

HEAT SHRINK STEP-DOWN BUTT CONNECTORS

22-8 GAUGE



PART #	GAUGE	COLOR	PACK
83-2624	22-18 to 16-14	Blue	100
84-2624	22-18 to 16-14	Blue	15
83-2625	16-14 to 12-10	Yellow	100
84-2625	16-14 to 12-10	Yellow	15
83-2626	12-10 to 8	Red	100
84-2626	12-10 to 8	Red	15

SEALED MULTIPLE WIRE HEAT SHRINK CONNECTORS

Multiple wire connectors allow installer to terminate and seal 1 wire to 2 wires or to join multiple wires together. When connecting multiple wires protection from moisture and corrosion are crucial. The heat shrink moisture seal provides superior protection and replaces the unsealed, tap style connector.

FEATURES & BENEFITS

- Seamless butt connectors provide superior crimp performance
- Window in butt connectors allows for visual inspection to ensure all wires are fully inserted
- Butt connectors have crimp indicators where the installation tool should be positioned to crimp connector
- High adhesive-flow 4:1 polyolefin tubing to seal multiple wires
- Color-coded dash on tubing to indicate the wire gauge for the connector
- Clear tubing to allow for visual inspection

IN-LINE HEAT SHRINK BUTT CONNECTORS, 24-10 GAUGE




- Shrink Ratio 4:1; Color dash on tubing identifies the proper gauge sizes
- Color dash on the connector identifies the proper crimp gauge
- Heat shrink tubing has an active adhesive that seals multiple wires

PART #	CONNECTOR GAUGE	MARKINGS	END COLOR	WIRE RANGE	PACK
84-2629	24-22	White	Red	24-22 x 2	15
84-2630	22-18	Red	Blue	22-18 x 2	15
84-2631	16-14	Blue	Yellow	16-14 x 2	15
84-2632	12-10	Red	Red	12-10 x 2	15

CLOSED-END HEAT SHRINK BUTT CONNECTORS, 22-10 GAUGE

- Color dash on tubing identifies the proper gauge sizes
- Color dash on the connector identifies the proper crimp gauge
- Heat shrink tubing has an active adhesive that seals multiple wires
- Excellent replacement for wire nuts, where moisture/corrosion is a problem

PART #	CONNECTOR GAUGE	MARKINGS	WIRE RANGE	PACK
84-2627	22-14	Blue	Multiple	15
84-2628	18-10	Yellow	Multiple	15



HEAT SHRINKABLE RING TERMINALS



22-18 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
83-2415	22-18	6	50
84-2415	22-18	6	15
84-2423	22-18	8	10
83-2416	22-18	10	50
84-2416	22-18	10	15
83-2417	22-18	1/4"	50
84-2417	22-18	1/4"	15

HEAT SHRINKABLE RING TERMINALS



16-14 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
84-2424	16-14	6	10
83-2408	16-14	8	50
84-2408	16-14	8	15
83-2410	16-14	10	50
84-2410	16-14	10	15
83-2412	16-14	1/4"	50
84-2412	16-14	1/4"	15
83-2413	16-14	5/16"	50
84-2413	16-14	5/16"	15
83-2414	16-14	3/8"	50
84-2414	16-14	3/8"	15

HEAT SHRINKABLE RING TERMINALS



12-10 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
83-2501	12-10	8	50
84-2501	12-10	8	15
83-2510	12-10	10	50
84-2510	12-10	10	15
83-2511	12-10	1/4"	50
84-2511	12-10	1/4"	15
83-2512	12-10	5/16"	50
84-2512	12-10	5/16"	15
83-2513	12-10	3/8"	50
84-2513	12-10	3/8"	15
84-2425	12-10	1/2"	10

HEAT SHRINKABLE RING TERMINALS



8 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
84-2443	8	10	10
84-2426	8	1/4"	10
84-2441	8	5/16"	10
84-2427	8	3/8"	10
84-2442	8	1/2"	10

22-10 GAUGE

HEAT SHRINKABLE QUICK DISCONNECTS

PART #	GAUGE	TYPE	TAB SIZE	PACK
84-2436	22-18	Male	.250"	15
84-2437	22-18	Female	.250" FI	15
83-2430	16-14	Male	.250"	50
84-2430	16-14	Male	.250"	15
83-2432	16-14	Female	.250" FI	50
84-2432	16-14	Female	.250" FI	15
84-2439	12-10	Male	.250"	15
84-2440	12-10	Female	.250" FI	15

FI = Fully Insulated



22-10 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
84-2421	22-18	6	15
84-2428	22-18	8	10
84-2422	22-18	10	15
84-2429	16-14	6	10
84-2418	16-14	8	15
84-2420	16-14	10	15
84-2518	12-10	8	15
84-2520	12-10	10	15
84-2521	12-10	1/4"	15

HEAT SHRINKABLE SPADE TERMINALS



22-14 GAUGE				
PART #	GAUGE	TYPE	BULLET SIZE	PACK
84-2460	22-18	Male	.180"	15
84-2431	16-14	Male	.157"	10
84-2433	16-14	Female	.157" FI	10
84-2447	16-14	Male	.180"	15
84-2448	16-14	Female	.180" FI	15
83-2434	16-14	Male	.197"	50
84-2434	16-14	Male	.197"	15
83-2435	16-14	Female	.197" FI	50
84-2435	16-14	Female	.197" FI	15

FI = Fully Insulated

HEAT SHRINKABLE BULLET & RECEPTACLE CONNECTORS



22-18 GAUGE			
PART #	GAUGE	PIN SIZE	PACK
84-2151	22-18	.075" Diameter	15

HEAT SHRINKABLE PIN TERMINAL



> Kits

SEE PAGE 164 FOR
OUR FULL LINE OF
ASSORTMENT KITS


CRYSTAL CLEAR HEAT SHRINKABLE CONNECTORS

TAKE THE GUESSWORK OUT OF CRIMPING!

Crystal Clear Heat Shrinkable Connectors are designed to provide visual assurance that the terminal or connector is installed correctly, ensuring optimal conductivity. They offer the ability to visually inspect the condition of the wire and termination after the repair or installation.



CRYSTAL CLEAR FEATURES & BENEFITS

- Window butt connector and 45° barrel allows installer to see wire is fully inserted and wire is crimped to terminal
- Window butt connector and 45° barrel on terminals ensure wire is stripped the proper length
- Color stripes provide alignment for tool to crimp center of barrel and indicates industry standard for wire gauge size
- Longer ring terminals provide ideal seal and offers a flush surface without tubing impeding contact between screw and terminal... allows ring terminals to be stacked
- Crystal Clear waterproof insulation allows for indisputable inspection of the wire's condition



Standard connectors don't allow the installer to see the wire which can cause the following problems:

1. Wire stripped too short, which can result in crimping the end of the wire (poor termination)
2. Wire is not fully seated to connector, which can result in a poor termination



HS BUTT CONNECTORS

CRYSTAL CLEAR

PART #	CONTENTS	GAUGE	PACK
83-4150	Crystal Clear Heat Shrinkable Butt Connector	22-18	100
83-4150-3	Crystal Clear Heat Shrinkable Butt Connector	22-18	300
84-4150	Crystal Clear Heat Shrinkable Butt Connector	22-18	15
88-4150	Crystal Clear Heat Shrinkable Butt Connector	22-18	1000
83-4350	Crystal Clear Heat Shrinkable Butt Connector	16-14	100
83-4350-3	Crystal Clear Heat Shrinkable Butt Connector	16-14	300
84-4350	Crystal Clear Heat Shrinkable Butt Connector	16-14	15
88-4350	Crystal Clear Heat Shrinkable Butt Connector	16-14	1000
83-4550	Crystal Clear Heat Shrinkable Butt Connector	12-10	50
83-4550-3	Crystal Clear Heat Shrinkable Butt Connector	12-10	200
84-4550	Crystal Clear Heat Shrinkable Butt Connector	12-10	15
88-4550	Crystal Clear Heat Shrinkable Butt Connector	12-10	500



Window Butt Connectors

- Window in connector assures that the wire is seated and is being crimped to the connector
- Color-coded stripes indicate/guide where to position crimp nest to install properly
- Seamless barrel butt connectors ensure superior crimp performance
- Wire-stop in butt connectors prevents over-insertion of wire



45° Ring Terminal

- 45° barrel angle allows tubing to adhere to it and provides stronger seal
- Color-coded stripes also indicate/guide where to position crimp nest to install properly
- Brazed seam barrel ensures superior crimp performance
- Serrations in crimp barrel provide strong mechanical termination



Adhesive-Lined Crystal Clear Heat Shrinkable Tubing

- Crystal Clear tubing provides optimal clarity for visual inspection
- Adhesive-Lined tubing ensures a waterproof seal
- Wire gauge imprint simplifies wire size identification


CRYSTAL CLEAR				
PART #	CONTENTS	GAUGE	STUD SIZE	PACK
84-4408	Crystal Clear Heat Shrinkable Ring Terminal	16-14	#8	15
84-4410	Crystal Clear Heat Shrinkable Ring Terminal	16-14	#10	15
84-4412	Crystal Clear Heat Shrinkable Ring Terminal	16-14	1/4"	15
84-4413	Crystal Clear Heat Shrinkable Ring Terminal	16-14	5/16"	15
84-4414	Crystal Clear Heat Shrinkable Ring Terminal	16-14	3/8"	15
84-4415	Crystal Clear Heat Shrinkable Ring Terminal	22-18	#6	15
84-4416	Crystal Clear Heat Shrinkable Ring Terminal	22-18	#10	15
84-4510	Crystal Clear Heat Shrinkable Ring Terminal	12-10	#10	15
84-4511	Crystal Clear Heat Shrinkable Ring Terminal	12-10	1/4"	15
84-4513	Crystal Clear Heat Shrinkable Ring Terminal	12-10	3/8"	15

HS RING TERMINALS



CRYSTAL CLEAR					
PART #	CONTENTS	GAUGE	STUD SIZE	TYPE	PACK
84-4430	Crystal Clear HS Quick Disconnect	16-14	.250"	Male	15
84-4432	Crystal Clear HS Quick Disconnect	16-14	.250"	Female	15
84-4436	Crystal Clear HS Quick Disconnect	22-18	.250"	Male	15
84-4437	Crystal Clear HS Quick Disconnect	22-18	.250"	Female	15
84-4439	Crystal Clear HS Quick Disconnect	12-10	.250"	Male	15
84-4440	Crystal Clear HS Quick Disconnect	12-10	.250"	Female	15

HS QUICK DISCONNECTS



CRYSTAL CLEAR					
PART #	CONTENTS	GAUGE	STUD SIZE	TYPE	PACK
84-4447	Crystal Clear HS Bullet Connector	16-14	.180"	Male	15
84-4448	Crystal Clear HS Bullet Connector	16-14	.180"	Female	15

HS BULLET CONNECTORS



CRYSTAL CLEAR		
PART #	CONTENTS	PACK
84-4624	Crystal Clear Heat Shrink Step Down Butt Connector	20-18 to 16-14 Ga 15
84-4625	Crystal Clear Heat Shrink Step Down Butt Connector	16-14 to 12-10 Ga 15

HS STEP DOWN BUTT CONNECTORS



CRIMP, SOLDER & SEAL LEAD FREE

TERMINALS & CONNECTORS

OPERATING TEMPERATURE:

-55°C (-67°F) to 110°C (230°F)

TENSILE STRENGTH: 2200 PSI

SOLDER MELTING TEMPERATURE:

138°C (280°F)


SHRINK RATIO: 3:1

FEATURES & BENEFITS

- Protects splices from water, corrosion, salt and moisture, provides strain relief
- Protects against added vibration in rugged environments
- Completely insulates and protects electrical connections
- Seamless butt connectors & brazed seam rings & spades prevent unwanted opening of the connector barrel
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job
- UL listed

LEAD FREE (NEW)


- Lead free solder has greater surface tension
- Solder stays in place which provides greater tensile strength than other solder sleeves
- Solder sleeves pre-fluxed to clean metals & provide a quality solder termination
- New solder sleeves are Tin & Bismuth alloy
- 45° barrel allows installer to see wire is fully inserted and wire is crimped to terminal
- RoHS compliant; better for the environment



CRIMP, SOLDER & SEAL BUTT CONNECTORS

22-10 GAUGE

PART #	GAUGE	PACK
88-2929	22-18	1000
83-2929	22-18	100
84-2929	22-18	15
88-2930	16-14	1000
83-2930	16-14	100
84-2930	16-14	15
88-2931	12-10	1000
83-2931	12-10	100
84-2931	12-10	15



CRIMP, SOLDER & SEAL RING TERMINALS

22-18 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-1932	22-18	10	25
83-1933	22-18	1/4"	25
83-1934	22-18	5/16"	25
83-1935	22-18	3/8"	25



CRIMP, SOLDER & SEAL RING TERMINALS

16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-1937	16-14	8	25
84-1937	16-14	8	6
83-1938	16-14	10	25
84-1938	16-14	10	6
83-1939	16-14	1/4"	25
84-1939	16-14	1/4"	6
83-1940	16-14	5/16"	25
84-1940	16-14	5/16"	6
83-1941	16-14	3/8"	25
84-1941	16-14	3/8"	6



12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-1943	12-10	10	25
84-1943	12-10	10	6
83-1944	12-10	1/4"	25
84-1944	12-10	1/4"	6
83-1945	12-10	5/16"	25
84-1945	12-10	5/16"	6
83-1946	12-10	3/8"	25
84-1946	12-10	3/8"	6
83-1947	12-10	1/2"	25
84-1947	12-10	1/2"	6

CRIMP, SOLDER & SEAL RING TERMINALS



22-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-1951	22-18	Female .250" FI	25
83-1952	22-18	Male .250"	25
83-1953	16-14	Female .250" FI	25
84-1953	16-14	Female .250" FI	6
83-1954	16-14	Male .250"	25
84-1954	16-14	Male .250"	6
83-1955	12-10	Female .250" FI	25
83-1956	12-10	Male .250"	25

FI = Fully Insulated

CRIMP, SOLDER & SEAL QUICK DISCONNECTS



22-10 GAUGE ASSORTMENT KIT

- Includes the most popular heat shrink crimp, solder and seal terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6542	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects (10) Female Disconnects (10)	120

CRIMP, SOLDER & SEAL TERMINAL & CONNECTOR



> Kits

SEE PAGE 164 FOR
OUR FULL LINE OF
ASSORTMENT KITS

SOLDER & SEAL LEAD FREE

TERMINALS & CONNECTORS

FEATURES & BENEFITS

- Protects splices from water, corrosion, salt and moisture, provides strain relief
- Protects against added vibration in rugged environments
- Completely insulates and protects electrical connections
- Color-coded tubing with wire gauge imprint provides easy identification of the correct part for the job
- UL listed

LEAD FREE (NEW)

- Lead free solder has greater surface tension
- Solder stays in place which provides greater tensile strength than other solder sleeves
- Solder sleeves pre-fluxed to clean metals & provide a quality solder termination
- New solder sleeves are Tin & Bismuth alloy
- RoHS compliant; better for the environment

OPERATING TEMPERATURE:


-55°C (-67°F) to 110°C (230°F)

TENSILE STRENGTH: 2200 PSI

SOLDER MELTING TEMPERATURE:

138°C (280°F)

SHRINK RATIO: 3:1



HEAT SHRINK & SOLDER SPLICE CONNECTORS

22-10 GAUGE

PART #	GAUGE	COLOR STRIPE	PACK
88-2618	22-18	Red	1000
83-2618	22-18	Red	100
84-2618	22-18	Red	15
88-2614	16-14	Blue	1000
83-2614	16-14	Blue	100
84-2614	16-14	Blue	15
83-2612	12-10	Yellow	100
84-2612	12-10	Yellow	15

HEAT SHRINK & SOLDER RING TERMINALS

22-18 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2803	22-18	8	25
84-2804	22-18	10	25
84-2805	22-18	1/4"	25
84-2806	22-18	5/16"	25
84-2807	22-18	3/8"	25

HEAT SHRINK & SOLDER RING TERMINALS

16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2809	16-14	8	25
84-2810	16-14	10	25
84-2811	16-14	1/4"	25
84-2455	16-14	5/16"	25
84-2813	16-14	3/8"	25

12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2814	12-10	10	25
84-2438	12-10	1/4"	25
84-2815	12-10	5/16"	25
84-2816	12-10	3/8"	25
84-2818	12-10	1/2"	25

HEAT SHRINK & SOLDER RING TERMINALS



22-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2822	22-18	Female .250" FI	25
84-2823	22-18	Male .250"	25
84-2824	16-14	Female .250" FI	25
84-2825	16-14	Male .250"	25
84-2826	12-10	Female .250" FI	25
84-2827	12-10	Male .250"	25

FI = Fully Insulated

HEAT SHRINK & SOLDER QUICK DISCONNECTS



22-10 GAUGE ASSORTMENT KIT

- Includes the most popular heat shrink solder and seal terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment resealable plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6539	Butt Connectors (40), Ring Terminals (50) Spade Terminals (10), Male Disconnects .250" (10) Female Disconnects .250" (10)	120

> Kits

SEE PAGE 164 FOR
OUR FULL LINE OF
ASSORTMENT KITS

HEAT SHRINK & SOLDER TERMINAL & CONNECTOR



NYLON BUTT CONNECTORS



22-8 GAUGE		
PART #	GAUGE	PACK
83-2190	22-16	100
84-2190	22-16	15
88-2390	16-14	1000
83-2390	16-14	100
84-2390	16-14	15
83-2590	12-10	100
84-2590	12-10	15
84-2592	8	10

VINYL BUTT CONNECTORS



22-6 GAUGE		
PART #	GAUGE	PACK
88-2180	22-16	1000
83-2180	22-16	100
84-2180	22-16	15
88-2380	16-14	1000
83-2380	16-14	100
84-2380	16-14	15
88-2580	12-10	1000
83-2580	12-10	100
84-2580	12-10	15
84-2170	8	5
84-2980	6	10
83-2602	22-10 Assortment Pack	20

VINYL STEP DOWN BUTT CONNECTORS



22-8 GAUGE		
PART #	GAUGE	PACK
84-2114	22-18 to 16-14	10
84-2314	16-14 to 12-10	10
84-2514	12-10 to 8	10

SEAMLESS + BUTTED SEAM – 22-6 GAUGE

PART #	GAUGE	TYPE	PACK
83-3110	22-16	Seamless	100
84-3110	22-16	Seamless	15
88-3100	22-16	Butted Seam	1000
83-3100	22-16	Butted Seam	100
84-3100	22-16	Butted Seam	15
88-3111	16-14	Seamless	1000
83-3111	16-14	Seamless	100
84-3111	16-14	Seamless	15
88-3101	16-14	Butted Seam	1000
83-3101	16-14	Butted Seam	100
84-3101	16-14	Butted Seam	15
83-3112	12-10	Seamless	100
84-3112	12-10	Seamless	15
88-3102	12-10	Butted Seam	1000
83-3102	12-10	Butted Seam	100
84-3102	12-10	Butted Seam	15
83-3103	8	Seamless	100
83-3104	6	Seamless	100

UNINSULATED BUTT CONNECTORS



22-16 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2204	22-16	4-6	50
84-2204	22-16	4-6	15
83-2205	22-16	8-10	50
84-2205	22-16	8-10	15
83-2206	22-16	1/4"	50
84-2206	22-16	1/4"	15
83-2207	22-16	5/16"	50
84-2207	22-16	5/16"	15
83-2208	22-16	3/8"	50
84-2208	22-16	3/8"	15

NYLON RING TERMINALS



22-16 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2102	22-16	4-6	100
83-2104	22-16	8-10	100
84-2104	22-16	8-10	15
83-2105	22-16	1/4"	100
84-2105	22-16	1/4"	15
84-2140	22-16	5/16"	15
84-2108	22-16	3/8"	15

VINYL RING TERMINALS



NYLON RING TERMINALS

16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2209	16-14	4-6	50
84-2209	16-14	4-6	15
83-2210	16-14	8	50
84-2210	16-14	8	15
83-2447	16-14	10	50
84-2211	16-14	10	15
83-2448	16-14	1/4"	50
84-2212	16-14	1/4"	15
83-2213	16-14	5/16"	50
84-2213	16-14	5/16"	15
83-2449	16-14	3/8"	50
84-2449	16-14	3/8"	15



VINYL RING TERMINALS

16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2302	16-14	4-6	100
84-2310	16-14	4-6	15
88-2303	16-14	6-8	1000
83-2303	16-14	6-8	100
84-2303	16-14	6-8	15
88-2304	16-14	8-10	1000
83-2304	16-14	8-10	100
84-2304	16-14	8-10	15
88-2305	16-14	1/4"	1000
83-2305	16-14	1/4"	100
84-2305	16-14	1/4"	15
83-2340	16-14	5/16"	100
84-2340	16-14	5/16"	15
83-2308	16-14	3/8"	100
84-2308	16-14	3/8"	15



NYLON RING TERMINALS

12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2455	12-10	8-10	50
84-2215	12-10	8-10	15
83-2456	12-10	1/4"	50
84-2456	12-10	1/4"	15
83-2457	12-10	5/16"	50
84-2457	12-10	5/16"	15
83-2458	12-10	3/8"	50
84-2458	12-10	3/8"	15
83-2216	12-10	1/2"	50
84-2216	12-10	1/2"	15



12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2502	12-10	4-6	100
84-2502	12-10	4-6	15
83-2504	12-10	8-10	100
84-2504	12-10	8-10	15
83-2505	12-10	1/4"	100
84-2505	12-10	1/4"	15
83-2540	12-10	5/16"	100
84-2540	12-10	5/16"	15
83-2507	12-10	3/8"	100
84-2507	12-10	3/8"	15
84-2509	12-10	1/2"	15

VINYL RING TERMINALS



8 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2705	8	1/4"	25
84-2740	8	5/16"	25
84-2707	8	3/8"	25
84-2709	8	1/2"	25

VINYL RING TERMINALS



6 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2941	6	1/4"	25
84-2940	6	5/16"	25
84-2942	6	3/8"	25
84-2909	6	1/2"	25

VINYL RING TERMINALS



4 GAUGE

PART #	GAUGE	STUD SIZE	PACK
84-2910	4	1/4"	10
84-2911	4	5/16"	10
84-2912	4	3/8"	10
84-2913	4	1/2"	10

VINYL RING TERMINALS



UNINSULATED RING TERMINALS



22-6 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
84-3000	22-16	6	50
84-3001	22-16	8	50
84-3002	22-16	10	50
84-3003	22-16	1/4"	50
84-3004	16-14	6	50
84-3005	16-14	8	50
84-3006	16-14	10	50
84-3007	16-14	1/4"	50
84-3022	16-14	5/16"	50
84-3021	16-14	3/8"	50
84-3008	12-10	8	50
84-3009	12-10	10	50
84-3010	12-10	1/4"	50
84-3011	12-10	5/16"	50
84-3012	12-10	3/8"	50
84-3013	8	10	25
84-3014	8	1/4"	25
84-3015	8	5/16"	25
84-3016	8	3/8"	25
84-3017	6	10	25
84-3018	6	1/4"	25
84-3019	6	5/16"	25
84-3020	6	3/8"	25

NYLON SPADE TERMINALS



22-16 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
83-2217	22-16	4-6	50
84-2217	22-16	4-6	15
83-2218	22-16	8-10	50
84-2218	22-16	8-10	15

VINYL SPADE TERMINALS



22-16 GAUGE			
PART #	GAUGE	STUD SIZE	PACK
83-2132	22-16	4-6	100
84-2132	22-16	4-6	15
83-2134	22-16	8-10	100
84-2134	22-16	8-10	15
84-2136	22-16	6 Flanged	15
84-2138	22-16	8 Flanged	15
84-2139	22-16	10 Flanged	15

16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2219	16-14	4-6	50
84-2219	16-14	4-6	15
83-2220	16-14	8-10	50
84-2220	16-14	8-10	15

NYLON SPADE TERMINALS



16-14 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2332	16-14	4-6	100
84-2332	16-14	4-6	15
83-2334	16-14	8-10	100
84-2334	16-14	8-10	15
84-2336	16-14	4-6 Flanged	15
84-2338	16-14	8-10 Flanged	15

VINYL SPADE TERMINALS



12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2221	12-10	4-6	50
84-2221	12-10	4-6	15
83-2222	12-10	8-10	50
84-2222	12-10	8-10	15


NYLON SPADE TERMINALS



12-10 GAUGE

PART #	GAUGE	STUD SIZE	PACK
83-2532	12-10	4-6	100
84-2532	12-10	4-6	15
83-2534	12-10	8-10	100
84-2534	12-10	8-10	15

VINYL SPADE TERMINALS



NYLON MALE BULLET CONNECTORS	16-14 GAUGE				
 84-2397	PART #	GAUGE	BULLET SIZE	MATE	PACK
	83-2398	16-14	.157"	83-2401	50
	84-2398	16-14	.157"	84-2401	15
	83-2227	16-14	.180"	83-2402	50
	84-2397	16-14	.180"	84-2402	15



NYLON FEMALE RECEPTACLE CONNECTORS	16-14 GAUGE – FULLY INSULATED				
 84-2402	PART #	GAUGE	RECEPTACLE SIZE	MATE	PACK
	83-2401	16-14	.157"	83-2398	50
	84-2401	16-14	.157"	84-2398	15
	83-2402	16-14	.180"	83-2227	50
	84-2402	16-14	.180"	84-2397	15

VINYL MALE BULLET CONNECTORS	22-10 GAUGE				
 84-2194 83-2394 83-2560	PART #	GAUGE	BULLET SIZE	MATE	PACK
	84-2194	22-16	.157"	84-2185	15
	83-2394	16-14	.157"	83-2400	100
	84-2394	16-14	.157"	84-2400	15
	83-2250	16-14	.180"	83-2251	100
	84-2250	16-14	.180"	84-2251	15
	83-2395	16-14	.195"	83-2396	100
	84-2395	16-14	.195"	84-2396	15
	83-2560	12-10	.195"	83-2561	100

VINYL FEMALE RECEPTACLE CONNECTORS	22-10 GAUGE – FULLY INSULATED				
 84-2185 84-2400 83-2561	PART #	GAUGE	RECEPTACLE SIZE	MATE	PACK
	84-2185	22-16	.157"	84-2194	15
	83-2400	16-14	.157"	83-2394	100
	84-2400	16-14	.157"	84-2394	15
	83-2251	16-14	.180"	83-2250	100
	84-2251	16-14	.180"	84-2250	15
	83-2396	16-14	.195"	83-2395	100
	84-2396	16-14	.195"	84-2395	15
	83-2561	12-10	.195"	83-2560	100

DOUBLE FEMALE BULLET RECEPTACLES			
 84-2388	PART #	FEATURES	QUANTITY
	84-2388	Double Female Bullet Receptacle .157"	15

VINYL PIN TERMINAL CONNECTORS	22-10 GAUGE			
 84-2171 84-2172 84-2173	PART #	GAUGE	PIN DIAMETER	PACK
	84-2171	22-16	.075"	15
	84-2172	16-14	.075"	15
	84-2173	12-10	.110"	15

22-10 GAUGE				QUICK SPLICE CONNECTORS
SELF STRIPPING TAP CONNECTORS				 84-2183 84-2383 84-2378 84-2377 88-2379 84-2583
PART #	GAUGE	COLOR	PACK	
84-2183	22-16	Red	5	
84-2377	22-14	Blue	5	
88-2383	16-14	Blue	1000	
83-2383	16-14	Blue	25	 84-2183 84-2378 84-2377 88-2379 84-2583
84-2383	16-14	Blue	5	
84-2378	18-14	Blue (with Gel)	5	
88-2379	18-14	White	1000	
83-2583	12-10	Yellow	25	
84-2583	12-10	Yellow	3	

22-10 GAUGE				QUICK SPLICE CONNECTORS
SELF-STRIPPING SPECIAL ADAPTERS				 84-2906 84-2384 84-2904 84-2905 84-2907
PART #	GAUGE	COLOR	FEATURES	PACK
84-2906	22-16	Red	Female Tap	25
83-2904	16-14	Blue	Female Tap	100
84-2904	16-14	Blue	Female Tap	5
84-2384	18-14	Black	Bullet Tap .157"	3
84-2905	12-10	Yellow	Female Tap	25
84-2907	16-14	Blue	Disconnect (25)	25 pair

				UNINSULATED SPECIAL ADAPTERS
PART #	STYLE	TAB SIZE	PACK	 84-2915 84-2900 84-2901
84-2900	Female – Double Male (Flat)	.250"	15	
84-2901	Female – Double Male (Piggyback)	.250"	15	
84-2915	Male	.250"	10	


22-10 GAUGE				VINYL 3 & 4 WAY CONNECTORS
 84-2381 84-2382	PART #	STYLE	GAUGE	PACK
	84-2181	3 Way	22-16	5
	84-2382	4 Way	16-14	5
	84-2381	3 Way	16-14	5
	84-2582	4 Way	12-10	5
	84-2581	3 Way	12-10	5

CLOSED END CONNECTORS



22-10 GAUGE			
PART #	GAUGE	FEATURES	PACK
83-3182	22-16	Closed End	100
84-3182	22-16	Closed End	15
83-3382	16-14	Closed End	100
84-3382	16-14	Closed End	15
83-3582	12-10	Closed End	100
84-3582	12-10	Closed End	15

TWIST ON WIRE CONNECTORS – THERMOPLASTIC



22-10 GAUGE					
PART #	GAUGE	MIN/MAX	COLOR	VOLTAGE	PACK
84-2704	22-14	2 #22; 3 #16	Blue	300V	15
84-2701	22-14	1 #18 + 1 #20; 4 #16 + 1 #20	Orange	600V	15
84-2702	22-14	3 #20; 1 #10 + 2 #14 + 1 #16	Yellow	600V	5
84-2703	18-10	3 #18; 3 #10	Red	600V	5

PREMIUM

SERVICE

In a world of automated phone systems and outsourced customer service it's rare to contact **REAL PEOPLE** with **REAL EXPERIENCE** providing **REAL SOLUTIONS**. That is exactly what you get from Grote's team of expert Sales and Customer Solutions personnel.

01

KNOWLEDGEABLE CUSTOMER SOLUTIONS TEAM

Our dedicated personnel are there to handle all of your questions related to ordering and inventory availability. You have questions, we are here to help!

02

EXPERT TECHNICAL SUPPORT

Rely on our experienced professionals for technical support so that you make the right purchasing decisions and minimize customer downtime.

03

REAL-TIME INVENTORY WITH G24/7™

Grote's G24/7™ gives you the capability to check inventory, place orders and track order status. Available when you need, as you need, because making it easier for you to do business with us matters.

TIP

WIRE COLOR

To keep yourself from tearing your hair out, color-code your wire by accessory. It will help you keep track of which wire goes where during installation and troubleshooting.

VINYL

- Kit contains 650 of the most popular automotive electrical terminals and accessories
- Assorted gauges (22-16, 16-14, 12-10) & stud sizes (#6 – 1/4")
- Matrix chart on inside lid describes piece parts, provides illustrations and details individual re-order part numbers

PART #	KIT CONTENTS	QUANTITY
83-6540	Butt Connectors (115) Ring Terminals (200) Spade Terminals (40) Male Disconnects .250" (80) Female Disconnects .250" (90) Bullet Connectors .157" (30) Bullet Receptacles .157" (30) Tap Connectors (15) Cable Ties – Black (50) Wire Terminal Crimper (1)	650

TERMINAL & CONNECTOR ASSORTMENT KIT



VINYL

PART #	KIT CONTENTS	QUANTITY
83-2608	Retail Clam Pack Butt Connectors (10) Ring Terminals (24) Female Disconnects .250" (3)	37

PART #	KIT CONTENTS	QUANTITY
83-6554 <i>Includes Hang Tab</i>	Butt Connectors (34) Ring Terminals (51) Male Disconnects .250" (6) Female Disconnects .250" (8)	99

TERMINAL & CONNECTOR ASSORTMENT KITS



VINYL

PART #	KIT CONTENTS	QUANTITY
83-2600	Rings, Spades and Quick Disconnects	100

VINYL ASSORTMENTS



NYLON TERMINAL & CONNECTOR

22-10 GAUGE ASSORTMENT KITS

- Includes the most popular Nylon terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-16, 16-14 and 12-10 gauges
- 12 compartment resealable plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6538	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects .250" (10) Female Disconnects .250" (10)	120

PART #	KIT CONTENTS	QUANTITY
83-6555 <i>Includes Hang Tab</i>	Butt Connectors (24) Ring Terminals (26) Male Disconnects .250" (10) Female Disconnects .250" (10)	70

PART #	KIT CONTENTS	QUANTITY
83-2609	Retail Clam Pack Butt Connectors (13) Ring Terminals (15) Male Disconnects .250" (3) Female Disconnects .250" (6)	37

CRIMP, SOLDER & SEAL TERMINAL & CONNECTOR

22-10 GAUGE ASSORTMENT KIT

- Includes the most popular heat shrink crimp, solder and seal terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6542	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects (10) Female Disconnects (10)	120

22-10 GAUGE ASSORTMENT KIT

- Includes the most popular heat shrinkable crimp splices and terminals
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6503	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects (10) Female Disconnects (10)	120

PART #	KIT CONTENTS	QUANTITY
83-6556 <i>Includes Hang Tab</i>	Butt Connectors (30) Ring Terminals (44) Male Disconnects (5) Female Disconnects (6)	85

PART #	KIT CONTENTS	QUANTITY
83-2610	Retail Clam Pack Butt Connectors (9) Ring Terminals (22) Female Disconnects (3)	34

RATCHET STYLE – 22-8 GAUGE

- Ratchet style tool properly crimps Heat Shrink and Crimp Solder & Seal Terminals
- Specially designed die ensures a clean crimp that protects the Heat Shrink jacket from over crimping
- 22-8 gauge is the largest crimp range industry wide
- Ergonomic design for easy use; a must have for any mechanic, installer or repair professional

83-6519

22-10 GAUGE

- Crimps heat shrink and crimp solder and seal terminals and connectors 22-10 Gauge
- Ratchet style is easy to use and provides a superior crimp
- Makes a clean crimp without damaging the conductor
- Ergonomic design for comfort
- 10" long

83-6524

HEAT SHRINKABLE TERMINAL & CONNECTORS



83-6503



83-2610

HEAT SHRINK TERMINAL CRIMPING TOOL



83-6519

HEAT SHRINK TERMINAL CRIMPING TOOL



83-6524



DEUTSCH TERMINALS

Deutsch DT and DTM series environmentally sealed connectors are designed specifically for cable to cable applications. The connectors will provide reliability and performance in the engine or transmission, under the hood, on the chassis, or in the cab. Thermoplastic, flame-retardant housings offer a wide operating temperature range while silicone rear wire and interface seals allow the connectors to withstand extreme temperatures and moisture. Contact insertion and removal do not require any special tools. All connectors are designed to carry the rated current at the maximum rated temperature.

DEUTSCH CONNECTOR CRIMPING TOOLS
SEE PAGE 64



DTM SERIES



DEUTSCH TERMINAL AND CONNECTORS

- Ideal for use under the hood, transmission, lighting connections and other engine compartments
- Operating temp: -55°C (-67°F) to 125°C (257°F)
- Silicon seals; Nickel plated contacts
- Current rating 7.5 amps @ 125°C (257°F) continuous
- Designed for lower amperage connectors

DTM SERIES: TERMINALS

PART #	GAUGE	TYPE	CRIMP STYLE	OEM #	PACK
84-2481	24-20	Male	Solid Barrel	0460-202-20141	10
84-2480	24-20	Female	Solid Barrel	0462-201-20141	10
84-2483	20-16	Male	Open Barrel	1060-20-0122	10
84-2482	20-16	Female	Open Barrel	1062-20-0122	10

DTM SERIES: HOUSING & WEDGELOCK

- Includes 2 Plugs or Receptacles and 2 wedge locks

PART #	PINS	TYPE	CONTENTS	OEM #	PACK
84-2484	2	Plug	Plug & Wedgelo	DTM06-2S, WM-2S	2 pair
84-2485	2	Receptacle	Receptacle & Wedgelo	DTM04-2P, WM-2P	2 pair
84-2486	3	Plug	Plug & Wedgelo	DTM06-3S, WM-3S	2 pair
84-2487	3	Receptacle	Receptacle & Wedgelo	DTM04-3P, WM-3P	2 pair
84-2488	4	Plug	Plug & Wedgelo	DTM06-4S, WM-4S	2 pair
84-2489	4	Receptacle	Receptacle & Wedgelo	DTM04-4P, WM-4P	2 pair
84-2490	6	Plug	Plug & Wedgelo	DTM06-6S, WM-6S	2 pair
84-2491	6	Receptacle	Receptacle & Wedgelo	DTM04-6P, WM-6P	2 pair
84-2492	8	Plug	Plug & Wedgelo	DTM06-8S, WM-8S	2 pair
84-2493	8	Receptacle	Receptacle & Wedgelo	DTM04-8P, WM-8P	2 pair

> Kits

SEE PAGE 64-65
FOR DEUTSCH
KITS AND TOOLS

DEUTSCH TERMINAL AND CONNECTORS

- Ideal for use under the hood, transmission, lighting connections and other engine compartments
- Operating temp: -55°C (-67°F) to 125°C (257°F)
- Silicon seals; Nickel plated contacts
- Current rating 13 amps @ 125°C (257°F) continuous

DT SERIES: TERMINALS

PART #	GAUGE	TYPE	CRIMP STYLE	OEM #	PACK
84-2462	20-16	Male	Solid Barrel	0460-202-16141	10
84-2459	20-16	Female	Solid Barrel	0462-201-16141	10
84-2468	16-14	Male	Solid Barrel	0460-215-16141	10
84-2467	16-14	Female	Solid Barrel	0462-209-16141	10
84-2464	18-16	Male	Open Barrel	1060-16-0122	10
84-2463	18-16	Female	Open Barrel	1062-16-0122	10
84-2466	16-14	Male	Open Barrel	1060-14-0122	10
84-2465	16-14	Female	Open Barrel	1062-14-0122	10

DT SERIES: HOUSING & WEDGELOCK

- Includes 2 Plugs or Receptacles and 2 wedge locks

PART #	PINS	TYPE	CONTENTS	OEM #	PACK
84-2471	2	Plug	Plug & Wedgelo	DT06-2S, W2S	2 pair
84-2470	2	Receptacle	Receptacle & Wedgelo	DT04-2P, W2P	2 pair
84-2473	3	Plug	Plug & Wedgelo	DT06-3S, W3S	2 pair
84-2472	3	Receptacle	Receptacle & Wedgelo	DT04-3P, W3P	2 pair
84-2475	4	Plug	Plug & Wedgelo	DT06-4S, W4S	2 pair
84-2474	4	Receptacle	Receptacle & Wedgelo	DT04-4P, W4P	2 pair
84-2477	6	Plug	Plug & Wedgelo	DT06-6S, W6S	2 pair
84-2476	6	Receptacle	Receptacle & Wedgelo	DT04-6P, W6P	2 pair
84-2479	8	Plug	Plug & Wedgelo	DT06-8S, W8S	2 pair
84-2478	8	Receptacle	Receptacle & Wedgelo	DT04-8P, W8P	2 pair
84-2495	12	Plug	Plug & Wedgelo	DT06-12S, W12S	1 pair
84-2494	12	Receptacle	Receptacle & Wedgelo	DT04-12P, W12P	1 pair
84-2469			Cavity Plug	114017	2




DT SERIES



Did You Know?

Deutsch
Part Numbering
System Explained:

Each segment of the OEM number for Deutsch Terminal and Connector products identify specifications of the product.



OEM replacement terminals and housings offer an alternative solution to the costly replacement of the entire electrical wiring harness. OEM replacement connection systems are ideal for low energy electronic circuits and are available in sealed and unsealed formats. These connectors have been internationally standardized for universal under-the-hood vehicle applications.

- Exact match for specific OEM styles
- Male connectors are packaged in clam shell resealable blisters
- Female receptacles are packaged in polybags
- OEM terminals and housings are packaged in economical 10-packs
- Also available in Bulk quantities
- Tin plated brass terminals



WEATHER PACK TERMINALS



TERMINALS

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2000	20-18	Male	Open Barrel	12089040	10
84-2001	20-18	Female	Open Barrel	12089188	10
84-2048	16-14	Male	Open Barrel	12124582	10
84-2047	16-14	Female	Open Barrel	12124580	10
84-2049	12-10	Male	Open Barrel	12124587	10
84-2050	12-10	Female	Open Barrel	12124581	10
84-2002	20-18	Green	Cable Seal	15324982	10
84-2082	16-14	Grey	Cable Seal	15324980	10
84-2081	12-10	Blue	Cable Seal	15324981	10
84-2003		Green	Cable Plug	12010300	10

CONNECTOR ASSEMBLIES

PART #	TERMINAL TYPE	DESCRIPTION	OEM #	PACK
84-2004	Male	1 Cavity Housing	12010996	10
84-2005	Female	1 Cavity Housing	12015791	10
84-2006	Male	2 Cavity Housing	12010973	10
84-2007	Female	2 Cavity Housing	12015792	10
84-2008	Male	3 Cavity Housing	12010717	10
84-2009	Female	3 Cavity Housing	12015793	10
84-9459	Male	4 Cavity Housing - Flat	12010974	5
84-9460	Female	4 Cavity Housing - Flat	12015797	5
84-2033	Male	4 Cavity Housing - Square	12015024	10
84-2034	Female	4 Cavity Housing - Square	12015798	10
84-2053	Male	6 Cavity Housing	12010975	10
84-2052	Female	6 Cavity Housing	12015799	10

CABLE SEALS AND PLUGS



PART #	OEM#	GAUGE	COLOR	PACK
88-2002	15324982	20-18	Green	1000
84-2002	15324982	20-18	Green	10
88-2082	15324980	16-14	Grey	1000
84-2082	15324980	16-14	Grey	10
88-2081	15324981	12-10	Blue	1000
84-2081	15324981	12-10	Blue	10
84-2003	12010300		Green	10

METRI PACK 150 SERIES

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2023	20-18	Male	Open Barrel	12047581	10
84-2036	24	Female	Open Barrel	12052466	10
84-2037	20-18	Female	Open Barrel	12103881	10
84-2024	20-18	Female	Open Barrel	12047767	10

METRI PACK 280 SERIES

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2026	20-18	Male	Open Barrel	12034047	10
84-2025	18-14	Male	Open Barrel	12020116	10
84-2078	—	Male	5 Cavity Housing	12084891	1
84-2079	—	—	Tab for 84-2078	12015798	5
84-2027	20-18	Female	Open Barrel	12034046	10
84-2035	18-14	Female	Open Barrel	12066214	10
84-2075	—	Female	5 Cavity Housing	12084891	5
84-2076	—	—	Tab for 84-2075	15324857	5
68680	14	Female	Assembly with 20" leads	—	1

METRI PACK 480 SERIES

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2028	16-14	Male	Open Barrel	12020120	10
84-2041	16-14	Female	Open Barrel	12124304	10

METRI PACK 630 SERIES

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2029	16-14	Female	Open Barrel	12015870	10

56 SERIES

PART #	GAUGE	TERMINAL TYPE	CRIMP STYLE	OEM #	PACK
84-2011	16-14	Male	Open Barrel	2971962	10
84-2013	16-14	Female	Open Barrel	2962447	10

METRI PACK TERMINALS



OEM TERMINAL REMOVAL TOOLS

- Economical tools designed to release both solid and open barrel terminals

PART #	TERMINAL STYLE
84-9450	Metri Pack & Weather Pack terminal release tool, for male & female terminals
83-6521	Metri Pack terminal release tool, narrow blade, for 150, 280 series terminals
83-6522	Metri Pack terminal release tool, wide blade, for 56, 480, 630, 800 series terminals
83-6570	Combo Pack (84-9450, 83-6521 & 83-6522)

> Kits

SEE PAGE 64-65 FOR
WEATHER PACK
KITS AND TOOLS



DEUTSCH TERMINAL & CONNECTOR



83-6549

ASSORTMENT KIT

- Perfect assortment kit for any repair or service technician or installer
- Includes 98 pieces of the most popular Deutsch, DT Series terminals and housings
- 20-16, 18-16 and 16-14 gauge terminals; 2, 3, 4, 6 and 8 way plugs/receptacles & wedge locks
- Crimping and removal tools also available
- 12 compartment resealable plastic box with re-order chart on the inside cover

83-6549

DEUTSCH TERMINAL & CONNECTOR



83-6568

SERVICE KIT

- Ideal for any repair shop or installer of Deutsch terminals & connectors
- A complete 6 piece tool kit to for crimping and releasing both solid and open barrel Deutsch terminals
- Includes 3 crimping tools for open and closed barrel terminals and 3 terminal release tools
- Supplied in a durable plastic molded storage case for easy storage and application
- Includes 83-6562, 83-6563 & 83-6564 crimping tools
- Includes 83-6567 assortment removal tool kit

83-6568

CRIMPING TOOLS – DEUTSCH



83-6562

83-6563

83-6516

83-6564

- Economical, ratcheting tools designed to crimp solid barrel or open barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6562	14, 16, 18	Solid Barrel
83-6563	20, 22	Solid Barrel
83-6564	14, 16, 18, 20, 24	Open Barrel (Deutsch + Weather Pack)

- OEM tools designed to crimp solid barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6516	12, 14, 16, 18, 20	Solid Barrel – 4 Indent Crimp

REMOVAL TOOLS – DEUTSCH



83-6565

83-6566

83-6567

- Economical tools designed to release both solid and open barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6565	14, 16	Solid & Open Barrel; Gold Handle
83-6566	16, 18	Solid & Open Barrel; Blue Handle
83-6567*	14, 16, 18, 20, 24	Solid & Open Barrel; Gold, Blue/Red Handles

*Kit contains 3 tools

WEATHER PACK

- Kit Includes 250 assorted pieces; assorted 22-14 GA terminals; 1, 2 and 4 cavity nylon housings and 22-18 & 16-14 GA cable seals
- Sturdy plastic container keeps all the connectors in one convenient location
- Easy to use reference re-order chart included
- Use Grote OEM crimping tool 84-9449 and extractor tool 84-9450 for superior connection and repair. Tools sold separately

83-6536

TERMINAL & CONNECTOR REPAIR KIT



83-6536

WEATHER PACK

- 185 male and female weather pack OEM terminals, cable seals and plugs
- Includes an OEM ratchet style crimping tool and extractor tool for a complete repair and installation kit
- Sturdy plastic container keeps connectors in one convenient location
- Easy to use reference re-order chart included

83-6546

TERMINAL & CONNECTOR INSTALLATION & REPAIR KIT



83-6546

WEATHER PACK & METRI PACK

- Can crimp terminals 24-14 gauge
- Heavy duty steel construction
- Ergonomic design with cushioned grips

PART #	DESCRIPTION
83-6569	For open barrel Weather Pack, Metri Pack 150 & 280 series and Molex terminals
84-9449	For open barrel Weather Pack terminals – ratchet style

OEM OPEN BARREL CRIMPING TOOL



83-6569

84-9449

05

WIRE & CABLE

FILS ET CÂBLES

ALAMBRES Y CABLES

- 67 Technical information
- 68 Primary Wire
- 70 Brake Cable & Portable Extension Cable
- 71 SXL & Bonded Wire
- 72 Trailer Cable
- 74 Battery Cable
- 75 Welding Cable
- 76 Booster Cable – Twin Conductor
- 77 Wire/Cable Displays

DETERMINING WIRE AND CABLE GAUGE SIZE BY CIRCUIT AMPS AND LENGTH

TOTAL CIRCUIT AMPS	WIRE GAUGE FOR LENGTH IN FEET (TOTAL CIRCUIT LENGTH)												
	12V	3'	5'	7'	10'	15'	20'	25'	30'	40'	50'	75'	100'
1	18	18	18	18	18	18	18	18	18	18	18	18	18
3	18	18	18	18	18	18	18	18	18	18	18	14	14
5	18	18	18	18	18	18	18	18	18	16	14	12	12
7	18	18	18	18	18	18	18	16	16	14	14	10	10
10	18	18	18	18	18	16	16	16	14	12	12	10	10
15	18	18	18	18	18	14	14	12	12	12	10	8	8
20	16	16	16	16	16	14	12	10	10	10	10	8	6
24	14	14	14	14	14	12	12	10	10	10	8	6	6
30	12	12	12	12	12	10	10	10	10	10	6	4	4
40	10	10	10	10	10	10	10	8	8	6	6	4	2
50	8	8	8	8	8	8	8	8	8	6	6	2	2
100	4	4	4	4	4	4	4	4	4	4	2	1	1/0
150	2	2	2	2	2	2	2	2	2	2	1	2/0	2/0
200	1/0	1/0	1/0	1/0	1/0	1/0	1/0	1/0	1/0	1/0	1/0	4/0	4/0

HOW TO MATCH CABLE & EQUIPMENT

TYPE OF EQUIPMENT	TYPICAL WIRE GAUGE
Garden Tractor	8, 6, 4
Compact Car, RV	6, 4
Standard Car	4, 2
Full-size Car, Van	2, 1
Tractor, Light Truck, Construction	1/0
HD Tractor, Truck, Bus, Construction	2/0, 3/0
Extra Heavy Duty	4/0, 250 MCM

METRIC AND AWG WIRE SIZE

METRIC VALUES ARE EXPRESSED AS A RANGE AND VARY BY COUNTRY																
mm ²	0.35	0.50	0.75	1	2	3	4-5	6-8	9-13	14-21	22-35	36-42	43-53	54-68	69-86	87-107
AWG	22	20	18	16	14	12	10	8	6	4	2	1	1/0	2/0	3/0	4/0

AWG: American Wire Gauge



ROHS COMPLIANCE The RoHS Directive stands for “the restriction of the use of certain hazardous substances in electrical and electronic equipment”. This Directive bans the placing on the EU market of new electrical and electronic equipment containing more than agreed levels of lead, cadmium, mercury, hexavalent chromium, polybrominated biphenyl (PBB) and polybrominated diphenyl ether (PBDE) flame retardants.

GPT – GENERAL PURPOSE THERMOPLASTIC WIRE



- Primary wire is single conductor based PVC jacketed wire
- PVC insulation resists heat up to 80°C (176°F) and provides protection from weather conditions and abrasives
- Maximum temperature rating -40°C (-40°F) to 80°C (176°F)
- Used for automotive, truck and marine applications
- Meets SAE J1128 specifications; rated to 60V
- Available in 25', 100' and 1000' spools
- Bulk sizes available
- Custom length wires available by special order only
- Made in North America

6 GAUGE (AUTOMOTIVE)

COLOR	25'	100'	1000'
Red	89-3000	87-3000	—
Black	89-3002	87-3002	—

8 GAUGE

COLOR	25'	100'	1000'
Red	89-4000	87-4000	—
Black	89-4002	87-4002	—
White	89-4007	87-4007	—

10 GAUGE

COLOR	25'	100'	1000'
Red	89-5000	87-5000	88-5000
Brown	89-5001	87-5001	—
Black	89-5002	87-5002	88-5002
Green	89-5006	87-5006	—
White	89-5007	87-5007	88-5007
Blue	89-5010	87-5010	—
Yellow	89-5011	87-5011	—

12 GAUGE

COLOR	25'	100'	1000'
Red	89-6000	87-6000	88-6000
Brown	89-6001	87-6001	88-6001
Black	89-6002	87-6002	88-6002
Green	89-6006	87-6006	88-6006
White	89-6007	87-6007	88-6007
Blue	89-6010	87-6010	88-6010
Yellow	89-6011	87-6011	88-6011



GPT – GENERAL PURPOSE THERMOPLASTIC WIRE

14 GAUGE

COLOR	25'	100'	1000'
Red	89-7000	87-7000	88-7000
Brown	89-7001	87-7001	88-7001
Black	89-7002	87-7002	88-7002
Green	89-7006	87-7006	88-7006
White	89-7007	87-7007	88-7007
Blue	89-7010	87-7010	88-7010
Yellow	89-7011	87-7011	88-7011
Orange	89-7012	87-7012	88-7012
Purple	—	87-7013	88-7013
Pink	—	87-7014	—
Gray	—	87-7003	—

16 GAUGE

COLOR	25'	100'	1000'
Red	89-8000	87-8000	88-8000
Brown	89-8001	87-8001	88-8001
Black	89-8002	87-8002	88-8002
Green	89-8006	87-8006	88-8006
White	89-8007	87-8007	88-8007
Blue	89-8010	87-8010	88-8010
Yellow	89-8011	87-8011	88-8011
Orange	89-8012	87-8012	88-8012
Purple	—	87-8013	88-8013
Pink	—	87-8014	—
Gray	—	87-8003	88-8003

18 GAUGE

COLOR	25'	100'	1000'
Red	89-9000	87-9000	88-9000
Brown	89-9001	87-9001	88-9001
Black	89-9002	87-9002	88-9002
Green	89-9006	87-9006	88-9006
White	89-9007	87-9007	88-9007
Blue	89-9010	87-9010	88-9010
Yellow	89-9011	87-9011	88-9011
Orange	—	87-9012	88-9012
Purple	—	—	88-9013
Pink	—	—	88-9014
Gray	—	87-9003	—

20 GAUGE

COLOR	25'	100'	1000'
Red	—	87-2010	—
Black	—	87-2012	—
White	—	87-2015	—
Blue	—	87-2017	—



83-6512
Wire Stripper
See page 172

PVC JACKETED BRAKE CABLE



Split Flex Tubing: See page 94

- PVC jacketed wire resists grease, oil, gasoline and acids
- Used for automotive, truck and marine applications
- Maximum temperature rating -40°C (-40°F) to 80°C (176°F)
- Meets SAE J1128 specifications; rated to 60V
- Custom lengths also available

2 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
10	Yellow, Green	50'	82-5509
10	Yellow, Green	100'	82-5508
10	Yellow, Green	1000'	82-5507
10	Blue, White	1000'	82-5590
12	Black, White	50'	82-5512
12	Black, White	100'	82-5511
12	Black, White	500'	82-5550
12	Black, White	1000'	82-5510
14	Black, White	20'	82-5504
14	Black, White	100'	82-5502
14	Black, White	1000'	82-5503
16	Black, White	100'	82-5500
16	Black, White	1000'	82-5501

3 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
12	White, Green, Black	1000'	82-5591
14	Red, Green, Black	100'	82-5520
16	Red, Green, Black	100'	82-5522

4 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Red, Green, Black, White	100'	82-5521
16	Red, Green, Black, White	100'	82-5519

PARALLEL BONDED WIRE



82-5514

- Ideal for RV, boat and utility trailers
- PVC insulation resists heat up to 80°C (176°F); provides protection from weather conditions and abrasives
- Maximum temp. rating -40°C (-40°F) to 80°C (176°F)
- Meets SAE J1128 specifications; rated to 60V

4 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	White, Brown, Yellow, Green	25'	82-5515
14	White, Brown, Yellow, Green	100'	82-5514
16	White, Brown, Yellow, Green	25'	82-5524
16	White, Brown, Yellow, Green	100'	82-5525
18	White, Brown, Yellow, Green	25'	82-5527
18	White, Brown, Yellow, Green	100'	82-5526



TYPE SJE00W

PORTABLE EXTENSION CABLE

- Black TPE jacketing provides premium oil resistance, sunlight, chemical and water resistance
- Rated at 300 Volt; Meets UL and CSA specifications
- Cable is suitable for use in temperatures between -40°C (-40°F) to maximum 105°C (221°F)
- Ideal for indoor and outdoor temporary power uses, portable industrial machinery, compressors, conveyor and automated production equipment
- All extension cord cable is spooled



2 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Black, White	50'	82-5902
14	Black, White	100'	82-5901
14	Black, White	500'	82-5901-500

3 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Black, White, Green	50'	82-5905
14	Black, White, Green	100'	82-5904
16	Black, White, Green	50'	82-5908
16	Black, White, Green	100'	82-5907

Molded Connectors
82-1025



See page 13



82-5902



82-5907

TYPE SXL

HEAVY DUTY PRIMARY WIRE

- SXL wire is designed to withstand harsher environments than general purpose primary wire
- SXL has an annealed copper conductor that is insulated with cross linked polyethylene base
- XLPE insulation provides a thicker jacket that resists heat up to 125°C (257°F) and provides protection from weather conditions and abrasives
- Maximum temp. rating: -40°C (-40°F) to 125°C (257°F)
- Resistant to grease, oil, gasoline and acids
- Meets SAE J1128 specifications; rated to 60V
- Additional sizes and gauges available upon request



GAUGE	COLOR	LENGTH	PART #
14	Red	100'	87-0000
14	Black	100'	87-0002
16	Red	100'	87-2000
16	Brown	100'	87-2001
16	Black	100'	87-2002
16	White	100'	87-2007



87-2002



87-2001



87-2000



TRAILER CABLE

LOW TEMPERATURE



DURABLE
CONSTRUCTION



MADE IN
NORTH AMERICA



SAE J1128™
STANDARD

- Used for wiring trucks and trailers where cable flexibility in extreme temperatures is a must
- Blue vinyl outer jacket provides protection from weather conditions and abrasive materials
- PVC insulation resists temperature ratings of -65°C (-85°F) to 105°C (221°F)
- Meets SAE J1128 specifications; rated to 60V
- Resistant to gasoline and oil; U.V. resistant
- Designed for 12V and 24V systems; made in North America



2 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Black, White	100'	82-5822
14	Black, White	250'	82-5822-250
14	Black, White	500'	82-5822-500

3 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Black, White, Red	100'	82-5823
14	Black, White, Red	250'	82-5823-250
14	Black, White, Red	500'	82-5823-500

4 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Yellow, Green, Brown, Red	100'	82-5824
14	Yellow, Green, Brown, Red	250'	82-5824-250
14	Yellow, Green, Brown, Red	500'	82-5824-500

6 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Yellow, Green, Brown, White, Red, Black	100'	82-5825
14	Yellow, Green, Brown, White, Red, Black	250'	82-5825-250
14	Yellow, Green, Brown, White, Red, Black	500'	82-5825-500

7 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5827
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	250'	82-5827-250
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	500'	82-5827-500
6/12, 1/10	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5826
6/12, 1/10	Yellow, Green, Brown, White, Red, Black, Blue	250'	82-5826-250
6/12, 1/10	Yellow, Green, Brown, White, Red, Black, Blue	500'	82-5826-500
4/12, 2/10, 1/8	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5828
4/12, 2/10, 1/8	Yellow, Green, Brown, White, Red, Black, Blue	250'	82-5828-250



82-5822



82-5824



82-5827

- Used for wiring trucks and trailers
- Black vinyl outer jacket provides protection from weather conditions and abrasive materials
- PVC insulation resists temperature ratings of -40°C (-40°F) to 80°C (176°F)
- Meets SAE J1128 specifications; rated to 60V
- ABS cable meets SAE J2394 specifications
- Designed for 12V and 24V systems; made in North America



4 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Yellow, Green, Brown, White	100'	82-5602
14	Yellow, Green, Brown, White	500'	82-5603
14	Yellow, Green, Brown, Red	100'	82-5600
14	Yellow, Green, Brown, Red	500'	82-5601

6 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Yellow, Green, Brown, White, Red, Black	100'	82-5604
14	Yellow, Green, Brown, White, Red, Black	500'	82-5605
16	Yellow, Green, Brown, White, Red, Black	100'	82-5623
16	Yellow, Green, Brown, White, Red, Black	500'	82-5620

7 CONDUCTOR

GAUGE	COLOR	LENGTH	PART #
14	Yellow, Green, Brown, White, Red, Black, Blue	50'	82-5610
14	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5609
14	Yellow, Green, Brown, White, Red, Black, Blue	250'	82-5619
14	Yellow, Green, Brown, White, Red, Black, Blue	500'	82-5614
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	50'	82-5612
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5611
6/14, 1/12	Yellow, Green, Brown, White, Red, Black, Blue	500'	82-5615
6/12, 1/10	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5606
6/12, 1/10	Yellow, Green, Brown, White, Red, Black, Blue	500'	82-5607

ABS

GAUGE	COLOR	LENGTH	PART #
4/12, 2/10, 1/8	Yellow, Green, Brown, White, Red, Black, Blue	50'	82-5622
4/12, 2/10, 1/8	Yellow, Green, Brown, White, Red, Black, Blue	100'	82-5621
4/12, 2/10, 1/8	Yellow, Green, Brown, White, Red, Black, Blue	250'	82-5624

PLUG & SOCKET



82-1019



82-1002

JUNCTION BOX



82-1000

See pages 10-16



DURABLE
CONSTRUCTION



MADE IN
NORTH AMERICA



SAE J1128™
STANDARD



82-5600



82-5606



82-5622

BATTERY CABLE – TYPE SGR



- Ideal for use as an interconnection between batteries and a starter or as a ground in a vehicle
- 100% Copper Cable; made in North America
- Ethylene Propylene Diene Monomer Rubber (EPDM) Insulation
- Provides better flexibility than standard PVC starter cable
- Jacket rated at -40°C (-40°F) to 105°C (221°F)
- Meets all SAE code J1127 specifications; rated @ 60V
- All battery cable is spooled



6 GAUGE

COLOR	25'	50'	100'
Black	82-5722	82-5725	82-5726
Red	82-6722	82-6725	82-6726

4 GAUGE

COLOR	25'	50'	100'
Black	82-5714	82-5713	82-5712
Red	82-6717	82-6713	82-6712

2 GAUGE

COLOR	25'	50'	100'
Black	82-5711	82-5710	82-5709
Red	82-6718	82-6710	82-6709

1 GAUGE

COLOR	25'	50'	100'
Black	82-5708	82-5707	82-5706
Red	82-6719	82-6707	82-6706

1/0 GAUGE

COLOR	25'	50'	100'
Black	82-5705	82-5704	82-5703
Red	82-6720	82-6704	82-6703

2/0 GAUGE

COLOR	25'	50'	100'
Black	82-5702	82-5701	82-5700
Red	82-6721	82-6701	82-6700

3/0 GAUGE

COLOR	25'	50'	100'
Black	82-5723	82-5715	82-5733
Red	82-6723	82-6715	82-6733

4/0 GAUGE

COLOR	25'	50'	100'
Black	82-5743	82-5716	82-5753
Red	82-6743	82-6716	82-6753



EZ-FIND

FOR COMPLETE
TECHNICAL SPECS
VISIT OUR WEBSITE

WELDING CABLE



- Ideal for use as an interconnection between batteries and a starter or as a ground in a vehicle
- Abrasion, salt and chemical resistant; good flame resistance
- Fine stranded copper conductor; made in North America
- Provides better flexibility than standard PVC starter cable
- Jacket rated at -50°C (-58°F) to 105°C (221°F) – Rated @ 600V
- Meets all SAE J1127 specifications
- All welding cable is spooled



6 GAUGE

COLOR	25'	100'
Black	82-5732	82-5734
Red	82-6732	82-6734

4 GAUGE

COLOR	25'	100'
Black	82-5724	82-5735
Red	82-6727	82-6735

2 GAUGE

COLOR	25'	100'
Black	82-5721	82-5736
Red	82-6728	82-6736

1 GAUGE

COLOR	25'	100'
Black	82-5737	82-5738
Red	82-6746	82-6738

1/0 GAUGE

COLOR	25'	100'
Black	82-5739	82-5740
Red	82-6739	82-6740

2/0 GAUGE

COLOR	25'	100'
Black	82-5730	82-5731
Red	82-6730	82-6731

3/0 GAUGE

COLOR	25'	100'
Black	82-5741	82-5742
Red	82-6741	82-6742

4/0 GAUGE

COLOR	25'	100'
Black	82-5744	82-5745
Red	82-6744	82-6745



EZ-FIND

FOR COMPLETE
TECHNICAL SPECS
VISIT OUR WEBSITE

BOOSTER CABLE

TWIN CONDUCTOR



- Make up your own booster cables
- Combine with heavy duty clamps for superior charging power
- Can be used with SB type connectors for plug in convenience
- Ideal for tarps system (dump truck / dump trailer)
- Insulation stays flexible in cold weather; bonded cable resists tangling
- 100% fine-stranded copper meets SAE J1127 specifications
- Temperature rated to -40°F (-40°C); rated @ 60V or less

GAUGE	OUTSIDE DIAMETER	COLOR	LENGTH	PART #
8 GA	.320" x .700"	Black & Yellow	1,500'	82-5759-1500
6 GA	.360" x .780"	Black & Orange	100'	82-5760
6 GA	.360" x .780"	Black & Orange	1,200'	82-5760-1200
4 GA	.410" x .880"	Black & White	100'	82-5761
4 GA	.410" x .880"	Black & White	500'	82-5761-500
2 GA	.450" x .960"	Black & Red	100'	82-5762

CABLE SLITTER/STRIPPER TOOL

HEAVY DUTY: 8 - 4/0 GAUGE



- Slits & strips round battery & trailer cables
- Can strip 8 GA to 4/0 GA wire, battery and trailer cables
- Self-adjusting cutting depth
- Makes a clean strip without damaging wire strands
- Blade swivels for longitudinal/spiral cuts
- Ergonomic design

83-6515

9" HAND HELD CABLE CUTTER



- Cuts cables up to 2/0 Gauge
- Ergonomic design with insulated grips

84-9088

PRIMARY WIRE DISPENSER

The Grote Wire Dispenser provides a unique, compact and effective inventory management solution for spooled wire.

- Unit holds up to 123 spools of wire – 63 x 100' spools of wire and 60 x 25' spools of primary wire
- Can accommodate 12GA-18 GA wire spools
- Ease of re-stocking through the top loading lid
- See through display provides inventory at-a-glance for immediate re-stocking
- Heavy gauge steel makes this unit rugged and very stable
- Effective use of shelf space improves revenue per square foot
- Mix-‘n-match – Stock the primary wire and cable you need to support your unique customers
- Wire not included

00872

▶ ONLY 34" WIDE X 17" HIGH X 12" DEEP Holds up to 7,800' of wire!



Top loading lid eliminates re-stocking hassles

WIRE & CABLE DISPLAY

- Constructed of heavy-duty steel, painted powder blue
- Can accommodate a variety of primary wire, battery cable or welding cable assortments in one display
- Steel bars can be removed to accommodate larger spools
- Mounting brackets included for mounting, safety and functionality
- Can be mounted or used as a stand alone display
- No assembly required
- Made in North America
- 27" wide x 18 1/4" tall x 6 1/4" deep; 11 lbs
- Wire not included

00870



06

SUPPORT & PROTECTIVE PRODUCTS

PRODUITS DE FIXATION
ET DE PROTECTION

PRODUCTOS DE SOPORTE
Y PROTECCIÓN

- 80 Nylon Cable Ties
- 84 Mounting Bases & Installation Tools
- 86 Heat Shrink Tubing
- 92 Heat Guns & Torches
- 94 Tube and Loom
- 96 Clamps, Clips & Grommets

WIRE & CABLE MANAGEMENT IS VITAL IN TODAY'S VEHICLES AND EQUIPMENT. GROTE'S SELECTION OF SUPPORT & PROTECTIVE PRODUCTS PROVIDE OPTIONS FOR ALL TYPES OF APPLICATIONS. EVERYTHING TO PROPERLY AFFIX, HANG, WRAP, BUNDLE AND SECURE EQUIPMENT'S CRITICAL POWER DELIVERY WIRES AND CABLES IN EQUIPMENT AND VEHICLES IS ALL RIGHT HERE. YOU NEED IT, GROTE'S GOT IT!





Protect critical wire and cable systems in your vehicle. Reduce downtime and maintenance costs with Grote's Support and Protective products.

NYLON CABLE TIES



- Made of general purpose (PA66) Polyamide 6.6 nylon material
- Flame rating: UL 94 V-2. All weather ties flame rating: UL 94 HB
- Provides flexible bundling and mounting options for wire, cable and multiple size hoses
- Absorbs vibration, insulates cables and provides abrasion protection
- Black ties are U.V. coated and provide superior protection from drying out and cracking
- Continuous operating temperature -40°C (-40°F) to 85°C (185°F)
- Use Grote's ergonomic and mechanical cable tie tools for an easy effective application (83-6527, 83-6528) on page 81
- Made in North America



FEDERAL ASTM SPECIFICATIONS: D-4066PA0111 | FDA SPECIFICATIONS: CFR177.1500

LIGHT DUTY TIES

PACK OF 25	PACK OF 100	PACK OF 1000	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
	83-6000	83-6000-3	4.10" (104mm)	.11" (2.8mm)	0.75" (19mm)	18 lbs	White
	83-6001	83-6001-3	4.10" (104mm)	.11" (2.8mm)	0.75" (19mm)	18 lbs	Black
	83-6004	83-6004-3	8.00" (203mm)	.11" (2.8mm)	2.20" (56mm)	18 lbs	White
	83-6005	83-6005-3	8.00" (203mm)	.11" (2.8mm)	2.20" (56mm)	18 lbs	Black



83-6004

STANDARD TIES

PACK OF 25	PACK OF 100	PACK OF 1000	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
	83-6006	83-6006-3	5.60" (142mm)	.26" (6.6mm)	1.25" (32mm)	40 lbs	White
	83-6007	83-6007-3	5.60" (142mm)	.26" (6.6mm)	1.25" (32mm)	40 lbs	Black
85-6018	83-6018	83-6018-3	8.00" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	White
85-6019	83-6019	83-6019-3	8.00" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Black
85-6020	83-6020	83-6020-3	11.10" (282mm)	.19" (4.8mm)	3.00" (76mm)	50 lbs	White
85-6021	83-6021	83-6021-3	11.10" (282mm)	.19" (4.8mm)	3.00" (76mm)	50 lbs	Black
85-6026	83-6026	83-6026-3	14.10" (358mm)	.19" (4.8mm)	4.00" (101mm)	50 lbs	White
85-6025	83-6025	83-6025-3	14.10" (358mm)	.19" (4.8mm)	4.00" (101mm)	50 lbs	Black



83-6019

HEAVY TIES

PACK OF 25	PACK OF 100	PACK OF 1000	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
	83-6017	83-6017-3	7.70" (196mm)	.30" (7.6mm)	2.37" (60mm)	120 lbs	White
	83-6016	83-6016-3	7.70" (196mm)	.30" (7.6mm)	2.37" (60mm)	120 lbs	Black
85-6028	83-6028	83-6028-3	14.10" (358mm)	.30" (7.6mm)	4.00" (101mm)	120 lbs	White
85-6029	83-6029	83-6029-3	14.10" (358mm)	.30" (7.6mm)	4.00" (101mm)	120 lbs	Black



83-6029

HIGH PERFORMANCE ALL WEATHER TIES

PART #	DESCRIPTION	LENGTH	WIDTH	BUNDLE DIA.	STRENGTH	PK SIZE	COLOR
83-6001C	Light Duty	4.10" (104mm)	.11" (2.8mm)	0.75" (19mm)	18 lbs	100	Black
83-6007C	Standard	5.60" (142mm)	.26" (6.6mm)	1.25" (32mm)	40 lbs	100	Black
83-6019C	Standard	8.00" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	100	Black
83-6021C	Standard	11.10" (282mm)	.19" (4.8mm)	3.00" (76mm)	50 lbs	50	Black
83-6025C	Standard	14.10" (358mm)	.19" (4.8mm)	4.00" (101mm)	50 lbs	50	Black
83-6016C	Heavy Duty	7.70" (196mm)	.30" (7.6mm)	2.37" (60mm)	120 lbs	30	Black
83-6029C	Heavy Duty	14.10" (358mm)	.30" (7.6mm)	4.00" (101mm)	120 lbs	20	Black

ALL-WEATHER



ALWAYS STRONG



ALWAYS FLEXIBLE

EXTRA HEAVY DUTY TIES

25 PACK	50 PACK	LENGTH	WIDTH	BUNDLE DIA.	STRENGTH	COLOR
	83-6121	24.00" (609mm)	.34" (8.6mm)	8.0" (203mm)	175 lbs	White
85-6120	83-6120	24.00" (609mm)	.34" (8.6mm)	8.0" (203mm)	175 lbs	Black
	83-6118	36.00" (914mm)	.34" (8.6mm)	11.00" (279mm)	175 lbs	White
	83-6119	36.00" (914mm)	.34" (8.6mm)	11.00" (279mm)	175 lbs	Black
	83-6122	48.00" (1,219mm)	.34" (8.6mm)	15.00" (381mm)	175 lbs	White
	83-6123	48.00" (1,219mm)	.34" (8.6mm)	15.00" (381mm)	175 lbs	Black



85-6120

RELEASABLE DUAL CLAMP TIES

- Unique one piece design with the 1/4" mounting head centered on the strap
- Constructed of high impact nylon material; with UL flame rating 94-HB excellent UV resistance
- Can reduce the need to carry numerous clamps and other mounting devises
- Is releasable and extremely flexible for tough to reach areas
- Continuous operating temperature -40°C (-40°F) to 110°C (230°F)



FEDERAL ASTM SPECIFICATIONS: D-4066PA0151

10 PACK	50 PACK	LENGTH	WIDTH	BUNDLE DIA. (EA. SIDE)	STRENGTH	MOUNTING HOLE	COLOR
85-6040	83-6040	13.0" (331mm)	.50" (12.7mm)	1.3" (33.02mm)	150 lbs	.250" (6.35mm)	Black
85-6041	83-6041	19.2" (489mm)	.50" (12.7mm)	2.3" (58.42mm)	150 lbs	.250" (6.35mm)	Black



83-6040

RELEASABLE TIES

25 PACK	100 PACK	LENGTH	WIDTH	BUNDLE DIA.	STRENGTH	COLOR
	83-6012	8.00" (203mm)	.18" (4.5mm)	2.00" (51mm)	50 lbs	White
	83-6013	8.00" (203mm)	.18" (4.5mm)	2.00" (51mm)	50 lbs	Black
	83-6022	15.00" (381mm)	.18" (4.5mm)	4.00" (101mm)	50 lbs	White
85-6023	83-6023	15.00" (381mm)	.18" (4.5mm)	4.00" (101mm)	50 lbs	Black
85-6163	83-6163	22.40" (569mm)	.49" (12.5mm)	5.90" (150mm)	250 lbs	Black



83-6023

SCREW MOUNT TIES

25 PACK	50 PACK	100 PACK	LENGTH	WIDTH	BUNDLE DIA.	STRENGTH	MOUNT HOLE	COLOR
85-6104		83-6104	8.00" (203mm)	.18" (4.5mm)	2.00" (51mm)	50 lbs	#10	White
		83-6105	8.00" (203mm)	.18" (4.5mm)	2.00" (51mm)	50 lbs	#10	Black
		83-6107	11.50" (292mm)	.18" (4.5mm)	3.00" (76mm)	50 lbs	#10	Black
		83-6027	14.50" (368mm)	.18" (4.5mm)	4.00" (101mm)	50 lbs	#10	White
		83-6108	14.50" (368mm)	.18" (4.5mm)	4.00" (101mm)	50 lbs	#10	Black
	83-6037	83-6116	15.75" (400mm)	.30" (7.6mm)	4.00" (101mm)	120 lbs	.250"	White
	83-6117		15.75" (400mm)	.30" (7.6mm)	4.00" (101mm)	120 lbs	.250"	Black



83-6104

NYLON CABLE TIE ASSORTMENT



- Made of general purpose (PA66) Polyamide 6.6 nylon material
- Assortment of most popular ties; available in white, U.V. resistant black, assorted colors
- Compact and attractive polybag packaging with a clear view of all the products inside

PART #	PACK SIZE	COLOR
83-6506	125	White
83-6507	125	Black

Includes 25 x 4" (18lb.); 25 x 8" (40lb.); 25 x 7", 11" & 14" (50 lb.)

PART #	PACK OF	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH
83-6514	50	7.6" (193mm)	.18" (4.6mm)	2.0" (51mm)	50 lbs
83-6559	50	11.1" (282mm)	.19" (4.8mm)	3.0" (76mm)	50 lbs

Includes 10 x Blue, Yellow, Green, Orange and Red

CABLE TIE ASSORTMENT CANISTER



- Assortment of light to standard duty nylon cable ties
- 10 different cable ties ranging from 4" to 12" and in various colors
- 100 of each of the cable ties (total 1,000 pieces)
- Convenient storage canister
- Ideal use; at home, the garage or workshop

PART #	PACK OF	LENGTHS	STRENGTH	COLORS
83-6600	1,000	4", 6", 8", 12"	18lb–50lb	Yellow, Blue, Red, Green, White

COLOR TIES



Color Ties help to ease wire identification


PACK OF 25	PACK OF 1000	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
85-6030	83-6030-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Red
85-6031	83-6031-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Orange
85-6032	83-6032-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Blue
85-6033	83-6033-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Yellow
85-6034	83-6034-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Green
85-6035	83-6035-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Purple
85-6036	83-6036-3	8.0" (203mm)	.19" (4.8mm)	1.87" (47mm)	50 lbs	Gray

WIDE STRAP CABLE TIES



- Made of general purpose (PA66HIRHS) Polyamide 6.6 high impact, heat-stabilized nylon
- UL flame rating 94-HB, excellent UV resistance
- Continuous operating temp: -40°C (-40°F) to 110°C (230°F)

- The wide strap tie minimizes pinching on soft bundles
- Features a low profile head to provide compact bundling
- Accommodates a large bundle diameter range .375" (9.5mm) – 4.125" (104.7mm)



FEDERAL ASTM SPECIFICATIONS: D-4066PA0161

PACK OF 25	PACK OF 100	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
85-6042	83-6042	9.1" (231mm)	.5" (12.7mm)	2.25" (57mm)	120 lbs	Black
85-6043	83-6043	15.1" (244mm)	.5" (12.7mm)	4.12" (104mm)	120 lbs	Black

FIR TREE

MOUNT & CABLE TIE ASSEMBLIES

- Made of general purpose (PA66HS) Polyamide 6.6 nylon heat-stabilized material
- UL flame rating 94V-2 cable tie; 94-HB mount – excellent UV resistance
- Provides low insertion force and high extraction force
- Continuous operating temperature -40°C (-40°F) to 105°C (221°F) cable tie; -40°C (-40°F) to 110°C (230°F) mount



FEDERAL ASTM SPECIFICATIONS: D-4066PA0121

PUSH MOUNT

- Fir tree design grips to inside of a hole for materials like sheet metal, wood and cast iron
- Panel thickness range: .052"-.280" (1.32mm-7.0mm)

PACK OF 100	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
83-6045	8.27" (210mm)	.18" (4.57mm)	1.90" (48mm)	50 lbs	Black



DOMED FIR TREE

MOUNT & CABLE TIE ASSEMBLY

- The domed head tie provides a tight rattle-free installation and outside serrated strap has ribs designed for convoluted tubing. Dome also keeps out dust and liquids
- Panel thickness range: .250"-.280" (6.3mm-7.0mm)

PACK OF 100	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
83-6048	6.69" (170mm)	.20" (5.1mm)	1.22" (31mm)	45 lbs	Black



FIR TREE

MOUNT & CABLE TIE ASSEMBLY

- Cable mount can slide along the cable tie for easy assembly. Fir tree design grips to inside of a hole for materials like sheet metal, wood, and cast iron
- Popular on trailer manufacturing
- Panel thickness range: .028"-.193" (.75mm-3.0mm)

PACK OF 100	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
83-6046	8.00" (203mm)	.18" (4.6mm)	1.75" (44.5mm)	50 lbs	Black




BUTTON HEAD CABLE TIE

- Made of general purpose (PA66HIRHS) Polyamide 6.6 high impact, heat stabilized nylon
- UL flame rating 94-HB, excellent UV resistance
- Continuous operating temperature -40°C (-40°F) to 110°C (230°F)

- The buttons tie provides parallel entry and exit through the button head
- With teeth on both sides of the strap it can be installed through bi-directional looping clockwise or counter-clockwise
- Standoff tabs prevent tie head from seating into the button head
- Pilot bushings protect strap from abrasion
- Popular OEM product – reducing part numbers and labor time

FEDERAL ASTM SPECIFICATIONS: D-4066PA0161

PACK OF 50	LENGTH	WIDTH	BUNDLE DIAMETER	STRENGTH	COLOR
83-6049	9.63" (244mm)	.22" (5.6mm)	2.62" (66.7mm)	105 lbs	Black
83-6052	15.00" (578mm)	.30" (7.6mm)	4.33" (110mm)	130 lbs	Black



EDGE CLIP & CABLE TIE ASSEMBLIES



- Made of general purpose (PA66HIRHS) Polyamide 6.6 high impact, heat stabilized nylon
- UL flame rating 94V-2 cable tie; 94-HB mount – excellent UV resistance
- Continuous operating temperature -40°C (-40°F) to 110°C (230°F)
- The edge clip is designed to route bundles by securing to the edge of plastic or metal rails without the need for a mounting hole
- The clips are easy to secure and are extremely economical
- Comes complete with cable tie and edge clip
- Panel thickness range: .039"-.117" (1mm-3mm)

FEDERAL ASTM SPECIFICATIONS: D-4066PA0161

PACK OF 25	PACK OF 100	LENGTH	BUNDLE DIAMETER	STRENGTH	MOUNT STYLE	COLOR
85-6063	83-6063	7.9" (200mm)	1.80" (45mm)	50 lbs	Top	Black

HEAVY DUTY MOUNTS



- Made of general purpose (PA66HIRHS) Polyamide 6.6 high impact, heat stabilized nylon material; UL flame rating 94-HB, excellent UV resistance
- Continuous operating temperature -40°C (-40°F) to 110°C (230°F)
- When used with a cable tie, eliminates the need to carry multiple sizes of clamps
- Provides quick and easy service in the field; replace the cable tie only
- Has an excellent heat ratio and commonly used near an engine block
- Can accommodate up to .5" wide cable ties
- Contains a small tab inside the mounting hole that allows you to pre-install the mount on a stud before securing with a washer and a nut
- Additional sizes available upon request

FEDERAL ASTM SPECIFICATIONS: D-4066PA0161

PACK OF 25	PACK OF 100	MOUNTING HOLE	LENGTH	WIDTH	MAX TORQUE	COLOR
85-6060	83-6060	.187" (4.8mm)	.76" (19.3mm)	2.25" (57mm)	115 lb - in.	Black
85-6061	83-6061	.250" (6.4mm)	.76" (19.3mm)	2.25" (57mm)	115 lb - in.	Black
85-6062	83-6062	.312" (8.0mm)	.76" (19.3mm)	2.25" (57mm)	115 lb - in.	Black

CABLE TIE MOUNTING BASES



- Made of general purpose (PA66) Polyamide 6.6 nylon material; rubber-based adhesive
- Accommodates 18-50 lb cable ties

PART #	LENGTH	WIDTH	MOUNTING STYLE/HOLE	PACK	COLOR
83-6030	0.75" (19.05mm)	0.75" (19.05mm)	4-Way with adhesive, #6	50	White
83-6032	0.75" (19.05mm)	0.75" (19.05mm)	4-Way with adhesive, #6	50	Black
83-6031	1.00" (25.4mm)	1.00" (25.4mm)	4-Way with adhesive, #10	50	White
83-6033	1.00" (25.4mm)	1.00" (25.4mm)	4-Way with adhesive, #10	50	Black

CABLE TIE TENSION AND CUTTER "GUN STYLE" TOOL

- Cable tie tension and cut-off tools reduce operator fatigue and speed assembly
- Ergonomic design ideally fits the operators hand
- Cushion grip for comfort
- Quick tension adjustability for a flush "cut-off"
- Equipped with a hook for easy hanging

MILITARY SPECIFICATIONS: MS90387-1 (83-6527), MS90387-2 (83-6528)

83-6527 For 18-50 lb Ties
83-6528 For 18-250 lb Ties



83-6527



83-6528

CABLE TIE TENSION AND CUTTER "TWISTER" TOOL

- Compact tensioning tool enables cinching and cutting
- For cable ties ranging from 18lbs-50lbs tensile strength
- Twisting action leaves a clean edge to prevent chaffing of wires
- Lightweight ergonomic design
- 7" long

83-6509



83-6509



Did You Know?




CABLE TIES WILL ABSORB AND RELEASE MOISTURE AS THE ATMOSPHERE CHANGES!

Grote recommends the following information to ensure the most reliable and efficient cable tie application:

- Straps should be stored in an unopened bag in a storage environment at (70°F and 50% humidity)
- Installation temperature should be at or greater than (32°F and 40% humidity)
- Over tightening of the strap can cause stress on the pawl and greater potential of failure



SHRINK RATIO



POLYOLEFIN HEAT SHRINKABLE TUBING

Product Line	SWT	DWT	FDWA	FDWA-CLEAR	HWA	DWA
Type	Single Wall	Dual Wall	Dual Wall	Dual Wall	Dual Wall	Dual Wall
Shrink Ratio	2 to 1	3 to 1	3 to 1	3 to 1	3 to 1	4 to 1
Outer Wall Construction	Thin/Flexible	Semi-Rigid	Flexible	Flexible	Rigid	Semi-Rigid
Inner Wall Construction	N/A	Encapsulant Lined	Adhesive Lining	Adhesive Lining	Adhesive Lining	Adhesive Lining
Minimum Shrink Temp.	70°C (158°F)	125°C (257°F)	80°C (176°F)	80°C (176°F)	90°C (195°F)	110°C (230°F)
Operating Temperature	-55°C (135°C)	-55°C (110°C)	-40°C (110°C)	-40°C (110°C)	-55°C (110°C)	-40°C (130°C)
Moisture Resistance	Low	Medium	High	High	High	High
Flame Retardancy	Good		Excellent		Excellent	Excellent
Abrasion Protection	Good	Excellent	Excellent	Excellent	Excellent	Excellent
Strain Relief & Insulation	Good	Excellent	Excellent	Excellent	Excellent	Excellent
Mil Spec	23053/5 Class 1, 3	20353/4 Class 1	23053/4 Class 3		23053/15 Class 1	
ROHS	Yes	Yes	Yes	Yes	Yes	Yes
Other	Lead/Halogen Free	Lead/Halogen Free		Lead/Halogen Free		

* Custom lengths and additional materials available upon request

ADHESIVE LINED, DUAL WALL

4:1 SHRINK RATIO, DWA

Dual Wall is designed to meet automotive industry requirements for environmental sealing and electrical insulation. It has a dual wall construction. The outer jacket is semi-rigid, radiation cross-linked polyolefin that is flame retardant and provides strain relief and abrasion protection. The inner layer is a unique hot-melt adhesive designed to adhere to all major automotive wire and terminal insulations. The adhesive forms an effective barrier against fluids and moisture; protects harnesses from corrosion and water wicking and covers a wide temperature range. This product is an OEM approved product.

SPECS / APPROVALS: UL E85381RECOGNIZED, 600 V, 125° C



SIZE	LENGTH	PACK	WIRE SIZE	PART #
1/16" - 3/16" (.225")	6"	6	22-12 GA	84-5006
1/16" - 3/16" (.225")	6"	20	22-12 GA	84-5006-3
1/16" - 3/16" (.225")	48"	6	22-12 GA	84-5006-48
3/16" - 1/4" (.293")	6"	6	20-10 GA	84-5007
3/16" - 1/4" (.293")	6"	20	20-10 GA	84-5007-3
3/16" - 1/4" (.293")	48"	6	20-10 GA	84-5007-48
1/4" - 3/8" (.427")	6"	6	16-8 GA	84-5008
1/4" - 3/8" (.427")	6"	20	16-8 GA	84-5008-3
1/4" - 3/8" (.427")	48"	6	16-8 GA	84-5008-48
1/2" - 5/8" (.700")	6"	6	8-1/0 GA	84-5009
1/2" - 5/8" (.700")	6"	10	8-1/0 GA	84-5009-3
1/2" - 5/8" (.700")	48"	6	8-1/0 GA	84-5009-48

"HOT MELT" HEAT SHRINK TUBING

Minimum shrink temperature:
110°C (230°F)
Minimum full recovery temperature:
135°C (275°F)
Operating temperature range:
-40°C to 130°C (-40°F to 266°F)



ADHESIVE LINED, DUAL WALL

4:1 SHRINK RATIO, DWA

- 40, 6", Black Dual Wall Heat Shrink pieces
- 6 compartment resealable box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6535	84-5006	1/16" - 3/16"	12
	84-5007	3/16" - 1/4"	12
	84-5008	1/4" - 3/8"	10
	84-5009	1/2" - 5/8"	6

"HOT MELT" HEAT SHRINK TUBING KIT



83-6535

HEAT SHRINK TUBING

Minimum shrink temperature:
80°C (176°F)
Minimum full recovery temperature:
125°C (257°F)
Operating temperature range:
-40°C to 110°C (-40°F to 230°F)

** Remains semi-flexible post-heat*



FLEXIBLE, ADHESIVE LINED, DUAL WALL

3:1 SHRINK RATIO, FDWA & FDWA-CLEAR

Flexible Dual Wall is an adhesive lined heat shrink tubing that provides moisture resistance, strain relief and electrical insulation for splices, terminations, breakouts and mechanical connections. The outer wall is semi-rigid, cross-linked polyolefin, while the inner wall is an adhesive lining that flows with the application of heat. This moisture resistant tubing provides flexibility to insulate and protect irregular shape products. It also provides rugged protection from chemicals, abrasion, vibration and flexing.

SPECS / APPROVALS: UL E35586, 600 V, 125°C | CSA LR31929, 600 V, 125° C



PART #	DESCRIPTION	GAUGE	SIZE	LENGTH	QUANTITY
84-5029	3:1, DUAL WALL, CLEAR	22-18 GA	1/8"	6"	6
84-5030	3:1, DUAL WALL, CLEAR	20-12 GA	3/16"	6"	6
84-5031	3:1, DUAL WALL, CLEAR	16-10 GA	1/4"	6"	6
84-5032	3:1, DUAL WALL, CLEAR	12-8 GA	3/8"	6"	6
84-5033	3:1, DUAL WALL, CLEAR	8-4 GA	1/2"	6"	6
84-5034	3:1, DUAL WALL, CLEAR	4-2/0 GA	3/4"	6"	6
84-5035	3:1, DUAL WALL, CLEAR	1-4/0 GA	1"	6"	6

PART #	DESCRIPTION	GAUGE	SIZE	LENGTH	QUANTITY
84-4015	3:1, DUAL WALL, BLACK	22-18 GA	1/8"	6"	6
84-4015-3	3:1, DUAL WALL, BLACK	22-18 GA	1/8"	6"	20
84-4015-48	3:1, DUAL WALL, BLACK	22-18 GA	1/8"	48"	6
84-4016	3:1, DUAL WALL, BLACK	20-12 GA	3/16"	6"	6
84-4016-3	3:1, DUAL WALL, BLACK	20-12 GA	3/16"	6"	20
84-4016-48	3:1, DUAL WALL, BLACK	20-12 GA	3/16"	48"	6
84-4017	3:1, DUAL WALL, BLACK	16-10 GA	1/4"	6"	6
84-4017-3	3:1, DUAL WALL, BLACK	16-10 GA	1/4"	6"	20
84-4017-48	3:1, DUAL WALL, BLACK	16-10 GA	1/4"	48"	6
84-4018	3:1, DUAL WALL, BLACK	12-8 GA	3/8"	6"	6
84-4018-3	3:1, DUAL WALL, BLACK	12-8 GA	3/8"	6"	20
84-4018-48	3:1, DUAL WALL, BLACK	12-8 GA	3/8"	48"	6
84-4019	3:1, DUAL WALL, BLACK	8-4 GA	1/2"	6"	6
84-4019-3	3:1, DUAL WALL, BLACK	8-4 GA	1/2"	6"	20
84-4019-48	3:1, DUAL WALL, BLACK	8-4 GA	1/2"	48"	6
84-4020	3:1, DUAL WALL, BLACK	4-2/0 GA	3/4"	6"	6
84-4020-3	3:1, DUAL WALL, BLACK	4-2/0 GA	3/4"	6"	10
84-4020-48	3:1, DUAL WALL, BLACK	4-2/0 GA	3/4"	48"	6
84-4021	3:1, DUAL WALL, BLACK	1-4/0 GA	1"	6"	6
84-4021-3	3:1, DUAL WALL, BLACK	1-4/0 GA	1"	6"	10
84-4021-48	3:1, DUAL WALL, BLACK	1-4/0 GA	1"	48"	6

HEAT SHRINK TUBING KIT

FLEXIBLE, ADHESIVE LINED, DUAL WALL

3:1 SHRINK RATIO, FDWA, 50 QTY

PART #	FEATURES	SIZE	LENGTH	QUANTITY
83-6537	84-4015	1/8"	6"	12
	84-4016	3/16"	6"	12
	84-4017	1/4"	6"	12
	84-4018	3/8"	6"	6
	84-4019	1/2"	6"	6
	84-4020	3/4"	6"	2



83-6537

DUAL WALL

3:1 SHRINK RATIO, DWT

Dual Wall is an encapsulant-lined heat shrink tubing that provides moisture resistance, strain relief and electrical insulation for splices, terminations, breakouts and mechanical connections. The outer wall is semi-rigid, cross-linked encapsulant lined, while the inner wall is a meltable encapsulant lining that flows with the application of heat. This moisture resistant tubing provides rugged protection from chemicals, abrasion, vibration and flexing.

SPECS / APPROVALS: UL E85381, 600 V, 125°C | MILITARY AMS-DTL-23053/4 CLASS 1



SIZE	LENGTH PER PIECE	PACK	WIRE SIZE	BLACK PART #	RED PART #
1/8"	6"	6	22-18 GA	84-4006	84-6106
1/8"	6"	20	22-18 GA	84-4006-3	84-6106-3
1/8"	48"	6	22-18 GA	84-4006-48	84-6106-48
1/8"	48"	50	22-18 GA	88-4006	
3/16"	6"	6	20-12 GA	84-4005	84-6105
3/16"	6"	20	20-12 GA	84-4005-3	84-6105-3
3/16"	48"	6	20-12 GA	84-4005-48	84-6105-48
3/16"	48"	50	20-12 GA	88-4005	
1/4"	6"	6	16-10 GA	84-4000	84-6100
1/4"	6"	20	16-10 GA	84-4000-3	84-6100-3
1/4"	48"	6	16-10 GA	84-4000-48	84-6100-48
1/4"	48"	50	16-10 GA	88-4000	
3/8"	6"	6	12-8 GA	84-4001	84-6101
3/8"	6"	20	12-8 GA	84-4001-3	84-6101-3
3/8"	48"	6	12-8 GA	84-4001-48	84-6101-48
3/8"	48"	50	12-8 GA	88-4001	
1/2"	6"	6	8-4 GA	84-4002	84-6107
1/2"	6"	20	8-4 GA	84-4002-3	84-6107-3
1/2"	48"	6	8-4 GA	84-4002-48	84-6107-48
1/2"	48"	50	8-4 GA	88-4002	
3/4"	6"	6	4-2/0 GA	84-4003	84-6103
3/4"	6"	10	4-2/0 GA	84-4003-3	84-6103-3
3/4"	48"	6	4-2/0 GA	84-4003-48	84-6103-48
3/4"	48"	30	4-2/0 GA	88-4003	
1"	6"	6	1-4/0 GA	84-4004	84-6104
1"	6"	10	1-4/0 GA	84-4004-3	84-6104-3
1"	48"	6	1-4/0 GA	84-4004-48	84-6104-48
1"	48"	20	1-4/0 GA	88-4004	

Minimum shrink temperature:
125°C (257°F)
Minimum full recovery temperature:
135°C (275°F)
Operating temperature range:
-55°C to 110°C (-67°F to 230°F)



HEAT SHRINKABLE TUBING KITS



DUAL WALL

3:1 SHRINK RATIO, DWT

- 50, 6", Dual Wall Heat Shrink Pieces
- 6-compartment resealable plastic box
- Re-order chart on inside cover

PART #	FEATURES	QUANTITY
83-6502	Black Tubing	50
83-6505	Red and Black Tubing	50

HEAT SHRINK TUBING

Minimum shrink temperature:
90°C (195°F)
Minimum full recovery temperature:
121°C (250°F)
Operating temperature range:
-55C to 110C (-67F to 230F)



ADHESIVE LINED, HEAVY WALL

3:1 SHRINK RATIO, HWA

Dual Wall is designed for insulating, protecting and sealing electrical connections and low voltage cables. It provides insulation thickness equal to or greater than standard wire insulation. Heavy wall shrink tubing provides an environmental seal and is highly resistant to impact and abrasion. Longer lengths and sizes available upon request.

SPECS / APPROVALS: UL E1 15664					UL
INSIDE DIAMETER PRE HEAT	INSIDE DIAMETER POST HEAT	LENGTH PER PIECE	PACK	PART #	
.750" (19mm)	.220" (5.6mm)	48"	1	84-4030	
1.100" (28mm)	.375" (9.5mm)	48"	1	84-4031	
1.500" (38mm)	.500" (12mm)	48"	1	84-4032	

HEAT SHRINK TUBING

Minimum shrink temperature:
90°C (195°F)
Minimum full recovery temperature:
121°C (250°F)
Operating temperature range:
-55°C to 110°C (-67°F to 230°F)



DUAL WALL

3:1 SHRINK RATIO

Dual Wall is an encapsulant-lined heat shrink tubing that provides moisture resistance, strain relief and electrical insulation for splices, terminations, breakouts and mechanical connections. The outer wall is semi-rigid, cross-linked polyolefin, while the inner wall is a meltable polyolefin that flows with the application of heat. This moisture resistant tubing provides rugged protection from chemicals, abrasion, vibration and flexing. Meets UL #486D requirements.

SPECS / APPROVALS: CSA C22.2 | UL 486D | MILITARY DTL-23053/15, CLASS 2



SIZE	LENGTH PER PIECE	PACK	WIRE SIZE	BLACK PART #	RED PART #
1/2"	1.5"	10	6-2 GA	84-9561	84-9562
3/4"	1.5"	10	4-1/0 GA	84-9563	84-9564
1 1/8"	1.5"	10	2/0-250mcm	84-9565	84-9566

SINGLE WALL

2:1 SHRINK RATIO, SWT

Single Wall is cost effective tubing that insulates and protects electrical connections. It also provides a flexible option for wire bundling. It is made of cross-linked polyolefin and provides good protection from abrasion and moisture. Meets UL VW-1 and CSA OFT flame-retardancy.

SPECS / APPROVALS: CSA LR31929 VW-1, 600 V, 125°C
UL E35586 VW-1, 600 V, 125°C | MILITARY AMS-DTL-23053/5, CLASSES 1 AND 3

SIZE	LENGTH PER PIECE	PACK	BLACK PART #	RED PART #	BLUE PART #	YELLOW PART #
1/8"	6"	6	84-5010	84-4013		
1/8"	100'	Spool	83-4999			
3/16"	6"	6	84-5011	84-4007	84-5020	
3/16"	100'	Spool	83-5000			
1/4"	6"	6	84-5012	84-4008	84-5019	84-5025
1/4"	100'	Spool	83-5001			
3/8"	6"	6	84-5013	84-4009	84-5022	84-5024
3/8"	100'	Spool	83-5002			
1/2"	6"	6	84-5014	84-4011	84-5021	
1/2"	100'	Spool	83-5003			
3/4"	6"	6	84-5015	84-4010	84-5023	
3/4"	100'	Spool	83-5004			
1"	6"	6	84-5016			

* Custom lengths and colors available upon request

HEAT SHRINK TUBING

Minimum shrink temperature:
70°C (158°F)
Minimum full recovery temperature:
90°C (194°F)
Operating temperature range:
-55°C to 135°C (-67°F to 275°F)



SINGLE WALL

2:1 SHRINK RATIO, SWT

- 50, 6", Black Single Wall Heat Shrink Pieces
- 6-compartment resealable plastic box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6545	84-5010	1/8"	12
	84-5011	3/16"	12
	84-5012	1/4"	8
	84-5013	3/8"	6
	84-5014	1/2"	6
	84-5015	3/4"	6

HEAT SHRINKABLE TUBING KIT, BLACK



SINGLE WALL

PART #	FEATURES	SIZE	QUANTITY
83-6533	Black	1/4" x 6"	3
		3/8" x 6"	2
		1/2" x 6"	2

HEAT SHRINK TUBING ASSORTMENT



FLAMELESS HEAT GUN



- Portable, self igniting, multi function heat tool; 7 1/2" long
- Cordless & flameless; OEM approved
- Comes with an attachable heat deflector, cooling tray and replacement orifice
- The wide nozzle has a high output long life catalyst
- Ready to use in 15 seconds; adjustable heat settings
- Gas container capacity: 20 ml
- Recommended butane: Triple Refined
- Continuous Operating Temperature: 250°C to 500°C (480°F to 930°F)
- Maximum Temperature Rating: 750°C (1400°F)

83-6508

HEAT GUN



- Two heat settings; 120 Volt, 10 AMP
- Lightweight (1 lb)
- 3-wire ground cord set
- UL and cUL listed
- Thermoplastic casing
- Minimum Temperature Rating: 260°C (500°F)
- Maximum Temperature Rating: 538°C (1000°F)

83-6501

HANDS-FREE HEAT TOOL



- Hands-free slide lock for continuous use and instant operation
- Ergonomic handle design ensures a non-slip grip
- Removable base for table-top or hand-held use
- 60 minute continuous run time with full charge
- Gas adjustment wheel provides adjustable, long blue torch flame
- Unique shutter lever to easily extinguish ignition flame
- Instant off safety switch
- 1300°C (2500°F)

83-6525

BUTANE POWERED MICRO TORCH



- Compact palm size is perfect for tool kits and field service kits
- Produces an adjustable, wind resistant flame with temperatures up to 1300°C /2500°F, perfect for many microtorch applications
- Built in safety lock with improved easy to use self-ignition system
- Meets consumer products safety commission (CPSC) child safety requirements
- Powered by refillable "fuel cell" (included) with flame adjustment lever
- Built in fuel level viewing window
- Use with Master Ultratane butane for best performance
- Pinpoint flame is perfect for soldering, desoldering, heating shrinking and terminating heating lighting and many other applications
- Patent pending

83-6500

WE KNOW THE POWER OF A GOOD CONNECTION



At Grote Industries, **WE ARE COMMITTED TO TAKING CARE OF OUR CUSTOMERS** by ensuring that they receive the information and products they need, when they need them. That's why we are continually investing in industry-leading technology that allows us to connect to our valued customers.

MANY WAYS TO CONNECT, MANY WAYS TO GROW TOGETHER

From our updated website with instant-search and live technical help, to our completely refreshed **G24/7 ONLINE CUSTOMER SERVICE PLATFORM**, Grote's experienced team of sales and customer solutions experts are never more than a click or a phone call away. Let us help you connect with your customers, with our digital tools, best-in-class customer service and innovative safety solutions.



CONTACT US

CALL US AT 1-800-268-5612, OR CHECK OUT OUR G24/7 ONLINE CUSTOMER SERVICE PLATFORM AT SHOP.GROTE.COM

SPLIT FLEX CONVOLUTED TUBING



- Provides excellent chemical protection. Allows flexible routing of wire, cable, hoses
- Protects hoses, wire and cables from extreme heat and abrasion
- Helps reduce noise and protects wires from stones and other harmful debris
- Slit opening allows for easy installation of wires
- The slit snaps closed after installation to maintain its protective properties
- Applications: Automotive, Truck, Bus, Trailer, Marine, R.V., OE harness manufacturing

NYLON SPLIT LOOM

- Made of lightweight, black nylon material, with grey striping
- Continuous operating temp: -40°C (-40°F) to 125°C (257°F), FMVSS 302 Flame Rating

SPECS: FORD: WSS-M4D933-A1, ES-XU5T-14A099-AA CHRYSLER: MS-DB41 CPN 4059 | ASTM: D4066PA283

SIZE	LENGTH	PACK	PART #	SIZE	LENGTH	PACK	PART #
1/4"	50' (15.2m)	Bag	83-8030	5/8"	50' (15.2m)	Bag	83-8033
1/4"	500' (152m)	Box	83-8030-3	5/8"	500' (152m)	Box	83-8033-3
1/4"	3200' (975m)	Box	83-8030-3200	5/8"	800' (244m)	Box	83-8033-800
3/8"	50' (15.2m)	Bag	83-8031	3/4"	50' (15.2m)	Bag	83-8034
3/8"	500' (152m)	Box	83-8031-3	3/4"	500' (152m)	Box	83-8034-3
3/8"	1900' (579m)	Box	83-8031-1900	3/4"	550' (168m)	Box	83-8034-550
1/2"	50' (15.2m)	Bag	83-8032	1"	50' (15.2m)	Bag	83-8035
1/2"	500' (152m)	Box	83-8032-3	1"	300' (91.4m)	Box	83-8035-3
1/2"	1100' (335m)	Box	83-8032-1100	1.5"	150' (45.7m)	Box	83-8036-3
				2"	100' (30.4m)	Box	83-8037-3

POLYETHYLENE SPLIT LOOM

- Made of lightweight, black polyethylene (PE) material
- Continuous operating temperature -40°C (-40°F) to 93°C (200°F)

SIZE	LENGTH	PACK	PART #	SIZE	LENGTH	PACK	PART #
1/4"	10' (3.0m)	Bag	83-6999	1/2"	100' (30.4m)	Spool	83-8001-S
1/4"	25' (7.6m)	Bag	83-8013	1/2"	500' (152m)	Box	83-8001-3
1/4"	50' (15.2m)	Bag	83-8003	5/8"	50' (15.2m)	Bag	83-8007
1/4"	100' (30.4m)	Spool	83-8003-S	5/8"	100' (30.4m)	Spool	83-8007-S
1/4"	500' (152m)	Box	83-8003-3	5/8"	500' (152m)	Box	83-8007-3
3/8"	8' (2.43m)	Bag	83-7000	3/4"	5' (1.52m)	Bag	83-7002
3/8"	25' (7.6m)	Bag	83-8010	3/4"	50' (15.2m)	Bag	83-8002
3/8"	50' (15.2m)	Bag	83-8000	3/4"	100' (30.4m)	Spool	83-8002-S
3/8"	100' (30.4m)	Spool	83-8000-S	3/4"	500' (152m)	Box	83-8002-3
3/8"	500' (152m)	Box	83-8000-3	1"	5' (1.52m)	Bag	83-6998
7/16"	12' (3.6m)	Bag	83-8018	1"	50' (15.2m)	Bag	83-8004
7/16"	50' (15.2m)	Bag	83-8014	1"	300' (91.4m)	Box	83-8004-3
7/16"	500' (152m)	Box	83-8014-3	1-1/4"	50' (15.2m)	Bag	83-8008
1/2"	7' (2.13m)	Bag	83-7001	1-1/4"	250' (76.2m)	Box	83-8008-250
1/2"	25' (7.6m)	Bag	83-8011	1 1/2"	150' (45.7m)	Box	83-8005-3
1/2"	50' (15.2m)	Bag	83-8001	2"	100' (30.4m)	Box	83-8009-3

SPLIT LOOM INSTALLATION TOOL



- Loom tool allows for easy insertion of singular or multiple wires to split loom
- Ergonomic design, saves valuable time *(and your thumbs)*

SIZE RANGE	PART #	SIZE RANGE	PART #
1/4" – 7/16" Size Range	83-6990	3/4" – 7/8" Size Range	83-6992
1/2" – 5/8" Size Range	83-6991	1" – 1 1/2" Size Range	83-6993

SPIRAL WRAP – SPOOLED



- Made of lightweight Polyethylene material
- Black spiral wrap is U.V. resistant
- Provides wire and cables from abrasion and allows flexible routing options
- Continuous operating temperature: -60°C (-76°F) to 88°C (190°F)

MILITARY SPECS: MIL I-631D, MIL P-21922A (BLACK ONLY) | FED SPEC: LP390 (BLACK AND NATURAL)

SIZE	MIN/MAX BUNDLE DIAMETER	LENGTH	BLACK	NATURAL
1/4"	.187" (4.75mm) – 2" (50.8mm)	100' (30.5m)	83-9008	83-9003
3/8"	.312" (7.92mm) – 3" (76.2mm)	100' (30.5m)	83-9009	83-9000
1/2"	.375" (9.52mm) – 4" (102mm)	100' (30.5m)	83-9007	83-9001
3/4"	.750" (19.1mm) – 5" (127mm)	100' (30.5m)	83-9010	83-9002
1"	1.00" (25.4mm) – 7" (178mm)	100' (30.5m)	83-9011	83-9004

- Used to protect wire harnesses, fuel lines, battery cables, control rods, vacuum lines and anywhere extreme heat or harsh chemicals are present
- Made of lightweight, non-metallic flexible conduit
- Constructed with the highest grade PET (Polyetheylene Terephthalate) yarn and filled with PET monofilament
- Asphalt coating resists oil and fuel, water and other harsh chemicals
- Provides superior abrasion protection and crush resistance
- Extremely flexible and excellent for shock and noise reduction
- Continuous operating temperature -60°C (-76°F) to 163°C (325°F)
- Made in North America

INDUSTRY SPECS: FORD: ESB-M3L38-A, ESF-M3L45-A, ESB-M99H96-A | GENERAL MOTORS: GM-675M, GM-676M, GM-677M, GM-678M | CHRYSLER: MS-542, MS-JZ9-31 | MILITARY: HH-T-791 A,B,C SAE J562A

SIZE	LENGTH	COLOR	PART #
1/4"	100' (30.5m)	Black	87-1000
5/16"	100' (30.5m)	Black	87-1008
3/8"	100' (30.5m)	Black	87-1001
1/2"	100' (30.5m)	Black	87-1002
3/4"	100' (30.5m)	Black	87-1007



ELECTRICAL TAPE

- General purpose vinyl insulating tape
- Excellent resistance to abrasion, moisture and other weather conditions
- 3/4" x 60' black
- Maximum temperature rating -10°C (14°F) to 80°C (176°F)
- CSA 22.2

83-7029 1 Pack
83-7029-3 10 Pack



RUBBER INSULATED STEEL CLAMPS

- Black EPDM extruded material reduces vibration and has excellent heat resistance
- G-60 galvanized steel is resistant to acids, oxidizing, chemicals and weathering
- Ideal for securing wire loom, cables and hydraulic hoses
- Maximum temperature rating -40°C (-40°F) to 148°C (300°F)
- Made in North America; additional bulk sizes available

FEDERAL ASTM SPECIFICATIONS: D2000 M3 BA710 A14 B13 C12 F17 Z1

I.D. SIZE	WIDTH	MOUNTING HOLE	PACK OF 10	PACK OF 100
1/4" (6.4mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8000	83-8100
3/8" (9.5mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8001	83-8101
1/2" (12.7mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8002	83-8102
5/8" (15.9mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8003	83-8103
3/4" (19.1mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8004	83-8104
7/8" (22.2mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8005	83-8105
1" (25.4mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8006	83-8106
1 1/4" (31.7mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8007	83-8107
2" (50.8mm)	5/8" (15.8mm)	3/8" (9.52mm)	84-8008	83-8108

VINYL INSULATED CLAMPS

- Black Plastisol (PVC) dip coating provides excellent resistance to acids, salts & moisture
- Self extinguishing & excellent resistance to impact, vibration and abrasion
- G-60 galvanized steel is resistant to acids, oxidizing, chemicals and weathering
- Ideal for securing wire loom, split flex tubing, cables and hydraulic hoses
- Maximum temperature rating -40°C (-40°F) to 93°C (200°F)
- Made in North America; additional bulk sizes available

I.D. SIZE	WIDTH	MOUNTING HOLE	PACK OF 5	PACK OF 10	PACK OF 15	PACK OF 100
1/4" (6.4mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7007	83-7007
3/8" (9.5mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7010	83-7010
1/2" (12.7mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7008	83-7008
5/8" (15.9mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7018	83-7018
3/4" (19.1mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7009	83-7009
7/8" (22.2mm)	1/2" (12.7mm)	1/4" (6.35mm)			84-7019	83-7019
1" (25.4mm)	1/2" (12.7mm)	1/4" (6.35mm)		84-7020		83-7036
1 1/4" (31.7mm)	1/2" (12.7mm)	1/4" (6.35mm)	84-7021			83-7037
1 1/2" (38.1mm)	1/2" (12.7mm)	1/4" (6.35mm)	84-7022			83-7038
2" (50.8mm)	1/2" (12.7mm)	1/4" (6.35mm)	84-7023			83-7039

NYLON CLAMPS

- Made of general purpose (PA66) Polyamide 6.6 nylon material
- Ideal for securing wire, cable and hydraulic hoses
- Continuous operating temperature -40°C (-40°F) to 85°C (185°F)

I.D. SIZE	WIDTH	MOUNTING HOLE	PACK OF 10	PACK OF 100
1/4" (6.4mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7003	83-7003
5/16" (8.0mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7014	83-7014
3/8" (9.5mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7011	83-7011
1/2" (12.7mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7004	83-7004
5/8" (15.9mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7012	83-7012
3/4" (19.1mm)	1/2" (12.7mm)	.203" (5.2mm)	84-7005	83-7005

CHASSIS CLIPS

- Made of heat treated spring steel with black corrosion resistant finish
- Clamps snap in place and securely hold wires, cables and hoses

I.D. SIZE	DIMENSIONS	PACK SIZE	PART #
3/16"	1/2" wide x 1 1/4" long x 3/16" deep	15	84-7033
1/4"	1/2" wide x 1 1/2" long x 1/4" deep	100	83-7034
1/4"	1/2" wide x 1 1/2" long x 1/4" deep	15	84-7034
3/8"	1/2" wide x 1 1/2" long x 1/2" deep	15	84-7035



NYLON BUSHINGS

- Easy snap in style nylon bushings
- Protects wire and cables from chaffing and vibration
- Lightweight and easy to install; 1/8" thickness

I.D. SIZE	MOUNTING HOLE	PACK SIZE	PART #
3/8"	1/2"	10	84-8050
5/8"	3/4"	100	83-8051
5/8"	3/4"	10	84-8051
3/4"	1"	10	84-8052



PVC GROMMETS

- Protect wires from chafing against drilled holes
- Also available in bulk sizes

INSIDE DIA. SIZE (A)	GROOVE WIDTH (B)	OVERALL WIDTH (C)	OVERALL THICKNESS (D)	GROOVE DIAMETER (E)	PACK SIZE	PART #
1/8" (3.1mm)	1/16" (1.5mm)	11/32" (8.7mm)	3/16" (4.7mm)	1/4" (6.4mm)	30	83-7020
3/16" (4.7mm)	1/16" (1.5mm)	7/16" (11.1mm)	7/32" (5.5mm)	5/16" (7.9mm)	30	83-7021
1/4" (6.4mm)	1/16" (1.5mm)	9/16" (14.2mm)	1/4" (6.4mm)	3/8" (9.5mm)	30	83-7022
5/16" (7.9mm)	1/16" (1.5mm)	5/8" (15.9mm)	1/4" (6.4mm)	7/16" (11.1mm)	30	83-7023
3/8" (9.5mm)	1/16" (1.5mm)	5/8" (15.9mm)	1/4" (6.4mm)	1/2" (12.7mm)	30	83-7024
25/64" (9.9mm)	1/8" (3.1mm)	27/32" (21.4mm)	3/8" (9.5mm)	21/32" (16.6mm)	30	83-7025
1/2" (12.7mm)	1/16" (1.5mm)	3/4" (19.2mm)	9/32" (5.2mm)	5/8" (15.9mm)	30	83-7026
5/8" (15.9mm)	1/16" (1.5mm)	1 1/8" (28.5mm)	9/32" (5.2mm)	7/8" (22.2mm)	30	83-7027
11/16" (17.4mm)	1/16" (1.5mm)	1 5/16" (33.3mm)	3/8" (9.5mm)	1" (25.4mm)	30	83-7028



PVC GROMMET ASSORTMENT

- 30 assorted grommets
- 10 each (1/4", 1/8" & 3/8")

83-7006



07

SWITCHES & ELECTRICAL ASSEMBLIES

COMMUTATEURS ET ENSEMBLES ÉLECTRIQUES

APAGADORES Y ENSAMBLES ELÉCTRICOS

- 100 Battery Disconnect Switches
- 101 Ignition & Starter Switches
- 102 Toggle Switches
- 105 Rocker Switches
- 106 Push/Pull Switches
- 107 Solenoids
- 108 Miscellaneous Switches
- 110 Pigtails & Sockets

WHETHER YOU ARE INSTALLING NEW PRODUCTS OR REPLACING/UPDATING AN EXISTING SYSTEM, FOR REPAIRS AND MAINTENANCE ON LAWN AND GARDEN EQUIPMENT AROUND THE HOUSE, MARINE AND RV EQUIPMENT OR HEAVY VEHICLE AND EQUIPMENT NEEDS, GROTE OFFERS AN EXTENSIVE LINE OF SWITCHES & ELECTRICAL ASSEMBLIES YOU NEED TO GET THE JOB DONE RIGHT!



MASTER BATTERY DISCONNECT SWITCH



- Truck, Automotive, Marine, Off-Road and R.V. applications
- For battery circuit (82-2103, 82-2233); for alternator or generator field circuit (82-2155)
- 3/4" & #10-32 copper alloy stud terminals with hex nuts, lock washers included
- Large die cast lever for ease of operation; mounting stem 1/2" long x 3/4" dia.
- Fits panel up to 1/4" thick; 10,000 life cycle; 6-36V DC
- Includes faceplate
- Faceplate replacement for 82-2103 (82-2157)

DISCONNECTS ALL CIRCUITRY TO REDUCE THE POSSIBILITY OF THEFT / ACCIDENTAL ELECTRICAL FIRES

PRODUCT RATING

Continuous Rating (Make/Break), Large Studs – 180 AMP @ 6-36V DC; 1,000 AMP – in rush (82-2103)

Continuous Rating (Make/Break), Large Studs – 180 AMP @ 6-36V DC (82-2233)

Intermittent Rating (Carrying), Large Studs – 1800 AMP @12V DC; 1 cycle = 4 seconds on/20 minutes off)

PART #	POSITION	RATED	TYPE	TERMINATION	DIMENSIONS
82-2103	Off/On	12V	S.P.S.T.	2, 3/8" stud terminals ground w/ faceplate	4 3/8" L x 2 5/8" Dia.
82-2233	Off/On	12V	S.P.S.T.	2, 1/2" stud terminals ground w/ faceplate	4 3/8" L x 2 5/8" Dia.



DESIGNED TO BREAK ALTERNATOR GENERATOR CIRCUIT PRIOR TO BATTERY CIRCUIT DISCONNECT

PRODUCT RATING

Continuous Rating (Make/Break), Large Studs: 180 AMP, Small Studs: 20 AMP @ 6-36V DC

Intermittent Rating (Carrying), Large Studs: 1,000 AMPs (20 sec. "On" – 5 Minutes "Off")

PART #	POSITION	RATED	TYPE	TERMINATION	DIMENSIONS
82-2155	Off/On	12V	D.P.S.T.	4 stud terminal ground	4 1/8" L x 2 5/8"Dia.

BATTERY ISOLATOR SWITCH



- Prevents unauthorized use
- Eliminates battery discharge
- Waterproof body with removable key and protective cap
- Rated at 500 AMPs at 12V
- Stud Size: M10 (1.5mm)

82-2104

IGNITION STARTER SWITCHES

- Momentary start
- One piece die cast housing with brass terminals; includes 2 keys
- 4 position (ACC, OFF, ON/ACC, START – spring return to "ON")
- Key removable; key in "OFF" position only
- 50,000 life cycle
- Caution tag on ground terminal (82-2235)
- 82-2235 fits Packard #2984017

SPECIFICATIONS

Rating @ 14V DC

Ignition Terminal, 8 AMP

Accessory Terminal, 30 AMP (inductive)



Start Terminal – 75 AMP make, 20 AMP break

Continuous current carrying capacity, 30 AMP @14V DC;

Accessory terminal with #10 gauge wire

PART #	CONNECTION TYPE	STARTER LOCKOUT	KEYCODE	MOUNTING HOLE PATTERN
82-2150	Screw	No	Various	2
82-2156	Screw	No	Universal	1
82-2235	Blade	No	Various	1
82-2158*	Screw	No	D250	1

* Includes specially designed glow plug warmer



IGNITION STARTER SWITCH



- Special "Push to Choke" feature eliminates need for separate electronic choke switch
- Magneto grounded in "off" position
- Glass filled delrin housing, stainless steel terminals and molded velox base
- 13/16" diameter mounting bushing special weather proofing seal and drain hole
- Switch mounts in panels up to 1/4" thick
- Stainless steel terminals; 13/16" diameter mount
- Special weather proofing seal and drain hole
- 3 position (OFF – Magneto Grounded, ON/ACC & BATT, START/ACC BATT & SOL – spring return to "ON")

Product Specifications

Replaces – Johnson-Evinrude Numbers 388173, 390129, 390133


Rating: Off/Magneto grounded – 10 AMPs inductive, On – 5 AMP,

Start – 10 AMP, Choke – 1 AMP

PART #	CONNECTION TYPE
82-2306	Screw



TOGGLE SWITCHES



- For Heavy-Duty Truck, Off-Road, Automotive, Marine, R.V.
- Durable materials protect from breakage and corrosive materials
- Quick and easy installation

S.P.S.T. = Single Pole Single Throw **D.P.S.T.** = Double Pole Single Throw
S.P.D.T. = Single Pole Double Throw **D.P.D.T.** = Double Pole Double Throw

* **82-2111** – Sealed with 8" leads.
** **82-0315** – Waterproof and dust-proof to IP68 standard – allows mounting anywhere on vehicle. Sealed with 12" leads.

EXTRA HEAVY DUTY

PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
82-2226	On/Off	50 AMP @ 12V DC	S.P.S.T.	2 screw	1" Long x 15/32" dia.
82-2227	On/Off	50 AMP @ 12V DC	S.P.S.T.	2 screw	1 1/2" Long x 15/32" dia.
82-2120	On/Off	35 AMP @ 12V DC	S.P.S.T.	2 screw	11/32" Long x 15/32" dia.
82-2121	On/Off	35 AMP @ 12V DC	S.P.S.T.	2 screw	1 1/2" Long x 15/32" dia.
82-0216	On/Off	30 AMP @ 12V DC	S.P.S.T.	2 blade	1" Long x 15/32" dia.

HEAVY DUTY

PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
82-2117	On/On	20 AMP @ 12V DC	S.P.D.T.	3 screw	11/16" Long x 15/32" dia.
82-2114	On/On	20 AMP @ 12V DC	D.P.D.T.	6 screw	11/16" Long x 15/32" dia.
82-2111*	On/Off	20 AMP @ 12V DC	S.P.S.T.	2 wire	11/16" Long x 15/32" dia.
82-2221	On/Off	20 AMP @ 12V DC	S.P.S.T.	2 screw	11/16" Long x 15/32" dia.
82-2116	On/Off	15 AMP @ 12V DC	S.P.S.T.	2 screw	3/8" Long x 15/32" dia.
82-2123	On/Off	10 AMP @ 12V DC	S.P.S.T.	2 screw	3/8" Long x 2 3/4" hole
82-2119	On/Off	15 AMP @ 12V DC	D.P.S.T.	4 screw	3/8" Long x 15/32" dia.
82-0315**	On/Off/On	25 AMP @ 12V DC	S.P.D.T.	3 wire	11/16" Long x 15/32" dia.
82-2222	On/Off/On	20 AMP @ 12V DC	S.P.D.T.	3 screw	11/16" Long x 15/32" dia.
82-2118	On/Off/On	15 AMP @ 12V DC	S.P.D.T.	3 screw	3/8" Long x 15/32" dia.
82-2224	On/Off/On	20 AMP @ 12V DC	D.P.D.T.	6 screw	11/16" Long x 15/32" dia.
82-2225	On/Off/On	20 AMP @ 12V DC	D.P.D.T.	6 blade	11/16" Long x 15/32" dia.
82-2122	On/Off/On	15 AMP @ 12V DC	D.P.D.T.	6 screw	3/8" Long x 15/32" dia.
82-2128	On/Off/On	15 AMP @ 12V DC	D.P.D.T.	6 blade	3/4" Long x 1/4" dia.
82-2124 (Toggle Plate for 82-2123)					

MOMENTARY TOGGLE SWITCHES



PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
82-2112	Mom On/Off	25 AMP @ 12V DC	S.P.S.T.	2 screw	11/16" Long x 15/32" dia.
82-2127	Mom On/Off/Mom On	50 AMP @ 12V DC	S.P.D.T.	3 screw	1" Long x 15/32" dia.
82-2125	Mom On/Off/Mom On	35 AMP @ 12V DC	S.P.D.T.	3 screw	11/32" Long x 15/32" dia.
82-2220*	Mom On/Off/Mom On	20 AMP @ 12V DC	S.P.D.T.	3 wire	11/16" Long x 15/32" dia.
82-2110	Mom On/Off/Mom On	20 AMP @ 12V DC	D.P.D.T.	6 screw	11/32" Long x 15/32" dia.

* Sealed with 8" leads

MOMENTARY STARTER SWITCH

- Miniaturized H.D. panel switch for Diesel Trucks, Tractor, Farm, Marine
- Neoprene Cap to seal out weather
- 60 AMP @ 12V DC
- 5/8" Long x 15/16" Diameter; 2 screw

82-2151 With Cap
82-2152 Without Cap



MOMENTARY PUSH SWITCH

- 10 AMP @ 12V DC
- 2 screw terminals; 1 5/16" mounting hole
- Mounting stem 7/8"-20; .45" long
- Replaces 21A11500A

82-0600



TOGGLE SWITCH BOOT

- Rubber boot with 15/32" thread
- Used with 15/32" mounting stem
- Provides protection from weather conditions

82-2106




TOGGLE SWITCH GUARD

- Spring loaded cover holds the guard cover in the up or down position
- Face plate is steel with black glossy finish
- Accepts standard 11/16" bat handles and 15/32" diameter mounting stem
- Used where accidental switch activation may cause an undesired or hazardous condition
- Switch will not operate with the cover in the down position

82-2108




ILLUMINATED TOGGLE SWITCH



PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE	COLOR
82-2115	On/Off	30 AMP @ 12V DC	S.P.S.T.	3 blade	1" x 15/32" dia.	Red/Green
82-1905	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	1" x 15/32" dia.	Red
82-1906	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	1" x 15/32" dia.	Yellow
82-1907	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	1" x 15/32" dia.	Green
82-1908	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	1" x 15/32" dia.	Blue

ILLUMINATED TOGGLE SWITCH – DUCKBILL



PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE	COLOR
82-1909	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	9/16" x 15/32" dia.	Red
82-1910	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	9/16" x 15/32" dia.	Yellow
82-1911	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	9/16" x 15/32" dia.	Green
82-1912	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade	9/16" x 15/32" dia.	Blue

ILLUMINATED LED ROCKER SWITCHES



PART #	POSITION	RATED	TYPE	TERMINAL	DIMENSIONS	COLOR
82-0302	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 screw	Fits .830" x 1.45" Hole	Red
82-0303	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 screw	Fits .830" x 1.45" Hole	Yellow
82-0304	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 screw	Fits .830" x 1.45" Hole	Green
82-1901	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits .500" x 1.00" Hole	Red
82-1902	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits .500" x 1.00" Hole	Yellow
82-1903	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits .500" x 1.00" Hole	Green
82-1904	On/Off	20 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits .500" x 1.00" Hole	Blue

LED ROCKER SWITCHES

- Provides protection from dust and moisture
- Available in LED or standard bulb options
- Screw and .250" quick disconnect contact options
- Single and modular mounting brackets also available



SEALED LED

PART #	POSITION	RATED	TYPE	TERMINAL	DIMENSIONS	COLOR
82-0309	On/Off	20 AMP @ 12V DC	S.P.S.T.	4 blade (.250")	Fits .830" x 1.45" Hole	Amber
82-0310	Mom On/Off	20 AMP @ 12V DC	S.P.S.T.	4 blade (.250")	Fits .830" x 1.45" Hole	Amber



PANELS

PART #		DIMENSIONS	FITS ROCKER SWITCH
82-1914	Single Unit	Fits .980" x 1.88" Hole	82-0309, 82-0310
82-1915	End Unit	Fits .980" x 1.88" Hole	82-0309, 82-0310
82-1916	Middle Unit	Fits .980" x 1.88" Hole	82-0309, 82-0310
82-1913	Single Unit	Fits .500" x 1.00" Hole	82-1901, 82-1902, 82-1903, 82-1904

NOTE: Switches not included



SQUARE LED


PART #	POSITION	RATED	TYPE	TERMINAL	DIMENSIONS	COLOR
82-2130	On/Off	25 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 15/16" Hole	Red
82-2131	On/Off	25 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 15/16" Hole	Yellow
82-2132	On/Off	25 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 15/16" Hole	Green
82-2136	On/Off	25 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 15/16" Hole	Blue



OVAL LED

PART #	POSITION	RATED	TYPE	TERMINAL	DIMENSIONS	COLOR
82-2133	On/Off	30 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 1/2" Hole	Red
82-2134	On/Off	30 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 1/2" Hole	Yellow
82-2135	On/Off	30 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 1/2" Hole	Green
82-2137	On/Off	30 AMP @ 12V DC	S.P.S.T.	3 blade (.250")	Fits 1/2" Hole	Blue

PUSH/PULL SWITCHES



- For Heavy Duty Truck, Off-Road, Automotive, Marine and Recreational Vehicles
- Durable materials protect from breakage and corrosive materials
- Quick and easy installation

S.P.S.T. = Single Pole Single Throw
S.P.D.T. = Single Pole Double Throw

D.P.S.T. = Double Pole Single Throw
D.P.D.T. = Double Pole Double Throw

EXTRA HEAVY DUTY

PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
82-2100	On/Off	75 AMP @ 6-28V DC	S.P.S.T.	2 Screw	5/8" Long x 15/32" diameter

HEAVY DUTY

PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
44170	On/Off	10 AMP @ 12V DC	S.P.S.T.	2 Blade	
82-2102	On/Off	15 AMP @ 12V DC	S.P.S.T.	2 Screw	5/8" Long x 7/16" diameter
82-2107	Off/On/On	15 AMP @ 12V DC	S.P.S.T.	5 Screw	5/8" Long x 7/16" diameter
82-2105*	Off/On/On	15 AMP @ 12V DC	S.P.S.T.	5 Screw	5/8" Long x 7/16" diameter

(* Includes 15 AMP glass fuse)

MARINE

PART #	POSITION	RATED	TYPE	TERMINAL	HANDLE
82-0402	On/Off	15 AMP @ 12V DC	S.P.S.T.	2 Screw	1 1/4" Long x 7/16" diameter



AXLE SWITCH



- High-low axle ranges
- Die-cast with rubber protection
- 3 female terminals to receive male bullets
- Large red knob to use with Eaton 2 speed rear axle

82-2236

STARTER SOLENOID SWITCH

- Automotive, truck, tractor, construction, off-road and R.V. applications
- Continuous duty, 150 AMP in rush; 6-24V DC
- Ignition and ground terminals, #10-32 thread
- Contact terminals 5/16"-24 thread
- Bracket mounting holes, 5/16" x 19/32"; 2 1/8" on center
- 82-0307 (UL Listed)

PRODUCT SPECIFICATIONS

82-0307 replaces Prestolite 15-132, 15-133, 15-236, 15-311, SAS-4201, 4202, 4213, 5203; Delco 1114218

82-0311 replaces Prestolite 15-141, 15-196, 15-310, SAS-4401, 4408, 5401

82-0308 replaces Prestolite 15-139, SAS-4208

82-0312 replaces Prestolite SAZ-4201N

82-0313 replaces Prestolite SAZ-4201E



CONTINUOUS DUTY

PRODUCT RATING

82-0307 Continuous duty 100 AMP, 150A in rush @ 12V DC

82-0311 Continuous duty 100 AMP, 150A in rush @ 24V DC

82-0308 Continuous duty 100 AMP, 150A in rush @ 12V DC

PART #	TYPE	TERMINATION	RATED
82-0307	S.P.S.T. Normally Open, Off-On	4 terminal ground	12V DC
82-0311	S.P.S.T. Normally Open, Off-On	4 terminal ground	24V DC
82-0308	S.P.S.T. Normally Open, Off-On	3 terminal ground	12V DC



INTERMITTENT DUTY

PRODUCT RATING

82-0312 Intermittent duty 750 AMP make, 100A break @ 12V DC

82-0313 Intermittent duty 600 AMP make, 200A break @ 12V DC

PART #	TYPE	TERMINATION	RATED
82-0312	S.P.S.T. Normally Open, Off-On	4 terminal base ground	12V DC
82-0313	S.P.S.T. Normally Closed, Off-On	3 terminal base ground	12V DC



BRAKE & BACK-UP PRECISION BALL SWITCH



- Leak proof
- 0-5 AMP operating current, 5-24V DC
- 500,000 electrical life cycles
- 7/8" hex nut; 9/16"-18 thread
- Temperature Rating: -40°C (-40°F) to 121°C (250°F)

PART #	STYLE	TYPE	TERMINATION	RATED
82-0456	Ball switch	Normally Open	2 screw terminal	12V DC
82-2234	Ball switch	Normally Open	2 stud terminal	12V DC
82-0465	Ball switch	Normally Open	Metri-Pack (12052644)	12V DC
82-0458	Ball switch	Normally Closed	2, .250" blade terminals	12V DC

STOP LIGHT SWITCH



- 1/4" – 18NPTF threads
- Meets DOT 121 requirements
- Brass body resists corrosion
- Installs with a deep socket
- North American

82-2159

HORN BUTTONS



- Black plastic button
- Chrome plated housing
- 2 Position On-Off
- 2 1/8" on center mounting holes

82-2231 Includes Mounting Bracket
82-2232 Surface Mount

DOOR SWITCH – UNIVERSAL



- 5 AMP @ 12V DC
- 2 screw terminals
- “ON” when plunger is out
- Dual mounting holes 1 3/8" x 2 1/16"
- Replaces Chrysler 882943, KF-204229

82-2230

UNIVERSAL BUZZER



- 842 Buzzer use as low air pressure or Bus rear door warning buzzer
- 76 db, 12V DC; 2 screw terminals
- Ford: FDM2938A
GMC Truck & Coach: 76023
Divco Wayne: E-11811A

82-2238

PILOT LIGHT



- 12V DC; 15 AMP
- Red 1/2" diameter faceted lens
- For panel mounting through 5/16" hole
- North American

82-0115

FLOOR DIMMER SWITCHES



- 3 terminals for plug connection

PART #	STYLE	TYPE	FEATURES	MOUNTING
82-2203	Floor mount	S.P.D.T.	2 Position On – Low Beam, On High beam	1 5/8" on center, 7/32" diameter
82-2204	Floor mount	S.P.D.T.	2 Position On – Low Beam, On High beam	1 6/8" on center, 9/32" diameter

PIGTAILS & SOCKETS

1 WIRE



SOCKET REPAIR ASSEMBLY

- For 5/8" socket
 - Fits 63, 67, 81, 87, 93, 97, 209, 1003, 1073, 1129, 1133, 1141, 1156 bulbs
 - 18 GA, 12" wire
- 84-1070



SOCKET REPAIR ASSEMBLY

- For base sockets; universal
 - Fits 63, 67, 81, 89, 93, 209, 1003, 1073, 1129, 1133, 1141, 1156 bulbs
 - 18 GA, 12" wire
- 84-1075



LICENSE & UTILITY SOCKET ASSEMBLY

- Fits 63, 67, 81, 89, 93, 97, 1003, 1141, 1156 bulbs
 - 18 GA, 12" wire
- 84-1003



INSTRUMENT PANEL & LICENSE ASSEMBLY

- Fits 51, 53, 55, 57, 57X bulbs
 - 18 GA, 12" wire, 5/8" hole; snap-in mount
- 84-1060



INSTRUMENT PANEL & LICENSE ASSEMBLY

- GM: 2978302
 - Ford: D00Z-15536A
 - Chrysler: 3513162, 3780745
 - AMC: 4486949, 4489412
 - Fits 63, 67, 81, 87, 89, 93, 209, 1003, 1073, 1129, 1133, 1141, 1156 bulbs
 - 18 GA, 12" wire; 1 1/8" hole; universal
- 84-1062



MOLDED SENSOR RECEPTACLE

- Oil pressure switch; thermostat/brake sensors
 - PT404, 12112171
 - Mates with .157" to .159" male terminals or stud; #8 + M4 terminals
 - 18 GA, 12" wire, 90 degree
- 84-1069

PIGTAILS & SOCKETS

2 WIRE



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn, license & side marker lamps
 - Fits 194 bulbs; Includes 194 bulb
 - 18 GA, 9.5" wire, twist-in mount
- 68380



SOCKET REPAIR ASSEMBLY

- License & side marker lamps; Twist-in mount
 - Ford: E1FZ-13410A; D5VY-15442A
 - GM: 4489395, 6294015, 6298886, 6298892, 6298935, 8901283, 8910257, 8918527, 418977C91
 - Fits 67, 131, 158, 161, 168, 194, 194A bulbs
 - 18 GA, 10" wire
- 84-1008



SOCKET REPAIR ASSEMBLY

- Front & rear side marker lamps
 - GM: 12037105, 12083460
 - Fits 194 bulbs
 - 18 GA, 12" wire
- 84-1032



SOCKET REPAIR ASSEMBLY

- Front & rear side marker lamps
 - Chrysler: 3588314, 4400147, 4400588, 4400899, 4450821
 - Ford: E25Y-13410B
 - Fits 67, 158, 168, 194, 194NA bulbs
 - 18 GA, 12" wire
- 84-1031



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn, park & license lamps
 - GM: 12001470, 12078187, 12116169
 - Ford: E0SZ-15A442B
 - Fits 161, 168, 194, 194NA bulbs
 - 18 GA, 12" wire, 90° mounting
- 84-1054



INSTRUMENT PANEL SOCKET ASSEMBLY

- For 5/8" mounting hole; vinyl housing
 - GM, Ford, Chrysler vehicles
 - Fits 168, 194, 194NA bulbs
- 84-1052

2 WIRE (CONTINUED)

PIGTAILS & SOCKETS



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn & park lamps
 - Fits 198, 1016, 1034, 1154, 1157 bulbs
 - 18 GA, 12" wire
- 84-1004



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn & park lamps
 - Fits 198, 1016, 1034, 1154, 1157 bulbs
 - 18 GA, 12" wire
- 84-1000



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn & park lamps
 - LS224, 5947900, 8861101
 - GM: 2974309
 - Chrysler: 2926370
 - Fits 198, 1016, 1034, 1154, 1157 bulbs
 - 18 GA, 12" wire; 1 1/8" hole
- 84-1051



DOME AND MAP LIGHT SOCKET ASSEMBLY

- Dome and map lights; universal
 - Fits 64, 68, 82, 88, 90, 94, 210, 1004, 1076, 1130, 1142, 1158, 1176, 1178 bulbs
 - 18 GA, 12" wire
- 84-1068



SOCKET REPAIR ASSEMBLY

- Back-up & rear lamps
 - Ford: D3AZ-13410A, D80Z-15A434A
 - Ford 1973 & up
 - Fits 1156 bulbs
 - 18 GA, 6" wire
- 84-1048



HEADLAMP CONNECTOR HARNESS:
HIGH BEAM

- Weather-pack seal connector
 - For halogen bulb headlamp assembly with 2 terminals
 - GM: 12101898, PT168
 - Fits 9005 bulbs
 - 18 GA, 12" wire
- 84-1037



SEALED HORN REPLACEMENT
HARNESS ASSEMBLY

- GM: 1999160, 1999161, 10456327, 10456328
 - Delco: PT419, PT1357, 12116958, 15306302
 - 18 GA, 12" wire
- 84-1073



HEADLAMP CONNECTOR HARNESS:
LOW BEAM

- Weather-pack seal connector
 - For halogen bulb headlamp assembly with 2 terminals
 - GM: 12101897, PT167
 - Fits 9006 bulbs
 - 16 GA, 6" wire
- 84-1038



SOCKET REPAIR ASSEMBLY

- Fits H8 & H11 bulbs
 - 18 GA, 12" wire
- 84-1081



SOCKET REPAIR ASSEMBLY

- Fits H7 bulbs
 - 14 GA, 6" wire
- 84-1082



SOCKET REPAIR ASSEMBLY

- Fits H880 bulbs
 - 18 GA, 12" wire
- 84-1083



SEAL BEAM & FLASHER ASSEMBLY

- For 2 terminal sealed beam headlights or 2 terminal flashers
 - LS145, PT270, 1210879, 88860447
 - 18 GA, 12" wire; ABS molded housing
- 84-1007



SENSOR REPAIR HARNESS ASSEMBLY

- GM: 12046623, 12101899
 - Delco: PT169
 - 18 GA, 12" wire
- 84-1071



FOGLAMP AND SPEED SENSOR
HARNESS ASSEMBLY

- Fits 880, 881, 884, 885, 886, 889, 890, 892, 893, 894, 896, 899 bulbs
 - PT120, 12043215, 12085498
 - 18 GA, 12" wire
- 84-1072



ALTERNATOR TERMINAL REPAIR ASSEMBLY

- Weather-pack seal connector
 - Includes internal voltage regulator
 - GM: 6294493, PT181, 624493, 12101909
 - 12 GA 12" red & 16 GA 12" white wire
- 84-1034

PIGTAILS & SOCKETS

3 WIRE



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn, park & license lamps
- GM: 12003759, 12089348
- Chrysler: 8218931, 4450816, 4331051
- Fits 1016, 1034, 1154, 1157 bulbs
- 18 GA, 8" wire, 90 degree; low profile

84-1056



SOCKET REPAIR ASSEMBLY

- Front turn & signal lamps
- Ford: D4ZZ-13234A
- Fits 1157 bulbs
- 18 GA, 8" wire

84-1057



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn & signal lamps
- For 3/4" hole with adapter plate & boot
- Fits 198, 1016, 1034, 1154, 1157 bulbs
- 18 GA, 8" wire

84-1064



SOCKET REPAIR ASSEMBLY

- Park, stop, tail & turn lamps
- GM: 8919916, 12013813
- Fits 1034, 1154, 1157 bulbs
- 18 GA, 12" wire

84-1030



SOCKET REPAIR ASSEMBLY

- Fits 3057/3157 bulbs
- GM: 12083689
- 18 GA, 12" wire

84-1084



SOCKET REPAIR ASSEMBLY

- Fits H13 & 9008 bulbs
- 18 GA, 12" wire

84-1085



SOCKET REPAIR ASSEMBLY

- Stop, tail, turn & park lamps
- 1 1/8" mount ; includes ground terminal
- Ford: D0AZ-13410-B, D1AZ-A, D2AZ-B, D3AZ-A
- Fits 1034, 1154, 1157 bulbs
- 18 GA, 6" wire

84-1067



SOCKET REPAIR ASSEMBLY

- Stop, turn & park lamps
- GM: 12083006, 12092377
- GM 1988 & up
- Delco LS-12
- Fits 3057, 3157 bulbs
- 18 GA, 12" wire

84-1049



SOCKET REPAIR ASSEMBLY

- Fits 3057, 3157, 415 bulbs
- 18 GA, 12" wire

84-1086



HEADLAMP CONNECTOR HARNESS: HIGH/LOW BEAM

- Weather-pack seal connector
- For halogen bulb headlamp assembly with 3 terminals
- High-low beam
- Chrysler: 4400395, 4414332, 4430976, 4439076
- Fits 9004, 9007 bulbs
- PT433, 12117260
- 18 GA, 12" wire

84-1039



SEAL BEAM & FLASHER ASSEMBLY

- ABS molded housing; universal
- For 2-3 terminal sealed beam headlights or 2-3 terminal flashers
- 16 GA, 12" wire

84-1006



SEALED BEAM HARNESS ASSEMBLY

- For 3 terminal sealed beam lamps with fiber optics
- Domestic and import vehicles
- LS144, 88860504
- 18 GA, 12" wire

84-1042



DIMMER SWITCH ASSEMBLY

- For floor mounted dimmer switch; locking ears
- GM: D-803, D-809
- 88865409
- 18 GA, 12" wire

84-1036



DIMMER SWITCH ASSEMBLY

- For dimmer switches
- AMC: 3160926
- Mopar: 1881938, 2497158
- Motorcraft: SW-263
- 18 GA, 12" wire

84-1035

4 WIRE

PIGTAILS & SOCKETS



METRIC-PACK SEALED REPAIR ASSEMBLY

- Sealed pigtail replacement
- OEM Metri-Pack 280 style connectors
- Fits either 4 or 5 wire applications
- Can plug into any 5370, 5371, 5372 and 5376 series lamps
- Additional parts available on page 59

68680

5 WIRE

PIGTAILS & SOCKETS



FLASHER & RELAY SOCKET ASSEMBLY

- Connects 4 or 5 terminal relays or flashers
- Molded housing; universal
- 12 volt
- 14 GA, 12" wire

84-1041



5 PIN RELAY & PIGTAIL ASSEMBLY

- Includes 5 terminal relay & pigtail assembly
- S.P.D.T. – Single Pole Double Throw, Form C
- Normally open or normally closed options
- Spike protection
- Includes mounting bracket
- Temperature range -40°C to 100°C (-40°F to 212°F)
- 12V DC, 30A/40A
- 14 GA, 12" wire

84-1040



FLASHER & RELAY SOCKET ASSEMBLY

- Connects 4 or 5 terminal relays or flashers
- Weather resistant, molded housing;
- 12 volt; fits 84-1079 relay
- 12 GA, 12" wire

84-1078

POWER PLUGS & SOCKETS



CIGARETTE LIGHTER POWER PLUG

- Provides a power source through a cigarette lighter plug-in port
- 2, 18 GA wires

84-1090



POWER SOCKET

- 12V power socket with pre-wired fuse holder & cap
- 2, 18 GA wires with .250" quick disconnects

84-1091



POWER SOCKET, PANEL MOUNT

- 12V panel mount power socket
- Includes socket, mounting bracket and locking ring
- 2, .250" quick disconnect terminals

84-1092

08

FUSE & CIRCUIT PROTECTION

FUSIBLE ET PROTECTION DE CIRCUIT

PROTECCIÓN DE FUSIBLE Y CIRCUITO

- 116 High Amperage Circuit Breakers
- 116 Standard & Miniature Blade Circuit Breakers
- 117 Universal Circuit Breakers
- 118 Miniature Blade Fuses & Holders
- 120 Standard Blade Fuses & Holders
- 122 Micro Blade Fuses & Holders
- 123 Large Blade Fuses & Holders
- 124 Automotive Link Fuses
- 126 Glass Fuses & Holders
- 127 Assortment Kits
- 128 Bolt-On Fuses
- 130 Fuse Panels & Terminal Strips
- 131 Relays

TO PROTECT YOUR EQUIPMENT'S SENSITIVE AND CRITICAL COMPONENTS FROM POWER SURGES AND OTHER POWER PROBLEMS, GROTE'S FUSE & CIRCUIT PROTECTION PRODUCTS OFFER YOU THE SELECTION, THE TYPE AND THE QUALITY YOU NEED TO MAKE SURE THAT YOUR INVESTMENT IS PROTECTED AND YOUR EQUIPMENT IS PERFORMING OPTIMALLY, EVERY TIME.

GROTE'S WIDE ARRAY OF FUSE & CIRCUIT PROTECTION PRODUCTS AND TOOLS, ENSURES THE JOB GETS DONE RIGHT THE FIRST TIME!

HIGH AMPERAGE THERMAL CIRCUIT BREAKERS

SAE
INTERNATIONAL
SAE J1625™
STANDARD

SAE
INTERNATIONAL
SAE J1171™
STANDARD




- For use in auxiliary and accessory circuits – trucks, buses, RV and marine applications
- Also used as battery chargers and DC audio systems
- Thermoplastic; UL Rated 94V-0 housing
- Surface Mount, Type III; Single Pole; Manual Reset; Ignition protected
- Complies with SAE J1625 and J1171 standards
- Operating Temperature -40°C (-40°F) to 85°C (185°F)
- Stud insulators provided; 1/4"-28 thread studs

PART #	CURRENT RATING	DESCRIPTION
82-2251	40A	Type III, Manual Reset, Surface Mount
82-2247	50A	Type III, Manual Reset, Surface Mount
82-2216	60A	Type III, Manual Reset, Surface Mount
82-2248	70A	Type III, Manual Reset, Surface Mount
82-2177	80A	Type III, Manual Reset, Surface Mount
82-2178	100A	Type III, Manual Reset, Surface Mount
82-2249	120A	Type III, Manual Reset, Surface Mount
82-2250	135A	Type III, Manual Reset, Surface Mount
82-2176	150A	Type III, Manual Reset, Surface Mount
82-2217	200A	Type III, Manual Reset, Surface Mount

UNIVERSAL CIRCUIT BREAKER

SAE
INTERNATIONAL
SAE J553™
STANDARD



PLUG-IN STYLE

- 12V DC; Type 1, Auto-Reset
- SAE J553C
- Replacement for Standard Blade type fuses
- Dimensions: .840" x .4000" (10.2mm) x 1.500" (38.1mm)
- See Standard Blade fuse holders / fuse panels on page 117 & 126


PART #	CURRENT RATING	DESCRIPTION
82-2195	10A	Type I, Auto-Reset
82-2196	15A	Type I, Auto-Reset
82-2197	20A	Type I, Auto-Reset
82-2199	25A	Type I, Auto-Reset
82-2198	30A	Type I, Auto-Reset
82-2200	35A	Type I, Auto-Reset
82-2201	40A	Type I, Auto-Reset

STANDARD BLADE CIRCUIT BREAKER

SAE
INTERNATIONAL
SAE J553™
STANDARD




- 12V DC; Type III, Manual-Reset
- Voltage: Up to 28VDC
- Interrupt Rating: 2,000A @ 28VDC
- Materials: Thermoplastic (UL Rated 94-V-0)
- Conforms to American National Standard SAE J553 Type III
- Operating Temperature: -40°C to 85°C



PART #	CURRENT RATING	COLOR	DESCRIPTION
82-2355	10A	Red	Type III, Manual Reset
82-2356	15A	Blue	Type III, Manual Reset
82-2357	20A	Yellow	Type III, Manual Reset
82-2358	25A	White	Type III, Manual Reset
82-2359	30A	Green	Type III, Manual Reset

- Voltage: 14VDC
- Materials: Thermoplastic – (UL Rated 94-V-0)
- Testing Standard: SAE J553
- Operating Temperature: -40°C to 85°C



TYPE I


PART #	CURRENT RATING	COLOR	DESCRIPTION
82-2340	10A	Red	Type I, Auto-Reset
82-2341	15A	Blue	Type I, Auto-Reset
82-2342	20A	Yellow	Type I, Auto-Reset
82-2343	25A	White	Type I, Auto-Reset
82-2344	30A	Green	Type I, Auto-Reset

TYPE II

PART #	CURRENT RATING	COLOR	DESCRIPTION
82-2350	10A	Red	Type II, Modified-Reset
82-2351	15A	Blue	Type II, Modified-Reset
82-2352	20A	Yellow	Type II, Modified-Reset
82-2353	25A	White	Type II, Modified-Reset
82-2354	30A	Green	Type II, Modified-Reset

MINIATURE BLADE CIRCUIT BREAKERS

SAE
INTERNATIONAL
SAE J553™
STANDARD



- 12V DC; Type 1, Auto-Reset
- 2, #10-32 stud terminals (hex nuts and washers included)
- SAE J553C

WITHOUT BRACKET

PART #	CURRENT RATING
82-2179	10A
82-2180	15A
82-2181	20A
82-2182	25A
82-2183	30A
82-2184	35A
82-2210	40A
82-2185	50A

*molded bracket

WITH HORIZONTAL BRACKET

PART #	CURRENT RATING
82-2189	10A
82-2190	15A
82-2191	20A
82-2192	25A
82-2193	30A
82-2187	35A
82-2194	40A
82-2188	50A
82-2186	40A*

UNIVERSAL CIRCUIT BREAKER

SAE
INTERNATIONAL
SAE J553™
STANDARD



SNAP-IN STYLE

- 12V DC; Type II, Modified-Reset
- Opens automatically on overload
- Replaces round glass-style fuses
- Fits 1 1/4" Long x 1/4" fuse clips

PART #	CURRENT RATING	DESCRIPTION
82-2170	10A	Type II, Modified-Reset
82-2171	15A	Type II, Modified-Reset
82-2172	20A	Type II, Modified-Reset
82-2173	30A	Type II, Modified-Reset
82-2174	40A	Type II, Modified-Reset

UNIVERSAL CIRCUIT BREAKER



MINIATURE BLADE FUSES

Fast Acting/Blade Mounting

A cost-effective standard automotive fuse for use in automotive, battery and general DC applications.

2A-30A, 32VDC



82-ANM-5A

SPECIFICATIONS


Voltage: 32VDC

Amperage: 2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A, 35A

Interrupt Rating: 1000A @ 32 VDC

Terminals: Zinc Alloy

Body Material: Nylon PA 66



Inches [mm]


APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANM-2A	2A	Gray	5	Miniature Blade Fuse
82-ANM-3A	3A	Violet	5	Miniature Blade Fuse
82-ANM-4A	4A	Pink	5	Miniature Blade Fuse
82-ANM-5A	5A	Tan	5	Miniature Blade Fuse
82-ANM-7.5A	7.5A	Brown	5	Miniature Blade Fuse
82-ANM-10A	10A	Red	5	Miniature Blade Fuse
82-ANM-15A	15A	Blue	5	Miniature Blade Fuse
82-ANM-20A	20A	Yellow	5	Miniature Blade Fuse
82-ANM-25A	25A	Clear	5	Miniature Blade Fuse
82-ANM-30A	30A	Green	5	Miniature Blade Fuse
82-ANM-35A	35A	Blue-Green	5	Miniature Blade Fuse
82-ANM-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		7	Miniature Blade Fuse Assortment
82-ANM-8P	(2A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		9	Miniature Blade Fuse Assortment & Puller
82-ANM-8T	(2A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		9	Miniature Blade Fuse Assortment & Tester
82-ASST-43	(5A, 10A, 15A, 20A, 25A, 30A)		43	Miniature Blade Fuse Assortment & Tester
82-ASST-64	(2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A) + (30A, 40A, 50A)		64	Miniature & Large Blade Fuse Assortment & Tester
82-ASST-80M	(3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		80	Miniature Blade Fuse Assortment
82-ASST-180			180	Low Profile Miniature, Miniature, Standard Blade Fuses
FUSE HOLDER				
82-2241	30A (12GA)	Red	1	Miniature Blade Fuse Holder, 12" with Protective Cap
82-2208	20A (14GA)	Red	1	Miniature Blade Fuse Holder, 7" with Protective Cap
82-2213	Max 10A Primary Circuit, 10A Auxiliary Circuit (Total not to exceed 20A combined)	Red	1	"Add A Fuse" Miniature Blade Fuse Holder; 16GA

WITH LED INDICATOR

MINIATURE BLADE FUSES



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANM-I-3A	3A	Violet	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-5A	5A	Tan	2	Miniature Blade Fuse with LED Indicator
82-ANMI-7.5A	7.5A	Brown	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-10A	10A	Red	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-15A	15A	Blue	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-20A	20A	Yellow	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-25A	25A	Clear	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-30A	30A	Green	2	Miniature Blade Fuse with LED Indicator
82-ANM-I-5	(10A, 15A, 20A, 25A, 30A)		5	Miniature Blade Fuse with LED Indicator Assortment

LOW PROFILE

MINIATURE BLADE FUSES

SPECIFICATIONS


Voltage: 32VDC

Amperage: 3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A

Interrupt Rating: 1000A @ 32 VDC

Terminals: Zinc Alloy

Body Material: Nylon PA 66



Inches [mm]

APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANS-3A	3A	Violet	5	Low Profile Miniature Blade Fuse
82-ANS-5A	5A	Tan	5	Low Profile Miniature Blade Fuse
82-ANS-7.5A	7.5A	Brown	5	Low Profile Miniature Blade Fuse
82-ANS-10A	10A	Red	5	Low Profile Miniature Blade Fuse
82-ANS-15A	15A	Blue	5	Low Profile Miniature Blade Fuse
82-ANS-20A	20A	Yellow	5	Low Profile Miniature Blade Fuse
82-ANS-25A	25A	Clear	5	Low Profile Miniature Blade Fuse
82-ANS-30A	30A	Green	5	Low Profile Miniature Blade Fuse
82-ANS-I-5 (LED)	(10A, 15A, 20A, 25A, 30A)		5	Low Profile Miniature Blade Fuse LED Assortment
82-ANS-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		7	Low Profile Miniature Blade Fuse Assortment
82-ANS-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		8	Low Profile Miniature Blade Fuse Assortment & Puller
82-ANS-7T	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		8	Low Profile Miniature Blade Fuse Assortment & Tester
82-ASST-180			180	Low Profile Miniature, Miniature, Standard Blade Fuses
FUSE HOLDER				
82-2218	Max 10A Primary Circuit, 10A Aux Circuit (Total not to exceed 15A combined)	Red	1	"Add A Fuse" Low Profile Miniature Blade: 16GA

STANDARD BLADE FUSES

Fast Acting/Blade Mounting

A cost-effective standard automotive fuse for use in automotive, battery and general DC applications.

2A-40A, 32VDC



82-ANR-15A

SPECIFICATIONS

Voltage: 32VDC


Amperage: 1A, 2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A, 35A, 40A

Interrupt Rating: 1000A @ 32 VDC

Terminals: Zinc Alloy

Body Material: Nylon PA 66

Inches [mm]



APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANR-1A	1A	Black	5	Standard Blade Fuse
82-ANR-2A	2A	Gray	5	Standard Blade Fuse
82-ANR-3A	3A	Violet	5	Standard Blade Fuse
82-ANR-4A	4A	Pink	5	Standard Blade Fuse
82-ANR-5A	5A	Tan	5	Standard Blade Fuse
82-ANR-7.5A	7.5A	Brown	5	Standard Blade Fuse
82-ANR-10A	10A	Red	5	Standard Blade Fuse
82-ANR-15A	15A	Blue	5	Standard Blade Fuse
82-ANR-20A	20A	Yellow	5	Standard Blade Fuse
82-ANR-25A	25A	Clear	5	Standard Blade Fuse
82-ANR-30A	30A	Green	5	Standard Blade Fuse
82-ANR-35A	35A	Blue-Green	5	Standard Blade Fuse
82-ANR-40A	40A	Orange	5	Standard Blade Fuse
82-ANR-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		7	Standard Blade Fuse Assortment
82-ANR-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		8	Standard Blade Fuse Assortment & Puller
82-ANR-6T	(5A, 10A, 15A, 20A, 25A, 30A)		7	Standard Blade Fuse Assortment & Tester
82-ASST-44	(5A, 10A, 15A, 20A, 25A, 30A)		43	Standard Blade Fuse Assortment & Tester
82-ASST-53	(10A, 15A, 20A, 30A) + (30A, 40A, 50A)		45	Standard Blade & Large Blade Fuse Assortment & Tester
82-ASST-80R	(3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		80	Standard Blade Fuse Assortment
82-ASST-180			180	Low Profile Miniature, Miniature and Standard Blade Fuses


WITH LED INDICATOR

STANDARD BLADE FUSES



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANR-I-3A	3A	Violet	2	Standard Blade Fuse with LED Indicator
82-ANR-I-5A	5A	Tan	2	Standard Blade Fuse with LED Indicator
82-ANR-I-7.5A	7.5A	Brown	2	Standard Blade Fuse with LED Indicator
82-ANR-I-10A	10A	Red	2	Standard Blade Fuse with LED Indicator
82-ANR-I-15A	15A	Blue	2	Standard Blade Fuse with LED Indicator
82-ANR-I-20A	20A	Yellow	2	Standard Blade Fuse with LED Indicator
82-ANR-I-25A	25A	Clear	2	Standard Blade Fuse with LED Indicator
82-ANR-I-30A	30A	Green	2	Standard Blade Fuse with LED Indicator
82-ANR-I-40A	40A	Orange	2	Standard Blade Fuse with LED Indicator
82-ANR-I-5	(10A, 15A, 20A, 25A, 30A)		5	Standard Blade Fuse with LED Indicator Assortment

STANDARD BLADE FUSE HOLDERS



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-2209	20A (14GA), 7"	Red	1	Standard Blade with Cap and 20A Fuse
82-2164	20A (14GA), 7"	Black	1	Standard Blade
82-2207	20A (16GA), 7"	Red	1	Standard Blade with Cap
82-2165	30A (12GA), 8"	Orange	1	Standard Blade
82-2246	40A (10GA), 12"	Red	1	Standard Blade with Cap
82-2166	30A (12GA), 10"	Orange	1	Standard Blade with Cap and Mounting Tab
84-2903	20A (18-14GA)	Blue	1	Self Stripping Standard Fuse Holder
82-2212	Max 10A Primary Circuit, 10A Aux Circuit (Total not to exceed 20A combined)	Red	1	Add A Fuse Holder with 16GA wire

MICRO BLADE – 2 BLADE FUSES


Fast Acting/Blade Mounting

- New standard for vehicle circuit protection
- Sub-miniature design
- Space saving – smaller than the Miniature fuse

5A-30A, 32VDC



82-2219



SPECIFICATIONS


Voltage: 32VDC

Amperage: 5A, 7.5A, 10A, 15A, 20A, 25A, 30A

Interrupt Rating: 1000A @ 32 VDC

Terminals: Zinc Alloy

Body Material: Nylon PA 66



APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS

PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANT-5A	5A	Tan	5	Micro Blade – 2 Blade Fuse
82-ANT-7.5A	7.5A	Brown	5	Micro Blade – 2 Blade Fuse
82-ANT-10A	10A	Red	5	Micro Blade – 2 Blade Fuse
82-ANT-15A	15A	Blue	5	Micro Blade – 2 Blade Fuse
82-ANT-20A	20A	Yellow	5	Micro Blade – 2 Blade Fuse
82-ANT-25A	25A	Clear	5	Micro Blade – 2 Blade Fuse
82-ANT-30A	30A	Green	5	Micro Blade – 2 Blade Fuse
82-ANT-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		7	Micro Blade – 2 Blade Fuse Assortment
82-ANT-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		8	Micro Blade – 2 Blade Fuse Assortment & Puller
FUSE HOLDER				
82-2219	Max 10A Primary Circuit, 10A Aux Circuit (Total not to exceed 15A combined)	Red	1	“Add A Fuse” Micro Blade – 2 Blade: 16GA

MICRO BLADE – 2 BLADE FUSES

WITH LED INDICATOR




PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANT-I-5A	5A	Tan	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANTI-7.5A	7.5A	Brown	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANT-I-10A	10A	Red	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANT-I-15A	15A	Blue	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANT-I-20A	20A	Yellow	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANT-I-25A	25A	Clear	2	Micro Blade – 2 Blade Fuse with LED Indicator
82-ANT-I-30A	30A	Green	2	Micro Blade – 2 Blade Fuse with LED Indicator

MICRO BLADE – 3 BLADE FUSES

Fast Acting/Blade Mounting

- Provides 2 fuse elements with a common center terminal

5A-15A, 32VDC



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANK-5A	5A	Tan	5	Micro Blade – 3 Blade Fuse
82-ANK-7.5A	7.5A	Brown	5	Micro Blade – 3 Blade Fuse
82-ANK-10A	10A	Red	5	Micro Blade – 3 Blade Fuse
82-ANK-15A	15A	Blue	5	Micro Blade – 3 Blade Fuse

LARGE BLADE FUSES

Fast Acting/Blade Mounting

A cost-effective automotive fuse for use in automotive, battery and general DC applications.

20A-80A, 32VDC

SPECIFICATIONS


Voltage: 32VDC

Amperage: 20A, 30A, 40A, 50A, 60A, 70A, 80A

Interrupt Rating: 1000A @ 32 VDC

Terminals: Zinc Alloy

Body Material: Nylon PA 66



Inches [mm]

APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-ANX-20A	20A	Yellow	1	Large Blade Fuse
82-ANX-30A	30A	Green	1	Large Blade Fuse
82-ANX-40A	40A	Orange	1	Large Blade Fuse
82-ANX-50A	50A	Red	1	Large Blade Fuse
82-ANX-60A	60A	Blue	1	Large Blade Fuse
82-ANX-70A	70A	Tan	1	Large Blade Fuse
82-ANX-80A	80A	Clear	1	Large Blade Fuse
82-ASST-53	(10A, 15A, 20A, 30A) + (30A, 40A, 50A)		45	Standard & Large Blade Fuse Assortment & Tester
82-ASST-64	(2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A) + (30A, 40A, 50A)		64	Miniature & Large Blade Fuse Assortment & Tester
FUSE HOLDER				
82-2211	60A (8GA)		1	Fuse Holder for Large Blade Style Fuses, 12"

AUTOMOTIVE LINK FUSE

Fast Acting/Blade Mounting

A cost-effective high-current automotive fuses for use in automotive, battery and general DC application.


20A-60A, 32VDC

SPECIFICATIONS

Voltage: 32VDC

Amperage: 15A, 20A, 25A, 30A, 40A, 50A, 60A, 70A, 80A, 100A, 120A

Interrupt Rating: 1,500A @32VDC



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-FMX-20A	20A	Blue	1	Automotive Link Fuse, Female
82-FMX-25A	25A	Clear	1	Automotive Link Fuse, Female
82-FMX-30A	30A	Pink	1	Automotive Link Fuse, Female
82-FMX-40A	40A	Green	1	Automotive Link Fuse, Female
82-FMX-50A	50A	Red	1	Automotive Link Fuse, Female
82-FMX-60A	60A	Yellow	1	Automotive Link Fuse, Female

AUTOMOTIVE LINK FUSE

LOW PROFILE



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-FMXLP-20A	20A	Blue	1	Automotive Link Fuse, Low Profile, Female
82-FMXLP-25A	25A	Clear	1	Automotive Link Fuse, Low Profile, Female
82-FMXLP-30A	30A	Pink	1	Automotive Link Fuse, Low Profile, Female
82-FMXLP-40A	40A	Green	1	Automotive Link Fuse, Low Profile, Female
82-FMXLP-50A	50A	Red	1	Automotive Link Fuse, Low Profile, Female
82-FMXLP-60A	60A	Yellow	1	Automotive Link Fuse, Low Profile, Female

AUTOMOTIVE LINK FUSE

MICRO



PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-FMX-M-15A	15A	Gray	1	Automotive Link Fuse, Micro, Female
82-FMX-M-20A	20A	Blue	1	Automotive Link Fuse, Micro, Female
82-FMX-M-25A	25A	White	1	Automotive Link Fuse, Micro, Female
82-FMX-M-30A	30A	Pink	1	Automotive Link Fuse, Micro, Female
82-FMX-M-40A	40A	Green	1	Automotive Link Fuse, Micro, Female

AUTOMOTIVE LINK FUSE




PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-FLB-40A	40A	Green	1	PAL Fuse Link, 13/16" Male Axial Terminal
82-FLB-60A	60A	Yellow	1	PAL Fuse Link, 13/16" Male Axial Terminal
82-FLB-70A	70A	Brown	1	PAL Fuse Link, 13/16" Male Axial Terminal
82-FLD-80A	80A	Black	1	PAL Fuse Link, 9/16" Male Axial Terminal
82-FLF-20A	20A	Light Blue	1	PAL Fuse Link, Female Terminal
82-FLF-30A	30A	Pink	1	PAL Fuse Link, Female Terminal
82-FLF-40A	40A	Green	1	PAL Fuse Link, Female Terminal
82-FLF-50A	50A	Red	1	PAL Fuse Link, Female Terminal
82-FLF-60A	60A	Yellow	1	PAL Fuse Link, Female Terminal
82-FLM-60A	60A	Yellow	1	PAL Fuse Link, Male Radial Terminal
82-FLM-80A	80A	Black	1	PAL Fuse Link, Male Radial Terminal
82-FLM-100A	100A	Blue	1	PAL Fuse Link, Male Radial Terminal
82-FLM-120A	120A	Gray	1	PAL Fuse Link, Male Radial Terminal
82-FLS-30A	30A	Pink	1	PAL Fuse Link, Female Terminal
82-FLS-40A	40A	Green	1	PAL Fuse Link, Female Terminal

AUTOMOTIVE LINK FUSE ASSORTMENT

- Includes the top male and female automotive fusible links for late model import vehicles
- Includes 1 each of: FLB 40A/60A/70A, FLD 80A, FLF 20A/30A/40A/50A/60A, FLM 80A/100A, FLS 30A/40A, FMX 20A/30A/40A

PART #	CURRENT RATING	PACK	DESCRIPTION
82-ASST-45	(20A, 30A, 40A, 50A, 60A, 70 A, 80A, 100A)	16	Automotive Link Fuse Assortment



GLASS FUSES

FSA, AGC, AGX, AGW, AGA, FSO



Agency Standards and Listings:


UL Listed 100mA~10A
UR Recognized 12A~30A
CSA Certified 100mA~30A

Interrupt Ratings:

10,000 amperes at 125V AC (100mA~10A)
35 amperes at 250V AC (100mA~1A)
100 amperes at 250V AC (1.2A~3.5A)
200 amperes at 250V AC (4A~10A)
300 amperes at 32V AC (12A~30A)

Operating Temperature:

-55°C to +125°C (-67°F to +257°F)



Inches [mm]

Physical Specifications:

Materials: Glass Body/Nickel Plated Brass Contacts

Electrical Characteristics

Rated Current: 100%
@ 100% – 4 hours min
@ 135% – 1 hour max
@ 200% – 5 sec max



PART #	CURRENT RATING	PACK	DESCRIPTION
82-FSA-1A-G	1A	5	AGC, Glass Fuse
82-FSA-2A-G	2A	5	AGC, Glass Fuse
82-FSA-3A-G	3A	5	AGC, Glass Fuse
82-FSA-5A-G	5A	5	AGC, Glass Fuse
82-FSA-10A-G	10A	5	AGC, Glass Fuse
82-FSA-15A-G	15A	5	AGC, Glass Fuse
82-FSA-20A-G	20A	5	AGC, Glass Fuse
82-FSA-25A-G	25A	5	AGC, Glass Fuse
82-FSA-30A-G	30A	5	AGC, Glass Fuse
82-FSA-9-G	(1A, 2A, 3A, 5A, 10A, 15A, 20A, 25A, 30A)	9	AGC, Glass Fuse Assortment
82-AGC-60	(5A, 10A, 15A, 20A, 25A, 30A)	60	AGC, Glass Fuse Assortment & Tester
82-AGX-5	(5A, 7.5A, 10A, 20A, 30A)	5	AGX, Glass Fuse Assortment
82-AGW-5	(5A, 7.5A, 10A, 20A, 30A)	5	AGW, Glass Fuse Assortment
82-AGA-6	(3A, 5A, 7.5A, 10A, 20A, 30A)	6	AGA, Glass Fuse Assortment
82-FSO-7-G	(4A, 6A, 7.5A, 9A, 14A, 20A, 30A)	7	SFE, Glass Fuse Assortment

ASSORTMENT KITS

Assortment Kits

Grote’s assortment packs contain a variety of popular fuses that will provide you with replacement fuses for circuit protection as you need them!

The Grote assortment pack is perfect for the shop at home or at work! Choose from a variety of assortment packs that best suit your needs and applications.



PART #	CURRENT RATING	PACK	DESCRIPTION
MINIATURE BLADE FUSES WITH LED INDICATOR			
82-ANM-I-5	(10A, 15A, 20A, 25A, 30A)	5	Miniature Blade Fuses with LED Indicator
MINIATURE BLADE FUSES			
82-ANM-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	7	Miniature Blade Fuses
82-ANM-8P	(2A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	9	Miniature Blade Fuses + Puller
82-ANM-8T	(2A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	9	Miniature Blade Fuses + Tester
82-ASST-43	(5A, 10A, 15A, 20A, 25A, 30A)	43	Miniature Blade Fuses + Tester
82-ASST-64	(2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A) + (30A, 40A, 50A)	64	Miniature Blade and Large Blade Fuses + Tester
82-ASST-80M	(3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	80	Miniature Blade Fuses
82-ASST-180	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	180	Low Profile Miniature Blade and Standard Blade Fuses
LOW PROFILE MINIATURE BLADE FUSES			
82-ANS-I-5	(10A, 15A, 20A, 25A, 30A)	5	Low Profile Miniature LED Blade Fuses
82-ANS-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	7	Low Profile Miniature Blade Fuses
82-ANS-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	8	Low Profile Miniature Blade Fuses + Puller
82-ANS-7T	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	8	Low Profile Miniature Blade Fuses + Tester
STANDARD BLADE FUSES WITH LED INDICATOR			
82-ANR-I-5	(10A, 15A, 20A, 25A, 30A)	5	Standard Blade Fuses with LED Indicator
STANDARD BLADE FUSES			
82-ANR-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	7	Standard Blade Fuses
82-ANR-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	8	Standard Blade Fuses + Puller
82-ANR-6T	(5A, 10A, 15A, 20A, 25A, 30A)	7	Standard Blade Fuses + Tester
82-ASST-44	(5A, 10A, 15A, 20A, 25A, 30A)	43	Standard Blade Fuses + Tester
82-ASST-53	(10A, 15A, 20A, 30A) + (30A, 40A, 50A)	45	Standard Blade & Large Blade Fuses + Tester
82-ASST-80R	(3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	80	Standard Blade Fuses
82-ASST-180	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	180	Low Profile Miniature, Miniature, Standard Blade Fuses
LARGE BLADE FUSES			
82-ASST-53	(10A, 15A, 20A, 30A) + (30A, 40A, 50A)	45	Standard Blade & Large Blade Fuses + Tester
82-ASST-64	(2A, 3A, 4A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A) + (30A, 40A, 50A)	64	Miniature Blade and Large Blade Fuses + Tester
MICRO BLADE – 2 BLADE FUSES			
82-ANT-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	7	Micro Blade – 2 Blade Fuses
82-ANT-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)	8	Micro Blade – 2 Blade Fuses + Puller
FUSIBLE LINK ASSORTMENT			
82-ASST-45	(20A, 30A, 40A, 50A, 60A, 70 A, 80A, 100A)	16	Automotive Link Fuse Assortment

BOLT ON FUSES


Fast Acting Automotive Bolt On Limiter Fuse
Bolt On type fuses are used in circuit where high current are present and are typically found in select late model cars and trucks. Bolt On type fuses are ideal for battery and/or alternator applications.

100A-300A, 32VDC



SPECIFICATIONS

Voltage: 32VDC
Amperage: 80A, 100A, 125A, 150A, 175A, 200A, 225A, 250A, 300A
Interrupt Rating: 2000A @ 32V
Operating Temperature: -40°C to +125°C (-40°F to +257°C)
Body Material: Polypropylene



APPROVALS: MEETS SAE STANDARDS & ISO 8820 STANDARD SPECIFICATIONS

PART #	CURRENT RATING	COLOR	PACK	DESCRIPTION
82-MGGA-80A	80A	Black	1	Bolt On Fuse
82-MGGA-100A	100A	Black	1	Bolt On Fuse
82-MGGA-125A	125A	Black	1	Bolt On Fuse
82-MGGA-150A	150A	Black	1	Bolt On Fuse
82-MGGA-175A	175A	Black	1	Bolt On Fuse
82-MGGA-200A	200A	Black	1	Bolt On Fuse
82-MGGA-225A	225A	Black	1	Bolt On Fuse
82-MGGA-250A	250A	Black	1	Bolt On Fuse
82-MGGA-300A	300A	Black	1	Bolt On Fuse
82-MGGA-FB			1	Fuse Block – Bolt On Fuse

FUSE TESTER/PULLER



- For standard blade automotive fuses
- Use to remove or insert or test fuses
- Can test fuses in or out of a fuse block
- Has a green indicator light on the end of the tester. Indicator light will remain on if fuse is good. If fuse is broken, the LED light will not light up

PART #	PACK	DESCRIPTION
82-PUL-07	1	Fuse Tester & Puller

FUSE PULLER



- For automotive miniature blade fuses
- Material: ABS

PART #	PACK	DESCRIPTION
82-PUL-01	1	Fuse Puller

FUSE TAPS – INSULATED



PART #	DESCRIPTION	SIZE	PACK
84-2917	Fuse Taps – Uninsulated	.187"	25
84-2919	Fuse Taps – Uninsulated	.187"	8
84-2916	Fuse Taps – Uninsulated	.250"	25
84-2918	Fuse Taps – Uninsulated	.250"	8

IN-LINE FUSE HOLDERS

- Nylon fuse holder for glass tube fuses
- Fits ¼" x 1 ¼" glass fuses
- Protects electrical equipment
- In-Line fuse holders include a fuse

PART #	CURRENT RATING	DESCRIPTION
82-2160	20A (18GA)	7" In-Line Fuse Holder (Black)
82-2162	10A (18GA)	7" In-Line Fuse Holder (White)
82-2161	15A (16GA)	7" In-Line Fuse Holder (Red)
82-2163	30A (14GA)	7" In-Line Fuse Holder (Black)



BAYONET STYLE FUSE HOLDER

- Nylon fuse holder for glass tube fuses
- Fits ¼" x 1 ¼" glass fuses
- Protects electrical equipment

PART #	CURRENT RATING	DESCRIPTION
82-2167	30A (12GA)	7" Bayonet Fuse Holder (Black)
82-2168	20A (14GA)	7" Bayonet Fuse Holder (Black)
82-2169	20A (14GA)	12" Bayonet Fuse Holder (Black)



FUSEBLOCK – GLASS FUSES

- For use with glass fuses
- Quick disconnect take off, .250"

PART #	DESCRIPTION	SIZE
82-2301	Glass Fuses Fuse Block – 4 Fuse	3" x 2.5"
82-2302	Glass Fuses Fuse Block – 6 Fuse	4.5" x 2.5"



PANEL MOUNT FUSE

- Provides circuit protection for electrical systems
- 15A, .250" quick disconnect contacts, glass fuse
- Round fuseholder mounts easily into any dashboard

PART #	CURRENT RATING	DESCRIPTION
82-2215	15A	.250" Panel Mount Fuse



LED STANDARD BLADE FUSE PANELS



82-BLR-I-310

- Fuse Type: Standard Automotive Blade
- Cover: Opaque Lexan (UL 94-V2)
- Indicating LED – Red
- Compact, lightweight and rugged construction
- Protects electrical equipment
- Base: Black thermoplastic (UL-Flame 94-V0)
- Terminals: Tin plated brass .250" quick disconnect
- Stud: #10-32 steel, nickel plated
- Max current rating: 25 A per circuit; 100 A max

PART #	DESCRIPTION
82-BLR-I-304	LED Standard Blade Fuse Panel w/cover – 4 Position
82-BLR-I-306	LED Standard Blade Fuse Panel w/cover – 6 Position
82-BLR-I-310	LED Standard Blade Fuse Panel w/cover – 10 Position

STANDARD BLADE FUSE PANELS



82-2304

- Fuse Type: Standard Automotive Blade
- Compact, lightweight and rugged construction
- Protects electrical equipment
- Base: Black thermoplastic (UL-Flame 94-V0)
- Terminals: Tin plated brass .250" quick disconnect
- Stud: #10-32 steel, nickel plated
- Max current rating: 25 A per circuit; 100 A max

PART #	DESCRIPTION
82-2303	Standard Blade Fuse Panel – 6 Position
82-2304	Standard Blade Fuse Panel – 8 Position
82-2305	Standard Blade Fuse Panel – 10 Position

LED MINIATURE BLADE FUSE PANELS



82-BLM-I-306

- Fuse Type: Miniature Automotive Blade
- Cover: Opaque Lexan (UL 94-V2)
- Indicating LED – Red
- Compact, lightweight and rugged construction
- Protects electrical equipment
- Base: Black thermoplastic (UL-Flame 94-V0)
- Terminals: Tin plated brass .250" quick disconnect
- Stud: #10-32 steel, nickel plated
- Max current rating: 25 A per circuit; 100 A max

PART #	DESCRIPTION
82-BLM-I-304	LED Miniature Blade Fuse Panel w/cover – 4 Position
82-BLM-I-306	LED Miniature Blade Fuse Panel w/cover – 6 Position
82-BLM-I-310	LED Miniature Blade Fuse Panel w/cover – 10 Position

TERMINAL STRIPS – STUD TYPE



82-2313

- Anti-corrosive nuts and washers
- 30 AMP @ 12V DC
- Stud: #10-32 brass, mounted on 5/8" centers

PART #	DESCRIPTION
82-2311	Terminal Strips, Stud Type – 4 Stud
82-2312	Terminal Strips, Stud Type – 6 Stud
82-2313	Terminal Strips, Stud Type – 8 Stud
82-2314	Terminal Strips, Stud Type – 10 Stud

BARRIER STRIPS – SCREW TYPE



82-2338

- Black phenolic base
- 30 AMP @ 12V DC
- Brass screws with 3/8" centers; #8 mounting screw
- Temperature rating: 150°C (302°F)

PART #	DESCRIPTION
82-2332	Barrier Strips, Screw Type – 4 Position
82-2334	Barrier Strips, Screw Type – 6 Position
82-2338	Barrier Strips, Screw Type – 10 Position

RELAYS



- General purpose relays designed to fit standard vehicles and equipment
- Available in standard and micro blade termination
- Available in 12V or 24V
- Can be purchased stand alone – or with a pigtail connection

RELAY ONLY

PART #	VOLTAGE	AMPS	FORM
84-1076	12V	30/40	S.P.D.T.
84-1093	24V	30/40	S.P.D.T.
84-1079	12V	40/30	S.P.D.T.
84-1077*	12V	30/20	S.P.D.T.

* Micro Blade


RELAY + PIGTAIL

PART #	VOLTAGE	AMPS	FORM
84-1040	12V	30/40	S.P.D.T.
84-1094	24V	40/30	S.P.D.T.
84-1080*	12V	40/30	S.P.D.T.

* Includes voltage spike resistor

PIGTAIL ONLY

PART #	GAUGE	LENGTH	APPLICATION
84-1041	14	12"	Pigtail for 84-1076 & 84-1093
84-1078	12	12"	Pigtail for 84-1079 (Weather Resistant)



09

BATTERY CONNECTORS & CABLE

CONNECTEURS ET
CÂBLES DE BATTERIE

TERMINALES Y CABLES
PARA BATERIA

- 134 Battery Connectors
- 142 Conversion Connectors and Adapters
- 144 Booster Clamps and Cables
- 145 Charging Clips
- 146 Booster Cable – Twin Conductor
- 148 Battery Cables
- 152 Battery Disconnect Switches
- 153 Battery Protective Products
- 154 Crimpers and Cutters
- 156 Battery Boxes
- 159 Hold-downs and Trays
- 160 Battery Cable
- 161 Welding Cable

GROTE'S HAS A COMPLETE LINE OF BATTERY CONNECTORS, CABLE, REPLACEMENT AND SERVICE PARTS, TEST CLIPS AND TERMINAL PROTECTIVE PRODUCTS AND OF COURSE CHARGING OPTIONS FOR ALL OF YOUR EQUIPMENT'S POWER DELIVERY NEEDS.

LIGHT DUTY, HOME AND GARDEN EQUIPMENT, HEAVY VEHICLE OR INDUSTRIAL APPLICATIONS – GROTE HAS THE BATTERY CONNECTION PRODUCT YOU NEED!





Proper connections to a vehicles power supply are vital to performance. Make the right choice – go with Grote Battery Connectors and Cables.

DIE-CAST BATTERY CONNECTORS



- Copper die-cast and bright tin plating exceeds SAE J163 & J1811 conductivity standards by 25 times
- Ultra-smooth, pit-free cast surface resists against harmful materials and corrosion
- Can be crimped or soldered; can be installed with most major crimping tools
- Provides full height post connection
- Includes 5/16" battery bolts and shoulder nuts; fasteners included
- Clamps are marked for easy identification
- Listed by UL STD. 486A & cUL® US when applied with Hex Crimp 84-9082
- Made in North America; Available in Retail and Bulk sizes
- Rated to 600V; lead-free

STRAIGHT BARREL CLAMP

CABLE GAUGE	COLOR CODE	RETAIL PACK SIZE	NEGATIVE	POSITIVE	BULK PACK SIZE	NEGATIVE	POSITIVE
4	Grey	1	82-9053	82-9054	5	84-9053	84-9054
2	Green	1	82-9050	82-9051	5	84-9050	84-9051
1	Pink	1	82-9047	82-9048	5	84-9047	84-9048
1/0	Black	1	82-9056	82-9057	5	84-9056	84-9057
2/0	Orange	1	82-9058	82-9059	5	84-9058	84-9059
3/0	Purple	1	82-9060	82-9061	5	84-9060	84-9061
4/0	Yellow	1	82-9062	82-9063	5	84-9062	84-9063

FLAG CONNECTOR

CABLE GAUGE	COLOR CODE	RETAIL PACK SIZE	NEGATIVE	POSITIVE	BULK PACK SIZE	NEGATIVE	POSITIVE
1/0	Black	1	82-9095	82-9096	5	84-9095	84-9096
2/0	Orange	1	82-9097	82-9098	5	84-9097	84-9098
3/0	Purple	1	82-9099	82-9100	5	84-9099	84-9100
4/0	Yellow	1	82-6010	82-6011	5	84-6010	84-6011

RIGHT AND LEFT ELBOW

CABLE GAUGE	COLOR CODE	ANGLE	RETAIL PACK SIZE	NEGATIVE	POSITIVE	BULK PACK SIZE	NEGATIVE	POSITIVE
1/0	Black	Right	1	82-9640	82-9641	5	84-9640	84-9641
1/0	Black	Left	1	82-9642	82-9647	5	84-9642	84-9647
2/0	Orange	Right	1	82-9648	82-9649	5	84-9648	84-9649
2/0	Orange	Left	1	82-9650	82-9651	5	84-9650	84-9651
3/0	Purple	Right	1	82-9652	82-9653	5	84-9652	84-9653
3/0	Purple	Left	1	82-9654	82-9655	5	84-9654	84-9655



84-9648

- Use on stud style batteries

CABLE GAUGE	COLOR CODE	5/16" (8 MM)	3/8" (10 MM)	1/2" (12 MM)	PACK SIZE
4	Grey	84-9105	84-9106	—	5
2	Green	—	84-9103	—	5
1	Pink	—	84-9101	—	5
1/0	Black	—	84-9108	84-9109	5
2/0	Orange	—	84-9110	84-9111	5
3/0	Purple	—	84-9112	84-9113	5
4/0	Yellow	—	84-9114	84-9115	5

HEAVY WALL COPPER LUGS



84-9110

STUD/SIDE LOCKING LUG



84-9309

SPLICES – TIN PLATED



84-9448



82-9556

UNINSULATED BRAZED SEAM LUGS



84-9443


- Seamless 100% copper tube construction
- Heavy tin-plated for superior conductivity and resistance to corrosion
- Can be crimped or soldered – ideal for most applications

CABLE GAUGE	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
8	82-9552	2	84-9552	10
6	82-9463	2	84-9463	10
4	82-9448	2	84-9448	10
2	82-9553	2	84-9553	10
1	82-9554	2	84-9554	10
1/0	82-9555	2	84-9555	10
2/0	82-9556	2	84-9556	10
3/0	82-9557	2	84-9557	10
4/0	82-9558	2	84-9558	10

- 100% copper tin-plated
- Serrated barrel increases pull-out strength of hard-to-crimp wire
- Can be crimped or soldered
- Ideal for solder dipping applications
- Lead-free

CABLE GAUGE	STUD SIZE	BULK PACK	PACK SIZE
8	#10	84-9548	10
6	1/2"	84-9442	10
4	1/2"	84-9443	10

MAGNALUG® CONNECTORS



STANDARD LUG MAGNALUG®

- MagnaLugs® are superior to standard tube lugs
- Wider pad for better electrical contact; thicker pad for greater strength & conductivity
- Exceeds SAE conductivity standards J163 and J1811
- MagnaLugs® listed by UL STD. 486A & cUL® US when applied with Hex Crimp 84-9082
- Up to 80% heavier wall than standard lugs
- Made of 100% copper, tin-plated twice as thick as industry standards
- For truck, bus, farm or construction equipment
- Excellent for commercial or industrial applications
- Flameless installation, safe for repair shop or field repair
- Lead-free

STARTER/GROUND COPPER LUGS



84-9208

CABLE GAUGE	COLOR CODE	1/4" (6 MM)	5/16" (8 MM)	3/8" (10 MM)	1/2" (12 MM)	PACK SIZE
8	Grey	84-9461	84-9635	—	—	5
6	Grey	—	—	84-9636	—	5
4	Grey	84-9199	—	84-9200	84-9201	5
1 & 2	Pink	84-9196	—	84-9197	84-9198	5
1/0	Black	84-9202	—	84-9203	84-9204	5
2/0	Orange	84-9205	84-9637	84-9206	84-9207	5
3/0	Purple	—	—	84-9208	84-9209	5
4/0	Yellow	—	—	84-9210	84-9211	5

LOCKING ANTI ROTATIONAL STACKABLE LUG



84-9192

CABLE GAUGE	COLOR CODE	3/8" (10 MM)	PACK SIZE
1/0	Black	84-9192	5
2/0	Orange	84-9193	5

SPLICES



84-9220

CABLE GAUGE	COLOR CODE	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
4	Grey	82-9219	2	84-9219	10
1 & 2	Pink	82-9218	2	84-9218	10
1/0	Black	82-9220	2	84-9220	10
2/0	Orange	82-9221	2	84-9221	10
3/0	Purple	—	2	84-9222	10
4/0	Yellow	—	2	84-9223	10

WE KNOW THE
POWER OF A GOOD
CONNECTION



At Grote Industries, **WE ARE COMMITTED TO TAKING CARE OF OUR CUSTOMERS** by ensuring that they receive the information and products they need, when they need them. That's why we are continually investing in industry-leading technology that allows us to connect to our valued customers.

CONNECT YOUR FLEET WITH GROTE
GROW YOUR FLEET WITH GROTE

Grote offers fleets full-service partnership support so you can stop worrying about inventories or suppliers. Grote can even provide comprehensive training to your maintenance partners, to ensure you get the most benefit from your Grote Electrical Connections and Accessory products. Connect with our experienced team of technical, sales & customer solution experts. Connect with our digital tools and **G24/7 ONLINE CUSTOMER SERVICE PLATFORM**. Limit unplanned maintenance downtime, and improve your fleet's safety and profitability, with our innovative and high quality electrical connection and accessory products.



CONTACT US

CALL US AT 1-800-268-5612, OR CHECK OUT OUR G24/7 ONLINE CUSTOMER SERVICE PLATFORM AT [SHOP.GROTE.COM](https://shop.grote.com)

TIN PLATED COPPER TUBE LUGS



- Seamless 100% copper tube construction
- Can be crimped/soldered; ideal for general wiring, starter, ground applications
- Heavy tin-plated for superior conductivity and resistance to corrosion
- Flared barrel for easy installation of cables
- Available in clam shell packaging or bulk bag
- Lead-free



CABLE GAUGE	STUD SIZE	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
8	#10	82-9164	2	84-9164	25
8	1/4"	82-9165	2	84-9165	25
8	5/16"	82-9537	2	84-9537	25
8	3/8"	82-9523	2	84-9523	25
8	1/2"	82-9547	2	84-9547	25
6	#10	82-9524	2	84-9524	25
6	1/4"	82-9166	2	84-9166	25
6	5/16"	82-9167	2	84-9167	25
6	3/8"	82-9168	2	84-9168	25
6	1/2"	82-9525	2	84-9525	25
4	1/4"	82-9317	2	84-9317	25
4	5/16"	82-9169	2	84-9169	25
4	3/8"	82-9170	2	84-9170	25
4	1/2"	82-9527	2	84-9527	25
2	1/4"	82-9318	2	84-9318	25
2	5/16"	82-9319	2	84-9319	25
2	3/8"	82-9171	2	84-9171	25
2	1/2"	82-9172	2	84-9172	25
1	1/4"	82-9528	2	84-9528	25
1	5/16"	82-9533	2	84-9533	25
1	3/8"	82-9173	2	84-9173	25
1	1/2"	82-9174	2	84-9174	25
1/0	1/4"	82-9535	2	84-9535	25
1/0	5/16"	82-9534	2	84-9534	25
1/0	3/8"	82-9175	2	84-9175	25
1/0	1/2"	82-9176	2	84-9176	25
2/0	5/16"	82-9536	2	84-9536	25
2/0	3/8"	82-9177	2	84-9177	25
2/0	1/2"	82-9178	2	84-9178	25
3/0	3/8"	82-9179	2	84-9179	25
3/0	1/2"	82-9180	2	84-9180	25
4/0	3/8"	82-9181	2	84-9181	25
4/0	1/2"	82-9182	2	84-9182	25



84-9175



83-6544

TIN PLATED COPPER TUBE LUG ASSORTMENT KIT

- Includes 76 of the most popular automotive & heavy duty copper tube lugs
- Heavy tin plated for superior conductivity and resistance to corrosion
- Can be crimped or soldered
- 12 compartment resealable box with re-order chart on inside cover

83-6544 8 – 3/0 GA Copper Tube Lugs

STANDARD COPPER TUBE LUGS



- Seamless 100% copper tube construction
- Can be crimped or soldered – ideal for most general purpose applications
- Flared barrel for easy installation of cables
- Available in clam shell packaging or bulk bag
- Lead-free



CABLE GAUGE	STUD SIZE	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
8	#10	82-9521	2	84-9521	25
8	5/16"	82-9538	2	84-9538	25
8	3/8"	82-9428	2	84-9428	25
8	1/2"	82-9539	2	84-9539	25
6	#10	82-9514	2	84-9514	25
6	1/4"	82-9522	2	84-9522	25
6	5/16"	82-9512	2	84-9512	25
6	3/8"	82-9429	2	84-9429	25
6	1/2"	82-9513	2	84-9513	25
4	1/4"	82-9515	2	84-9515	25
4	5/16"	82-9516	2	84-9516	25
4	3/8"	82-9430	2	84-9430	25
4	1/2"	82-9529	2	84-9529	25
2	1/4"	82-9517	2	84-9517	25
2	5/16"	82-9518	2	84-9518	25
2	3/8"	82-9431	2	84-9431	25
2	1/2"	82-9530	2	84-9530	25
1	1/4"	82-9519	2	84-9519	25
1	5/16"	82-9531	2	84-9531	25
1	3/8"	82-9432	2	84-9432	25
1	1/2"	82-9520	2	84-9520	25
1/0	1/4"	82-9545	2	84-9545	25
1/0	5/16"	82-9532	2	84-9532	25
1/0	3/8"	82-9433	2	84-9433	25
1/0	1/2"	82-9434	2	84-9434	25
2/0	5/16"	82-9546	2	84-9546	25
2/0	3/8"	82-9435	2	84-9435	25
2/0	1/2"	82-9436	2	84-9436	25
3/0	3/8"	82-9437	2	84-9437	25
3/0	1/2"	82-9438	2	84-9438	25
4/0	3/8"	82-9439	2	84-9439	25
4/0	1/2"	82-9440	2	84-9440	25



84-9436



83-6543

COPPER TUBE LUG ASSORTMENT KIT

- Includes 76 of the most popular automotive & heavy duty copper tube lugs
- Provides superior conductivity
- Can be crimped or soldered
- 12 compartment resealable box
- Re-order chart on inside cover

83-6543 8 – 3/0 GA Copper Tube Lugs

BATTERY CONNECTORS – HEAVY DUTY



84-9133

- Clamps designed for truck, bus, construction, agricultural, industrial applications
- Polarity-specific brass or universal polarity lead construction; hardware included
- Accept 1 through 4/0 gauge cable

DESCRIPTION	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Universal Clamp 1-4/0 Gauge	Lead; zinc-plated, steel fasteners	82-9133	2	84-9133	25

BATTERY CONNECTORS – AUTOMOTIVE



82-9613

84-9134

84-9126

- Automotive and light truck applications
- Universal clamp and side terminal styles; constructed of lead or brass
- Accept 6 through 2/0 gauge cable sizes
- Zinc-plated steel hardware included

DESCRIPTION	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Universal Clamp	Lead; zinc-plated, steel fasteners	82-9135	2	84-9135	25
Universal Clamp	Brass; zinc-plated, steel fasteners	82-9126	1	84-9126	25
Universal Clamp	Lead; epoxy coated 1 red, 1 black	82-9613	2		
Universal Side Terminal	Lead; zinc-plated, steel fasteners	82-9134	2	84-9134	25

AUTOMOTIVE TERMINAL CLAMPS



84-9671

TOP POST & SIDE MOUNT, CARDS OF 10

- Both products offered in convenient cards of 10 pieces per card
- Both accept 6 through 2/0 gauge cable

PART #	DESCRIPTION
84-9671	Automotive Top Post Terminal Clamps
84-9672	Automotive Side Mount Terminal Clamps

LEAD FREE CONNECTORS



84-9618

82-9597

- Accept 8 through 4 gauge cable sizes
- Tin plated alloy resists corrosion
- For recreational and light duty applications

DESCRIPTION	BULK PACK	PACK SIZE
Top Post, 8-6-4 GA	84-9618	5 Pair (Pos/Neg)
Top Post, 8-6-4 GA, with auxiliary take off	82-9597	1 Pair (Pos/Neg)

- Converts battery post to stud connector
- Permits quick disconnection from battery; eliminates current drain during storage
- Polarity-specific; meets U.S. Coast Guard regulations
- Brass or lead construction; hardware included



DESCRIPTION	SIZE	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Top Post; Positive	5/16"	Brass; zinc-plated steel fasteners	82-9124	1	84-9124	25
Top Post; Positive	3/8"	Lead; zinc-plated steel fasteners	82-9541	1	84-9541	25
Top Post; Negative	5/16"	Brass; zinc-plated steel fasteners	82-9125	1	84-9125	25
Top Post; Negative	5/16"	Lead; zinc-plated steel fasteners	82-9542	1	84-9542	25

- Exceeds military specifications # A52425-1 & A52425-2
- Low profile design, only 3/4" high
- Long bolt permits additional power connections

DESCRIPTION	MATERIAL	BULK PACK	PACK SIZE
Top Post; Positive	Lead; zinc plated steel fasteners	84-9581	5
Top Post; Negative	Lead; zinc plated steel fasteners	84-9580	5

BATTERY CONNECTORS – MARINE



84-9124

84-9542

BATTERY CONNECTORS – MILITARY



84-9580

TOP POST – 3 WAY TERMINAL

- Accept 2 through 1/0 gauge cable sizes
- Zinc plated, steel fasteners

DESCRIPTION	MATERIAL	RETAIL PACK	PACK SIZE
Top Post	Lead, 1 pos., 1 neg.	82-9620	1 pair



82-9620

BATTERY QUICK DISCONNECT

- 1/4" turn of the knob disconnects battery power
- Lead-free
- Copper; brass plated with zinc plated steel fasteners

DESCRIPTION	RETAIL PACK	PACK SIZE
Top Post, Negative	82-9595	1
Side Terminal, Universal	82-9596	1



82-9595

82-9596

CONVERSION CONNECTORS

STUD-TO-TOP POST



- Converts stud terminal battery to top post
- Polarity specific for exact fit
- 3/8" – 16 threaded steel insert and nylon lock ring provide superior electrical and mechanical integrity
- 3/4" hex base permits precise torquing

DESCRIPTION	SIZE	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Stud to Top Post	3/8"-16	Lead; die-cast steel	82-9130	1 pair	84-9130	5 pair

CONVERSION CONNECTORS

SIDE TERMINAL-TO-TOP POST



- Permits top terminal cable connection to side terminal battery
- Stud head resists over-torque and improves conductivity; zinc-plated stud resists corrosion
- Polarity-specific for exact fit; oversize polarity signs molded in

DESCRIPTION	SIZE	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Top Post to Side Terminal	3/8"	Lead; die-cast steel	82-9131	1 pair	84-9131	5 pair
Negative	3/8"				84-9610	5
Positive	3/8"				84-9611	5

TERMINAL CONNECTORS

TOP POST-TO-SIDE



- Permits side terminal cable connection to top terminal battery
- Polarity-specific for exact fit on posts; polarity signs molded in
- Lead construction – zinc plated hardware resists corrosion

DESCRIPTION	SIZE	MATERIAL	RETAIL PACK	PACK SIZE
Top Post to Side Terminal	3/8"	Lead; zinc-plated steel fasteners	82-9132	1 pair

PROTECTIVE WASHERS



- Extends the life of the battery, connectors and hardware
- Easy to assemble

DESCRIPTION	PACK SIZE	PART #
Top Post Terminal	2	82-9623
Top Post Terminal	100	84-9624

FASTENER HARDWARE

- Complete selection of standard and heavy-duty battery-related hardware
- Meets OEM and SAE specifications



DESCRIPTION	SIZE	MATERIAL	RETAIL PACK	PACK SIZE	BULK PACK	PACK SIZE
Bolt, square head & nut	5/16" - 18 x 1 3/8"	Steel; zinc-plated	82-9183	2	84-9183	25
Bolt, square head & shoulder nut	5/16" - 18 x 1 3/8"	Steel; tin-plated	—		84-9289	25
Nut, closed cap for Group 31	3/8" - 16	Stainless Steel	82-9184	1	84-9184	25
Nut, flange	3/8" - 16	Steel; zinc-plated	—		84-9445	10
Bolt, side terminal; single power lead	3/8"- 16 x 13/32"	Steel; zinc-plated	82-9216	2	84-9216	25
Bolt, side terminal; dual power lead	3/8"- 16 x 1"	Steel; zinc-plated	82-9217	2	84-9217	25
Shim, battery post		Lead	—		84-9593	25
Spacer, for dual power lead, side terminal bolt		Lead	—		84-9612	10

ACCESSORY ADAPTER NUTS

- Connects power accessories directly to battery
- Fits standard battery bolt
- For post-terminal applications



DESCRIPTION	SIZE	MATERIAL	PACK SIZE	BULK PACK	PACK SIZE
Top terminal accessory post	5/16" - 18 x 9/16"	Brass; zinc-plated steel fasteners	1	84-9185	5
Side terminal extension bolt	3/8" - 16 x 13/32"	Brass; zinc plated fasteners		84-9599	5

POST-TERMINAL BRUSH

- Corrosion-resistant self-contained brush set
- Inner bristles clean post terminals
- Conical outer bristles clean cable connectors

PART #	PACK SIZE
84-9186	1



BOOSTER CLAMPS – REPLACEMENT



- Jaws grip battery posts, studs & side terminals
- Insulated grips in both black & red
- For 1-3/0 gauges
- 3 coil spring, over 50 lbs of clamping pressure
- Solid copper clamps weigh over 3/4 lb.
- 5/16" – 18 nut & bolt included

RATING	JAW TYPE	DESCRIPTION	GRIP COLOR	PACK	PART #
400 AMP	Standard Jaws	Commercial grade	Red & Black	Pair	84-9280
500 AMP	Parrot Jaws	Industrial grade	Red & Black	Pair	84-9281
900 AMP	Parrot Jaws	Industrial grade	Red	1	84-9321
900 AMP	Parrot Jaws	Industrial grade	Black	1	84-9322
900 AMP	Parrot Jaws	Industrial grade	Red & Black	Pair	84-9630

BATTERY CABLE CONNECTORS



PLUG-IN STYLE

- Color coded ends help identify different voltages and will prevent mismatching power supply to the electrical output
- Comes complete with 1 housing and 2 contact terminals
- Housings mate together with the same color plug and receptacle – simply rotate connector 180° and plug similar part numbers together
- Available in 50, 175 and 350 AMP ratings for use up to 600 volt AC or DC

RATING	TYPE	GAUGE	COLOR	PACK	PART #
50 AMP	Plug-In End	12-10	Red	1	84-9680
50 AMP	Plug-In End	12-10	Grey	1	84-9627
50 AMP	Plug-In End	6	Red	1	84-9626
50 AMP	Plug-In End	6	Grey	1	84-9631
175 AMP	Plug-In End	4	Red	1	84-9681
175 AMP	Plug-In End	4	Blue	1	84-9551
175 AMP	Plug-In End	4	Grey	1	84-9632
175 AMP	Plug-In End	2	Red	1	84-9682
175 AMP	Plug-In End	2	Blue	1	84-9487
175 AMP	Plug-In End	2	Grey	1	84-9633
175 AMP	Plug-In End	1/0	Red	1	84-9628
175 AMP	Plug-In End	1/0	Blue	1	84-9683
175 AMP	Plug-In End	1/0	Grey	1	84-9634
350 AMP	Plug-In End	2/0	Red	1	84-9482
350 AMP	Plug-In End	2/0	Blue	1	84-9684
350 AMP	Plug-In End	2/0	Grey	1	84-9485

BATTERY CABLE CONNECTORS



PROTECTIVE CAPS – PLUG-IN STYLE

- Black protective caps cover the connector from weather and chemicals when not in use
- Available in three sizes

RATING	TYPE	DESCRIPTION	GRIP COLOR	PACK	PART #
50 AMP	Plug-In End	Fits 50 AMP housings	Black	1	84-9621
175 AMP	Plug-In End	Fits 175 AMP housing	Black	1	84-9456
350 AMP	Plug-In End	Fits 350 AMP housings	Black	1	84-9622

HEAVY DUTY CHARGING CLIPS



- Jaws accommodate up to 3/4"
- Excellent for test equipment
- Use for OEM repair and custom build
- Color-coded vinyl boots

RATING	JAW TYPE	DESCRIPTION	GRIP COLOR	RETAIL PACK	PACK
75 AMP	Clamp style	Industrial grade	Red	84-4997	1
75 AMP	Clamp style	Industrial grade	Black	84-4998	1
75 AMP	Clamp style	Industrial grade	Red & Black	84-4999	Pair
50 AMP	Clamp style	Industrial grade	Red	84-5002	1
50 AMP	Clamp style	Industrial grade	Black	84-5003	1
50 AMP	Clamp style	Industrial grade	Red & Black	84-5000	Pair

TEST CLIPS



- For test/charge applications
- Jaws accommodate up to 3/4"

RATING	JAW TYPE	JAW SPREAD	RETAIL PACK	PART #	BULK PACK	PACK
10 AMP	Standard Jaw	7/16"	2	82-9540	84-9540	25
25 AMP	Standard Jaw	3/4"	2	82-9543	84-9543	25
50 AMP	Standard Jaw	1"	2	82-9544	84-9544	25

ALLIGATOR CLIPS & TEST LEADS



- Jaws accommodate up to 5/16"

DESCRIPTION	INSULATED	COLOR	PART #	PACK
Test Lead, 10', 18 GA	Yes	Red	84-9615	1
Test Lead, 10', 18 GA	Yes	Black	84-9616	1
Test Lead, 2 1/2', 16 GA	Yes	Red & Black	84-9613	1 Pair
Alligator Clip	No	Red	84-5005	1
Alligator Clip	No	Black	84-5004	1

ALLIGATOR CLIP BOOTS



DESCRIPTION	COLOR	RETAIL PACK	PACK SIZE	BULK PACK	PACK
Protective boots for Alligator Clips	Red & Black	82-9614	1 Pair	84-9614	5 Pair

BOOSTER CABLES



- Cable construction of 100% fine-stranded copper conductors
- Tangle-free design remains flexible even in cold weather
- 1 & 2 Gauge includes Thermoplastic Elastomer (TPE) jacketing
- 4, 6 & 8 Gauge includes Polyvinyl chloride (PVC) jacketing
- All booster cables are supplied in a retail storage box
- Additional gauges and lengths available as special order
- 175A plug in ends for 84-9279 and 84-9496

LIGHT DUTY

GAUGE	JAW TYPE	JAW RATING	LENGTH	CABLE COLOR	JACKET	PART #
8 GA	Standard Jaws	200 AMP	12'	Yellow & Black	PVC	84-9550

MEDIUM DUTY – COMMERCIAL GRADE

GAUGE	JAW TYPE	JAW RATING	LENGTH	CABLE COLOR	JACKET	PART #
6 GA	Standard Jaws	500 AMP	16'	Orange & Black	PVC	84-9472
4 GA	Standard Jaws	500 AMP	16'	White & Black	PVC	84-9331
4 GA	Standard Jaws	500 AMP	20'	White & Black	PVC	84-9276
4 GA	Parrot Jaws	600 AMP	20'	White & Black	PVC	84-9277

MEDIUM DUTY, PLUG IN CONNECTOR – COMMERCIAL GRADE

GAUGE	JAW TYPE	JAW RATING	LENGTH	CABLE COLOR	JACKET	PART #
4 GA	Std. Jaws & Plug-In	500 AMP	20'	White & Black	PVC	84-9279
4 GA	Plug-In w/ 3/8" lugs	175 AMP	5'	White & Black	PVC	84-9496

HEAVY DUTY – INDUSTRIAL GRADE

GAUGE	JAW TYPE	JAW RATING	LENGTH	CABLE COLOR	JACKET	PART #
2 GA	Parrot Jaws	600 AMP	20'	Red & Black	TPE	84-9278
1 GA	Standard Jaws	500 AMP	12'	Grey & Black	TPE	84-9484
1 GA	Standard Jaws	500 AMP	16'	Red & Black	TPE	84-9477
1 GA	Standard Jaws	500 AMP	20'	Grey & Black	TPE	84-9476
1 GA	Parrot Jaws	900 AMP	25'	Grey & Black	TPE	84-9567

BOOSTER CABLE



TWIN CONDUCTOR

- Make up your own booster cables
- Combine with heavy duty clamps for superior charging power
- Can be used with SB type connectors for plug in convenience
- Ideal for tarps system (dump truck / dump trailer)
- Insulation stays flexible in cold weather; bonded cable resists tangling
- 100% fine-stranded copper meets SAE J1127 specifications
- Temperature rated to -40°F (-40°C); rated @ 60V or less

GAUGE	OUTSIDE DIAMETER	COLOR	LENGTH	PART #
8 GA	.320" x .700"	Black & Yellow	1,500'	82-5759-1500
6 GA	.360" x .780"	Black & Orange	100'	82-5760
6 GA	.360" x .780"	Black & Orange	1,200'	82-5760-1200
4 GA	.410" x .880"	Black & White	100'	82-5761
4 GA	.410" x .880"	Black & White	500'	82-5761-500
2 GA	.450" x .960"	Black & Red	100'	82-5762

LIFT GATE – CHARGING PLUGS & SOCKETS

- Designed for lift gate applications and as an alternative power source
- Solid brass pin terminals for best conductivity
- 2, 1/2" mounting holes; stainless steel spring
- Terminals accepts 4 gauge cable
- 200 AMP heavy die-cast construction

SOCKET

PART #	SOCKET #	DESCRIPTION	MATERIAL
82-1041	2	Socket – Dual Pole	Zinc Die-Cast
82-0851	1	Socket – Single Pole	Zinc Die-Cast
82-2144		Socket Boot	Rubber

PLUG

PART #	PLUG #	DESCRIPTION	MATERIAL
82-1042	2	Plug & Guard Spring – Dual Pole	Zinc Die-Cast
82-0852	1	Plug & Guard Spring – Single Pole	Zinc Die-Cast

PLUG & SOCKET COMBO

PART #	PLUG/SOCKET#	DESCRIPTION	MATERIAL
82-0950	1	Plug & Socket – Single Pole	Zinc Die-Cast



VERTICAL PIN

- Designed for dump truck, tarp and grain trailer applications; also alternative power source
- Solid brass pin terminals for best conductivity
- 2, 1/2" mounting holes; stainless steel spring
- Terminals accepts 4 gauge cable(s)
- 200 AMP heavy die-cast construction
- Vertical pin plug/socket = set screw termination

SOCKET

PART #	SOCKET #	DESCRIPTION	MATERIAL
82-1041V	2	Socket – Dual Pole	Zinc Die-Cast
82-2144		Socket Boot	Rubber

PLUG

PART #	PLUG #	DESCRIPTION	MATERIAL
82-1042V	2	Plug & Guard Spring – Dual Pole	Zinc Die-Cast

DUMP TRUCK & TARP TRAILER PLUGS & SOCKETS



MOLDED BATTERY HARNESSES

"BEST"



- 100% fine stranded copper conductor
- 2/0 GA, PVC jacketed starter cable
- Meets SAE J1127 specifications
- Designed to connect 2, 3 or 4 batteries
- Red and Black (+/-) option for easy polarity identification
- Protective caps protect contacts and prevent corrosion
- Precision molded provide a maintenance free seal

CENTRE TO CENTRE DIMENSION	POLARITY	PACK SIZE	PART #
7"	Negative	1	84-9582
7"	Positive	1	84-9583
14"	Negative	1	84-9584
14"	Positive	1	84-9585
21"	Negative	1	84-9586
21"	Positive	1	84-9587

QUICKLINK® STUD BATTERY HARNESSES

"BETTER"



- 100% fine stranded copper conductor
- 2/0 GA, welding cable provides extreme flexibility in colder temperatures
- Includes high-end locking, anti-rotational lug ends to ensure a tight fit and a superior connection
- Ideal for truck, farm, construction and automotive applications

CENTRE TO CENTRE DIMENSION	POLARITY	TYPICAL BATTERY LAYOUT	PACK SIZE	PART #
8 1/2"	Negative	Side-By-Side	1	84-9304
8 1/2"	Positive	Side-By-Side	1	84-9305
12"	Negative	Side-By-Side	1	84-9420
12"	Positive	Side-By-Side	1	84-9421
17"	Negative	End-To-End	1	84-9306
17"	Positive	End-To-End	1	84-9307

TIN PLATED STUD BATTERY HARNESSES

"GOOD"



- 100% fine stranded copper conductor
- 2/0 GA, welding cable provides extreme flexibility in colder temperatures
- Tin plated copper tube lug connections

CENTRE TO CENTRE DIMENSION	POLARITY	TYPICAL BATTERY LAYOUT	PACK SIZE	PART #
8 1/2"	Negative	Side-by-Side	1	84-9690
8 1/2"	Positive	Side-by-Side	1	84-9691
12"	Negative	Side-by-Side	1	84-9692
12"	Positive	Side-by-Side	1	84-9693
17"	Negative	End-to-End	1	84-9694
17"	Positive	End-to-End	1	84-9695

STUD BATTERIES – LUG TO LUG – BATTERY TO GROUND OR STARTER

CENTRE TO CENTRE DIMENSION	DESCRIPTION	GAUGE	PACK SIZE	PART #
10"	Lug to Lug, 3/8"- 3/8"	2/0 GA	1	84-9467
15"	Lug to Lug, 3/8"- 3/8"	2/0 GA	1	84-9470
20"	Lug to Lug, 3/8"- 3/8"	2/0 GA	1	84-9473



TOP POST-TO-POWER TAKE OFF POST

CENTRE TO CENTRE DIMENSION	POLARITY	GAUGE	PACK SIZE	PART #
13 5/8"	Negative	2/0 GA	1	84-9274
13 5/8"	Positive	2/0 GA	1	84-9275



BATTERY JUMPERS

- Designed for connection of 2 batteries to achieve additional voltage
- Premium quality synthetic rubber insulated copper welding cable enables easy routing & cold weather flexibility

CENTRE TO CENTRE DIMENSION	DESCRIPTION	GAUGE	PACK SIZE	PART #
12"	Offset	1 GA	1	84-9402
8"	Offset	1 GA	1	84-9401
8"	Offset	2/0 GA	1	84-9403



SOLDER SLUGS AND FLUX

- Pre-measured solder slugs for quick and easy battery cable soldering
- Improves your electrical connection by filling in any contact irregularities
- Color coded to industry standards, gauges 6 through 4/0
- Melting temperature rating 182°C (361°F)

CABLE GAUGE	COLOR CODE	PACK SIZE	PART #
6	Grey	25	84-9600
4	Grey	25	84-9601
2	Green	25	84-9602
1	Pink	25	84-9603
1/0	Black	25	84-9604
2/0	Orange	25	84-9605
3/0	Purple	25	84-9606
4/0	Yellow	25	84-9607
Solder Flux	Clear	2oz.	84-9608




Visit page 169 for more information on our 48-piece Battery Terminal Solder Slug Kit

READY-TO-INSTALL BATTERY CABLES


TOP POST CABLES



- Meet or exceed SAE specifications; ideal for OEM replacement
- 100% fine stranded copper wire with black or red PVC insulation
- Tinning of copper wire before casting ensures perfect bond between the wire and connector
- Antimonial lead connectors resist corrosion; die-cast process seals copper wires from acid fumes and corrosive salts
- Universal polarity top post connector
- Excellent for light duty trucks, vans, and recreational vehicles (R.V.)
- Industry standard 3/8" stud hole
- Individually packed



CENTRE TO CENTRE	BLACK 4 GAUGE PART #	BLACK 4 GAUGE W/LEAD	BLACK 1 GAUGE PART #	RED 4 GAUGE PART #	RED 4 GAUGE W/LEAD	RED 1 GAUGE PART #
9"	84-9224					
12"	84-9225	84-9371	84-9241	84-9225-R	84-9371-R	
14"	82-7014					
15"	84-9226	84-9361		84-9226-R	84-9361-R	
16"	84-9227		84-9242			84-9242-R
19"	84-9230		84-9243	84-9230-R		
21"			84-9503			84-9503-R
22"	84-9228			84-9228-R		
24"	84-9231					
25"	82-7025	84-9372		82-7025-R	84-9372-R	
27"	84-9232		84-9244			84-9244-R
30"	84-9233		84-9245	84-9233-R		84-9245-R
32"	84-9234	84-9373		84-9234-R	84-9373-R	
36"	84-9229	84-9365	84-9246	84-9229-R	84-9365-R	84-9571
37"	84-9235					
41"			84-9247			
42"	84-9236			84-9236-R		
48"	84-9237	84-9367	84-9248	84-9237-R	84-9367-R	84-9572
53"	82-7053					
56"		84-9374			84-9374-R	
60"	84-9238			84-9238-R		
65"			84-9510			84-9510-R
72"	82-7072	84-9375			84-9375-R	84-9500-R



SIDE TERMINAL CABLES

READY-TO-INSTALL BATTERY CABLES

- 3/8"- 16 x 13/32" bolts, 1/2" hex head bolt

CENTRE TO CENTRE	PACK SIZE	BLACK 4 GAUGE PART #	RED 4 GAUGE W/LEAD PART #
15"	1	84-9249	84-9249-R
25"	1	84-9250	84-9250-R
35"	1	84-9251	84-9251-R
45"	1	84-9252	84-9252-R
55"	1	84-9253	84-9253-R
65"	1	84-9254	84-9254-R



SWITCH-TO-STARTER CABLES

READY-TO-INSTALL BATTERY CABLES

CENTRE TO CENTRE	PACK SIZE	BLACK 4 GAUGE PART #	BLACK 1 GAUGE PART#	RED 4 GAUGE PART #
10"	1	84-9255	84-9505	84-9255-R
15"	1	84-9256	84-9262	84-9256-R
18"	1	84-9257	84-9382	84-9257-R
19"	1		84-9388	
24"	1	84-9258	84-9506	84-9258-R
25"	1		84-9263	
30"	1	84-9504		84-9504-R
33"	1	84-9259		
35"	1		84-9264	
36"	1	84-9260		84-9260-R
40"	1	84-9261		84-9261-R
46"	1		84-9376	
49"	1	84-9377		84-9377-R



READY-TO-INSTALL BRAIDED GROUND STRAP

- 3/8" Clamp-to-Lug or Lug-to-Lug styles
- Light to medium duty, marine and automotive applications
- Corrosion-resistant tin plating

CENTRE TO CENTRE DIMENSION	DESCRIPTION	PACK SIZE	4 GAUGE PART #	2 GAUGE PART #
9"	Clamp to Lug	1		84-9239
9"	Lug to Lug	1	84-9577	
13"	Clamp to Lug	1		84-9240
13"	Lug to Lug	1	84-9559	
18"	Lug to Lug	1	84-9465	
24"	Clamp to Lug	1		84-9464
24"	Lug to Lug	1	84-9576	



MASTER BATTERY DISCONNECT SWITCH



- Truck, Automotive, Marine, Off-Road and R.V. applications
- For battery circuit (82-2103, 82-2233); for alternator or generator field circuit (82-2155)
- 3/4" & #10-32 copper alloy stud terminals with hex nuts, lock washers included
- Large die cast lever for ease of operation; mounting stem ½" long x ¾" dia.
- Fits panel up to ¼" thick; 10,000 life cycle; 6-36V DC
- Includes faceplate
- Faceplate replacement for 82-2103 (82-2157)

DISCONNECTS ALL CIRCUITRY TO REDUCE THE POSSIBILITY OF THEFT / ACCIDENTAL ELECTRICAL FIRES

PRODUCT RATING
Continuous Rating (Make/Break), Large Studs – 180 AMP @ 6-36V DC; 1,000 AMP – in rush (82-2103)
Continuous Rating (Make/Break), Large Studs – 180 AMP @ 6-36V DC (82-2233)
Intermittent Rating (Carrying), Large Studs – 1800 AMP @12V DC; 1 cycle = 4 seconds on/20 minutes off)

PART #	POSITION	RATED	TYPE	TERMINATION	DIMENSIONS
82-2103	Off/On	12V	S.P.S.T.	2, 3/8" stud terminals ground w/ faceplate	4 3/8" L x 2 5/8" Dia.
82-2233	Off/On	12V	S.P.S.T.	2, ½" stud terminals ground w/ faceplate	4 3/8" L x 2 5/8" Dia.



DESIGNED TO BREAK ALTERNATOR GENERATOR CIRCUIT PRIOR TO BATTERY CIRCUIT DISCONNECT

PRODUCT RATING
Continuous Rating (Make/Break), Large Studs: 180 AMP, Small Studs: 20 AMP @ 6-36V DC
Intermittent Rating (Carrying), Large Studs: 1,000 AMPs (20 sec. "On" – 5 Minutes "Off")

PART #	POSITION	RATED	TYPE	TERMINATION	DIMENSIONS
82-2155	Off/On	12V	D.P.S.T.	4 stud terminal ground	4 1/8" L x 2 5/8"Dia.

BATTERY ISOLATOR SWITCH



- Prevents unauthorized use
- Eliminates battery discharge
- Waterproof body with removable key and protective cap
- Rated at 500 AMPs at 12V
- Stud Size: M10 (1.5mm)

82-2104

- Protects alternator and electrical system from shorts
- Reduces the risks of battery explosion caused by sparks
- High temperature PVC construction rated at 90°C (190°F)
- Color-coded for easy polarity identification
- Conforms to SAE J1128 dielectric specifications, meets USCG requirements

STRAIGHT CLAMP

FITS GAUGES	COLOR	PACK	PART #
1 & 2	Black	5	84-9140
1 & 2	Red	5	84-9141
1/0 & 2/0	Black	5	84-9142
1/0 & 2/0	Red	5	84-9143

STRAIGHT CLAMP SNAP ON FEATURE

FITS GAUGES	COLOR	PACK	PART #
6 & 4	Black	5	84-9138
6 & 4	Red	5	84-9139
1 & 2	Black	5	84-9136
1 & 2	Red	5	84-9137

AUTOMOTIVE LUG

FITS GAUGES	COLOR	PACK	PART #
1 & 2	Black	5	84-9150
1 & 2	Red	5	84-9151
1/0 - 2/0	Black	5	84-9152
1/0 - 2/0	Red	5	84-9153

TAB INSULATOR

FITS GAUGES	TERMINAL O.D.	COLOR	PACK	PART #
8-2	0.73"	Red	5	84-9323
8-2	0.73"	Black	5	84-9324
2-2/0	1.03"	Red	5	84-9327
2-2/0	1.03"	Black	5	84-9328
3/0-4/0	1.37"	Red	5	84-9325
3/0-4/0	1.37"	Black	5	84-9326

BATTERY TERMINAL PROTECTORS



BRUTE™ HAMMER CRIMPER



84-9087

- Inexpensive, simple crimping tool
- Use with hammer or vise
- Crimps 8- 4/0 gauge connectors
- Spring loaded pin locks in “up” position for loading connector and cable
- Pin is then released to hold connector securely during crimping
- 6 month limited warranty

CONNECTOR CABLE RANGE	PART #
8-4/0 GA	84-9087

CUB™ CRIMPER



84-9080

- Light-medium duty applications
- Adjustable crimp dies crimp all major lugs, connectors and splices
- Insulated grips
- One year limited warranty

OVERALL LENGTH	CONNECTOR CABLE RANGE	PART #
15"	8-1 GA	84-9080


HEXCRIMP™



84-9082

84-9085

- Medium to heavy duty applications
- Properly crimps copper, tin-plated, die cast and Magna lug splices and connectors
- Adjustable dies can crimp 8 to 250 MCM cable range
- 26" long with insulated handles for comfort
- 2 year limited warranty
- Made in North America



PART #	DESCRIPTION
84-9082	Hand Held
84-9085	Bench Mount
84-9084	Replacement Dies & Hardware (for 84-9082)

ROTARY CABLE SLITTER/STRIPPER TOOL

HEAVY DUTY



83-6515

- Slits & strips round battery & trailer cables
- Can strip 8 to 4/0 GA wire, battery and trailer cables
- Self-adjusting cutting depth
- Makes a clean strip without damaging wire strands
- Blade swivels for longitudinal/spiral cuts
- Ergonomic design



PART #	DESCRIPTION
83-6515	Heavy Duty Rotary Cable Slitter / Stripper Tool

9" CABLE CUTTER

- Cuts cable up to 2/0 gauge
- Fits any toolbox
- Forged steel with insulated grips
- 6 month limited warranty



84-9088

OVERALL LENGTH	CONNECTOR CABLE RANGE	PART #
9"	up to 2/0 GA	84-9088

22" CABLE CUTTER

- Cuts cables 22 GA to 250 mcm (6/0 GA)
- 22" handle for easy cutting
- 1075 Carbon steel blade, hardened for long life; can be sharpened
- 6 month limited warranty
- Made in North America

PART #	DESCRIPTION
84-9089	Hand Held
84-9090	Bench Mount



84-9089



84-9090

FIELD REPAIR KIT WITH HEXCRIMP™

- Contains components (except cable) needed to build or repair 2/0 battery cables
- The carrying case is made of steel, finished in corrosion resistant baked grey enamel

PART #	DESCRIPTION	RE-ORDER PART #
84-9290	Field Repair Kit- Includes:	
	1 HexCrimp™ Tool – 8 gauge - 250 mcm	84-9082
	1 9" Cutter – up to 2/0 cables	84-9088
	5 2/0 straight clamp – positive	84-9059
	5 2/0 straight clamp – negative	84-9058
	2 2/0 flag clamp – positive	84-9098
	2 2/0 flag clamp – negative	84-9097
	5 2/0 starter/ground lug – 3/8" hole	84-9110
	5 2/0 starter/ground lug – 1/2" hole	84-9111
	5 Terminal Protector straight – black	84-9142
	5 Terminal Protector straight – red	84-9143
	2 Terminal Protector flag – black	84-9144
	2 Terminal Protector flag – red	84-9145
	2 3/4" Heat shrink tubing 6" – Black 3:1	84-4003
	2 3/4" Heat shrink tubing 6" – Red 3:1	84-6103



84-9290

BATTERY BOXES

BATTERY BOXES FOR 6-VOLT, GC2 AND 4D BATTERIES

Growing demand for more power and deeper cycles has led to wider use of GC2 and 4D batteries in recreational vehicles, boats, and small alternative energy applications. Our Battery Box line allows you to set up the configuration that works best for your installation, whether it is single batteries, or dual batteries side by side or end-to-end.

Larger boxes use thumb screws to retain the covers and have foot pads to allow mounting options in low clearance environments like sailboats and campers.



Construction



Marine



RV

SINGLE & DUAL

- Rugged heavy wall polyethylene construction
 - Impervious to acid, gasoline, oil and solvents
 - Flame retardant
 - Cold temperature impact resistant to -30°F (-34°C)
 - Heat stable -30°F to +200°F (-34°C to +93°C)
 - Single box holds ONE 6-Volt battery
- Dual box holds TWO 6-Volt batteries
 - Depending on your space requirements, use two boxes side-by-side, end-to-end or use a dual box
 - Dual box is molded in black

PART #	GROUP SIZE	TYPICAL BATTERIES IN ARRAY	BOX COLOR	INSIDE DIMENSIONS			OUTSIDE DIMENSIONS			MOUNTING BRACKET
				LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT	
84-9660	6-Volt/GC2	1	Black	10-3/4" (27.3 cm)	7-1/4" (18.4 cm)	12-1/4" (31.1 cm)	13-1/2" (34.3 cm)	9-1/4" (23.5 cm)	13" (33 cm)	—
SIDE BY SIDE										
84-9661	Dual 6-Volt/GC2	2	Black	15" (38.1 cm)	11" (27.9 cm)	13" (33 cm)	20" (50.8 cm)	14-1/2" (36.8 cm)	14-1/2" (36.8 cm)	(2 Included)
END TO END										
84-9425	Dual 6-Volt Single 4D GC2	2	Black	21-5/8" (55 cm)	9-1/2" (24.1 cm)	11-1/2" (29.2 cm)	26-3/4" (68 cm)	14" (35.6 cm)	12-3/4" (32.4 cm)	(2 Included)



Single 6-Volt
84-9660



Dual 6-Volt side-by-side, black
84-9661



Dual 6-Volt end-to-end
84-9425

BATTERY BOXES

COMMERCIAL MARINE, RECREATIONAL VEHICLES, CONSTRUCTION MACHINERY, LARGER OFF-GRID, BACKUP POWER SYSTEMS

Big power requirements mean big batteries and big battery boxes. Our commercial boxes are used for 4D, 8D and other large arrays. These boxes traditionally have secured batteries on working boats and heavy construction equipment and now are found in larger residential and small commercial off-grid power systems.

With mounting options to accommodate a variety of installations, venting options and cable routing options including conduit mounting, these battery boxes have been carefully engineered to solve your battery security issues.



Construction



Heavy Duty



Marine

COMMERCIAL BOXES

- Rugged, durable, heavy wall construction
 - Impervious to acid, gasoline, oil and solvents
 - Heat stable to +200°F (+93°C)
 - Cold temperature impact resistant to -30°F (-34°C)
 - Flame retardant
 - UV stabilized (Rating 6)
 - 3-4 way cable channels molded into design
 - Large entry ports for heavy duty cable
- Cover held firmly with convenient thumb screws, no special tools required
 - Cover can be locked for protection and tamper resistance
 - Vent holes in cover allow gases to escape, preventing dangerous hydrogen build up
 - Accommodates variety of mounting options

PART #	TYPICAL GROUP SIZE	TYPICAL BATTERIES IN ARRAY	COLOR	INSIDE DIMENSIONS			OUTSIDE DIMENSIONS			MOUNTING BRACKET
				LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT	
84-9425	4D	1	Black	21-5/8" (55 cm)	9-1/2" (24.1 cm)	11-1/2" (29.2 cm)	26-3/4" (68 cm)	14" (35.6 cm)	12-3/4" (32.4 cm)	(2 Included)
84-9426	8D High	1	Black	21-5/8" (55 cm)	11-3/4" (29.8 cm)	13" (33 cm)	26-3/4" (68 cm)	16-1/2" (41.9 cm)	14" (35.6 cm)	(2 Included)
84-9664	Dual 8D End-to-End	2	Black	42-1/2" (108 cm)	12" (30.5 cm)	10-3/4" (27.3 cm)	49-1/2" (125.7 cm)	18-1/4" (46.4 cm)	12-1/4" (31.1 cm)	(Optional)
84-9665	Dual 8D Side-by-Side	2	Black	21-1/2" (54.6 cm)	23-1/2" (59.7 cm)	10-3/4" (27.3 cm)	27" (68.6 cm)	29" (73.7 cm)	12-1/4" (31.1 cm)	(2 Included)



4D
84-9425



8D high
84-9426



Dual 8D end-to-end
84-9664



Dual 8D side-by-side
84-9665

BATTERY BOXES



AUTO, LIGHT TRUCK, MARINE & RV



FITS ALL BATTERIES

- Fits all traditional battery group sizes
- Fits all new orbital or spiral celled, deep cycle, high performance batteries

NEW COVER

- Easy-on and easy-off
- Safe and secure
- Convenient, fast, durable

NEW MOUNTING HOLES IN HANDLE

- Use hold-down holes molded in to reinforced handles
- Use J-hooks, L-hooks, threaded rod or lag bolts
- Remove the lid while keeping the box secure

NEW TOUGHER MATERIAL

- Impact resistant to -30°F (-34°C)
- Heat stable to +200°F (+93°C)
- Meets U.S. Coast Guard Regulations 183.420 & ABYCE-10.7
- Impervious to acid, gasoline, oil and solvents
- Will not rust, UV protected

PART #	GROUP SIZE	INSIDE DIMENSIONS			OUTSIDE DIMENSIONS		
		LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT
84-9662	U1 Black	8" (20.3 cm)	5-1/4" (13.3 cm)	7-15/16" (20.1 cm)	10-3/4" (27.9 cm)	7-1/2" (19.1 cm)	8-1/2" (21.6 cm)
84-9424	24 Black	10-1/2" (26.7 cm)	7" (17.8 cm)	9-3/4" (24.8 cm)	13-1/2" (34.3 cm)	9-1/4" (23.5 cm)	10-1/4" (26 cm)
84-9427	27 Black	12-3/4" (32.4 cm)	7-1/4" (18.4 cm)	10" (25.4 cm)	16-1/8" (40.9 cm)	9-5/8" (24.4 cm)	10-7/8" (27.6 cm)
84-9423	Adjustable 24, 27, 31 Black	14-1/2" (36.8 cm)	7-1/4" (18.4 cm)	10-3/8" (26.3 cm)	17-3/4" (45.1 cm)	10-1/4" (26 cm)	10-7/8" (27.6 cm)
84-9422	Dual 27, 31	14-1/2" (36.8 cm)	15-1/2" (39.3 cm)	10-1/4" (26.0 cm)	19-1/4" (48.8 cm)	20" (50.8 cm)	11-7/8" (30.1 cm)

- New telescoping design
- Fiberglass-reinforced polypropylene is rust and corrosion-proof
- Non-conductive – eliminates hold-down as source of shorts
- Car, truck, bus, off-road, marine and recreational vehicle applications

PART #	DESCRIPTION	MIN/MAX EXTENSION	PACK SIZE
84-9288	Offset hold-down	5 1/2" - 9"	1
84-9320	Flush hold-down	8 5/8" - 14 3/4"	1
84-9480	Adjustable mount crossbar	6 7/8"	1

BATTERY HOLD-DOWNS



- Long thread accommodates all crossbar/frame designs including QuickHold® products
- "L" and "J" style bend eliminates any need to shift or remove battery
- Sold as pair; hardware included
- Use with battery tray below
- 4", ¼"-20 thread

PART #	DESCRIPTION	LENGTH	PACK
84-9287	J bolt	8"	Pair
84-9286	J bolt	10"	Pair
84-9685	J bolt	12"	Pair
84-9285	L bolt	10"	Pair

HOLD DOWN SETS – L & J STYLE



BATTERY TRAYS

- Drain slots prevent fluid accumulation
- Ideal replacement for OEM-style trays
- Vinyl coated steel resists corrosion & cold climate cracking
- Also fits group 1, 2, 17, 22, 23, 42, 54, 55, 56, 72 & 74 batteries (84-9481)

PART #	DESCRIPTION	PACK
84-9481	11" for Group 24 size batteries	1
84-9629	GM base mount hold down	1

BATTERY TRAYS



BATTERY CABLE – TYPE SGR



82-5703



82-6703

- Ideal for use as an interconnection between batteries and a starter or as a ground in a vehicle
- 100% Copper Cable; made in North America
- Ethylene Propylene Diene Monomer Rubber (EPDM) Insulation
- Provides better flexibility than standard PVC starter cable
- Jacket rated at -40°C (-40°F) to 105°C (221°F)
- Meets all SAE code J1127 specifications; rated @ 60V
- All battery cable is spooled



6 GAUGE

COLOR	25'	50'	100'
Black	82-5722	82-5725	82-5726
Red	82-6722	82-6725	82-6726

4 GAUGE

COLOR	25'	50'	100'
Black	82-5714	82-5713	82-5712
Red	82-6717	82-6713	82-6712

2 GAUGE

COLOR	25'	50'	100'
Black	82-5711	82-5710	82-5709
Red	82-6718	82-6710	82-6709

1 GAUGE

COLOR	25'	50'	100'
Black	82-5708	82-5707	82-5706
Red	82-6719	82-6707	82-6706

1/0 GAUGE

COLOR	25'	50'	100'
Black	82-5705	82-5704	82-5703
Red	82-6720	82-6704	82-6703

2/0 GAUGE

COLOR	25'	50'	100'
Black	82-5702	82-5701	82-5700
Red	82-6721	82-6701	82-6700

3/0 GAUGE

COLOR	25'	50'	100'
Black	82-5723	82-5715	82-5733
Red	82-6723	82-6715	82-6733

4/0 GAUGE

COLOR	25'	50'	100'
Black	82-5743	82-5716	82-5753
Red	82-6743	82-6716	82-6753



EZ-FIND

FOR COMPLETE
TECHNICAL SPECS
VISIT OUR WEBSITE

WELDING CABLE



- Ideal for use as an interconnection between batteries and a starter or as a ground in a vehicle
- Abrasion, salt and chemical resistant; good flame resistance
- Fine stranded copper conductor; made in North America
- Provides better flexibility than standard PVC starter cable
- Jacket rated at -50°C (-58°F) to 105°C (221°F) – Rated @ 600V
- Meets all SAE J1127 specifications
- All welding cable is spooled



6 GAUGE

COLOR	25'	100'
Black	82-5732	82-5734
Red	82-6732	82-6734

4 GAUGE

COLOR	25'	100'
Black	82-5724	82-5735
Red	82-6727	82-6735

2 GAUGE

COLOR	25'	100'
Black	82-5721	82-5736
Red	82-6728	82-6736

1 GAUGE

COLOR	25'	100'
Black	82-5737	82-5738
Red	82-6746	82-6738

1/0 GAUGE

COLOR	25'	100'
Black	82-5739	82-5740
Red	82-6739	82-6740

2/0 GAUGE

COLOR	25'	100'
Black	82-5730	82-5731
Red	82-6730	82-6731

3/0 GAUGE

COLOR	25'	100'
Black	82-5741	82-5742
Red	82-6741	82-6742

4/0 GAUGE

COLOR	25'	100'
Black	82-5744	82-5745
Red	82-6744	82-6745



82-5730



82-6730



EZ-FIND

FOR COMPLETE
TECHNICAL SPECS
VISIT OUR WEBSITE

10

TOOLS & KITS

OUTILS ET TROUSSES

HERRAMIENTAS Y JUEGOS

- 164 Heat Shrink Terminal Assortment Kits
- 165 Nylon & PVC Terminal Assortment Kits
- 166 Deutsch & Weather Pack Assortment Kits
- 167 Assorted Repair Kits
- 168 Heat Shrink Tubing Assortment Kits
- 170 Copper Lug Assortment Kits
- 171 Storage Trays
- 172 Crimping, Cutting and Installations Tools

GROTE'S LINE OF TOOLS & KITS ALLOW YOU TO CHOOSE EXACTLY THE TOOLS AND THE TYPES OF PRODUCTS YOU NEED TO GET THE JOB DONE RIGHT FOR YOUR SPECIFIC NEED & APPLICATION. GROTE'S KITS OFFER A SELECTION OF THE MOST POPULAR, IN-DEMAND PRODUCTS IN COMPACT, RUGGED CASES TO KEEP ALL THE PARTS TOGETHER AND EASY TO ACCESS.

CHOOSE THE RIGHT PRODUCT AND THE RIGHT TOOLS TO GET THE BEST RESULTS!



CRIMP, SOLDER & SEAL TERMINAL & CONNECTOR

22-10 GAUGE ASSORTMENT KIT



83-6542

- Includes the most popular heat shrink crimp, solder and seal terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6542	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects (10) Female Disconnects (10)	120

HEAT SHRINK & SOLDER TERMINAL & CONNECTOR

22-10 GAUGE ASSORTMENT KIT



83-6539

- Includes the most popular heat shrink solder and seal terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-18, 16-14 and 12-10 gauges
- 12 compartment resealable plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6539	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects .250" (10) Female Disconnects .250" (10)	120

HEAT SHRINKABLE TERMINAL & CONNECTORS

22-10 GAUGE ASSORTMENT KIT



83-6556

83-6503

- Includes the most popular polyolefin heat shrinkable crimp splices and terminals; 22-18, 16-14 and 12-10 gauges
- Includes rings, butts, spades and quick disconnects
- 12-compartment plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6503	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects (10) Female Disconnects (10)	120

PART #	KIT CONTENTS	QUANTITY
83-6556	Butt Connectors (30) Ring Terminals (44) Male Disconnects (5) Female Disconnects (6) <i>* Includes Hang Tab</i>	85

22-10 GAUGE ASSORTMENT KITS

- Includes the most popular Nylon terminals and connectors
- Includes rings, butts, spades and quick disconnects
- 22-16, 16-14 and 12-10 gauges
- 12-compartment resealable plastic box with re-order chart on the inside cover

PART #	KIT CONTENTS	QUANTITY
83-6538	Butt Connectors (40) Ring Terminals (50) Spade Terminals (10) Male Disconnects .250" (10) Female Disconnects .250" (10)	120

PART #	KIT CONTENTS	QUANTITY
83-6555	Butt Connectors (24) Ring Terminals (26) Male Disconnects .250" (10) Female Disconnects .250" (10) <i>* Includes Hang Tab</i>	70

22-10 GAUGE ASSORTMENT KITS

- Kit contains 650 of the most popular automotive electrical terminals and accessories
- Assorted gauges (22-16, 16-14, 12-10) & stud sizes (#6 - 1/4")
- Matrix chart on inside lid describes piece parts, provides illustrations and details individual re-order part numbers

PART #	KIT CONTENTS	QUANTITY
83-6540	Butt Connectors (115) Ring Terminals (200) Spade Terminals (40) Male Disconnects .250" (80) Female Disconnects .250" (90) Bullet Connectors .157" (30) Bullet Receptacles .157" (30) Tap Connectors (15) Cable Ties – Black (50) Wire Terminal Crimper (1)	650

PVC

PART #	KIT CONTENTS	QUANTITY
83-6554	Butt Connectors (34) Ring Terminals (51) Male Disconnects .250" (6) Female Disconnects .250" (8) <i>* Includes Hang Tab</i>	99

NYLON TERMINAL & CONNECTOR



83-6538

83-6555

VINYL & NYLON TERMINAL & CONNECTOR



83-6540

83-6554

DEUTSCH TERMINAL & CONNECTOR

ASSORTMENT KIT



83-6549

- Perfect assortment kit for any repair or service technician or installer
- Includes 98 pieces of the most popular Deutsch, DT Series terminals and housings
- 20-16, 18-16 and 16-14 gauge terminals; 2, 3, 4, 6 and 8 way plugs/receptacles & wedge locks
- Crimping and removal tools also available
- 12 compartment resealable plastic box with re-order chart on the inside cover

83-6549

TERMINAL & CONNECTOR REPAIR KIT

WEATHER PACK



83-6536

- Kit Includes 250 assorted pieces; assorted 22-14 GA terminals; 1, 2 and 4 cavity nylon housings and 22-18 & 16-14 GA cable seals
- Sturdy plastic container keeps all the connectors in one convenient location
- Easy to use reference re-order chart included
- Use Grote OEM crimping tool 84-9449 and extractor tool 84-9450 for superior connection and repair. Tools sold separately

83-6536

TERMINAL & CONNECTOR INSTALLATION & REPAIR KIT

WEATHER PACK



83-6546

- 185 male and female weather pack OEM terminals, cable seals and plugs
- Includes an OEM ratchet style crimping tool and extractor tool for a complete repair and installation kit
- Sturdy plastic container keeps connectors in one convenient location
- Easy to use reference re-order chart included

83-6546

22-10 GAUGE

AUTO ELECTRIC REPAIR KIT



83-6550

- Kit includes 208 electrical tools & components, voltage tester and test leads, assorted ring, butt, spade and quick disconnect wire terminals, terminal crimping tool, primary wire, cable ties, shrink tubing and nylon wire clamps, glass & ATO emergency fuses and a fuse puller, battery brush and miniature screwdrivers

83-6550

22-10 GAUGE

ALL PURPOSE TERMINAL KIT (83-6530)



83-6530

- 37 pieces; 2 miniature screwdrivers, electrical pliers & circuit tester, Assorted wire terminals and a heavy duty terminal crimping tool

PART #	KIT CONTENTS	QUANTITY
83-2102	22-16 Ring #6 (6)	37
83-2104	22-16 Ring #10 (4)	
83-2303	16-14 Ring #6 (6)	
83-2304	16-14 Ring #10 (2)	
83-2504	12-10 Ring #10 (1)	
83-2180	22-16 Butt Splice (2)	
83-2380	16-14 Butt Splice (1)	
83-2391	16-14 Male disconnect .250 (2)	
83-2387	16-14 Female disconnect .250 (2)	
83-2334	16-14 Spade #8 (4)	
83-6510	4-way crimp tool: 8 - 1/2" (1)	

Kit also includes 6" long nose pliers, Voltage tester, Slotted screw driver (-), Phillips screw driver (+), Electrical tape UL 30'

22-10 GAUGE

ECONOMY TERMINAL KIT (83-6520)



83-6520

PART #	KIT CONTENTS	QUANTITY
84-2180	22-16 Butt Connectors (5)	51
84-2380	16-14 Butt Connectors (5)	
84-2580	12-10 Butt Connectors (5)	
84-2303	16-14 Ring Terminals (5)	
84-2104	22-16 Ring Terminals (5)	
84-2304	16-14 Ring Terminals (5)	
84-2191	22-16 Male Quick Disconnect (5)	
84-2391	16-14 Male Quick Disconnect (5)	
84-2187	22-16 Female Quick Disconnect (5)	
84-2387	16-14 Female Quick Disconnect (5)	
83-6510	Wire Terminal Crimper (1)	

HEAT SHRINK TUBING KIT

DUAL WALL – ADHESIVE LINED “HOT MELT”



83-6535

4:1 SHRINK RATIO

- 40, 6" black Dual Wall heat shrink pieces
- 6 compartment resealable box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6535	84-5006	1/16"- 3/16"	12
	84-5007	3/16"- 1/4"	12
	84-5008	1/4"- 3/8"	10
	84-5009	1/2"- 5/8"	6

HEAT SHRINK TUBING KIT

DUAL WALL – FLEXIBLE, ADHESIVE LINED



83-6537

3:1 SHRINK RATIO

- 50, 6" black flexible Dual Wall heat shrink pieces
- 6 compartment resealable box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6537	84-4015	1/8"	12
	84-4016	3/16"	12
	84-4017	1/4"	12
	84-4018	3/8"	6
	84-4019	1/2"	6
	84-4020	3/4"	2

HEAT SHRINKABLE TUBING KIT

DUAL WALL, RED/BLACK



83-6505

3:1 SHRINK RATIO

- Combination of 50, 6" Red & Black Dual Wall heat shrink pieces
- 6-compartment resealable plastic box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY	COLOR
83-6505	84-4006	1/8"	6	Black
	84-6106	1/8"	6	Red
	84-4005	3/16"	6	Black
	84-6105	3/16"	6	Red
	84-4000	1/4"	6	Black
	84-6100	1/4"	6	Red
	84-4001	3/8"	3	Black
	84-6101	3/8"	3	Red
	84-4002	1/2"	3	Black
	84-6107	1/2"	3	Red
	84-4003	3/4"	1	Black
	84-6103	3/4"	1	Red

DUAL WALL, BLACK

3:1 SHRINK RATIO

- 50, 6" Black Dual Wall heat shrink pieces
- 6-compartment resealable plastic box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6502	84-4006	1/8"	12
	84-4005	3/16"	12
	84-4000	1/4"	12
	84-4001	3/8"	6
	84-4002	1/2"	6
	84-4003	3/4"	2

HEAT SHRINKABLE TUBING KIT



83-6502

SINGLE WALL, BLACK

2:1 SHRINK RATIO

- 50, 6", Black Single Wall heat shrink pieces
- 6-compartment resealable plastic box
- Re-order chart on inside cover

PART #	FEATURES	SIZE	QUANTITY
83-6545	84-5010	1/8"	12
	84-5011	3/16"	12
	84-5012	1/4"	8
	84-5013	3/8"	6
	84-5014	1/2"	6
	84-5015	3/4"	6

HEAT SHRINKABLE TUBING KIT



83-6545

SOLDER SLUGS AND CONNECTOR KIT

- Kit contains 48 pieces of heat shrink tubing, solder slugs and flux
- Ideal kit for any repair garage, mechanic or installer
- Provide superior protection from corrosion
- Improves electrical connection by filling in any contact irregularities
- Color coded to industry standards
- Solder slugs melting temperature rating 182°C (361°F)

PART #	KIT CONTENTS	QUANTITY
83-6532	Solder Slug 4 GA – Gray (5)	48
	Solder Slug 2 GA – Green (5)	
	Solder Slug 1 GA – Pink (5)	
	Solder Slug 1/0 GA – Black (5)	
	Solder Slug 2/0 GA – Orange (5)	
	Solder Slug 3/0 GA – Purple (5)	
	Solder Slug 4/0 GA – Yellow (5)	
	ELA-Flux, 2 oz. Bottle (1)	
	3/4" Dual Wall Shrink Tubing 1.5", Black (2)	
	3/4" Dual Wall Shrink Tubing 1.5", Red (2)	
	1" Dual Wall Shrink Tubing 1.5", Black (2)	
	1" Dual Wall Shrink Tubing 1.5", Red (2)	
	1 1/2" Dual Wall Shrink Tubing 1.5", Black (2)	
	1 1/2" Dual Wall Shrink Tubing 1.5", Red (2)	



83-6532

TIN PLATED COPPER TUBE LUG ASSORTMENT KIT

8-3/0 GAUGE



83-6544

- Includes 76 of the most popular automotive and heavy-duty copper tube lugs
- Heavy tin plated for superior conductivity and resistance to corrosion
- Can be crimped or soldered
- Flared barrel for easy installation of cables
- 12 compartment resealable box
- Re-order chart on inside cover

83-6544 8 – 3/0 GA Copper Tube Lugs

COPPER TUBE LUG ASSORTMENT KIT

8-3/0 GAUGE



83-6543

- Includes 76 of the most popular automotive and heavy-duty copper tube lugs
- Provides superior conductivity
- Can be crimped or soldered
- Flared barrel for easy installation of cables
- 12 compartment resealable box
- Re-order chart on inside cover

83-6543 8 – 3/0 GA Copper Tube Lugs

REPAIR AND INSTALLATION KITS

ELECTRICAL CONNECTION, WIRE AND CABLE



83-6552

- Comes with quality cutting, stripping and crimping tools needed to properly repair or install electrical connections
- Electrical repair kit comes in a sturdy metal steel case with a comfort fit foam insert to protect your tools
- Economical and easy access tool kit is perfect for emergency repair and can be stored in a tool chest or under the driver seat
- Is a 'must have' for any mechanic, installer or service professional
- Use the right tool for the right job!

ELECTRICAL TERMINATION AND REPAIR KIT 83-6552

KIT INCLUDES

- 83-6508** Flameless Heat Gun (OEM approved)
- 83-6509** Cable Tie Tension and Cutter Tool, 18-50 lbs
- 83-6515** Heavy Duty Rotary Cable Stripper/Slitter
- 83-6512** Heavy Duty Wire Stripper, Cutter, 22-10 gauge
- 83-6511** 22-10 Gauge "Ratchet Style" Terminal Crimping Tool

WIRE AND CABLE INSTALLATION AND REPAIR KIT 83-6553

KIT INCLUDES

- 84-9088** 9" Heavy Duty Cable Cutter (up to 2/0 GA)
- 83-6509** Cable Tie Tension and Cutter Tool, 18-50 lbs
- 83-6515** Heavy Duty Rotary Cable Stripper/Slitter
- 83-6512** Heavy Duty Wire Stripper, Cutter, 22-10 gauge
- 83-6511** 22-10 Gauge "Ratchet Style" Terminal Crimping Tool



83-6553

- Streamline your shop inventory with fully customizable fleet/installer trays and insert labels
- Wide range of fast moving electrical connection and accessory products
- Clear and concise product labeling for easy restocking
- Fully customizable insert tray labels to accommodate existing hardware
- 12" (304mm) deep x 3" (76mm) high x 18" (457mm) wide

PART #	DESCRIPTION	PIECES
83-6650	Heat-Shrink Term Fleet Tray Assortment	245
83-6651	Crimp, Solder & Seal Fleet Tray Assortment	130
83-6652	Solder & Seal Fleet Tray Assortment	130
83-6653	Copper Lug Fleet Tray Assortment	145
83-6654	Tin-Plated Copper Lug Fleet Tray Assortment	145
83-6655	Cable Tie Fleet Tray Assortment	525
83-6656	Heat Shrink Tubing Fleet Tray Assortment	88
83-6657	Deutsch Terminal Fleet Tray Assortment	189
83-6658	Insulated Rubber Clamp Fleet Tray Assortment	64
83-6659	Fuse & Circuit Breaker Fleet Tray Assortment	553

FLEET TRAYS



83-6650

83-6653

83-6657



EZ-FIND
SCAN TO VIEW THE FULL
LIBRARY OF FLEET TRAY
OFFERINGS FROM GROTE

- Heavy duty storage tray designed to hold an array of small parts and tools
- 21 compartment large scoop box
- Prime cold rolled steel with a durable gray powder coat finish
- Boxes can be removed and transported to any job site
- Rugged plastic inserts and scoop bottoms fit neatly into steel outer shell boxes
- 12" (304mm) deep x 3" (76mm) high x 18" (457mm) wide; 8 lbs

83-6547

LARGE STORAGE TRAY



83-6547

- Heavy duty storage racks are perfect for any garage or service vehicle
- Accommodates up to 4 large storage trays (83-6660)
- Prime cold rolled steel with a durable gray powder coat finish
- Does not include storage trays (above)
- 83-6548: 15 3/4" deep x 8 1/8" high x 20" wide; 20 lbs
- 83-6660: 15 3/4" deep x 15" high x 20" wide; 30 lbs

PART #	DESCRIPTION
83-6548	Easy Glide Slide Rack, 2 Trays
83-6660	Easy Glide Slide Rack, 4 Trays
83-6661	Base for Large Slide Rack

HEAVY DUTY STORAGE RACKS



83-6548

83-6660

83-6661

HEAT SHRINK TERMINAL CRIMPING TOOL

RATCHET STYLE, 22-8 GAUGE



83-6519

- Ratchet style tool properly crimps Heat Shrink and Crimp Solder & Seal Terminals
- Specially designed die ensures a clean crimp that protects the Heat Shrink jacket from over-crimping
- 22-8 gauge is the largest crimp range industry wide
- Ergonomic design for easy use; a must have for any mechanic, installer or repair professional

83-6519



HEAVY DUTY HEAT SHRINK CRIMPING TOOL

22-10 GAUGE



83-6524

- Crimps heat shrink and crimp solder and seal terminals and connectors 22-10 Gauge
- Ratchet style is easy to use and provides a superior crimp
- Makes a clean crimp without damaging the conductor
- Ergonomic design for comfort
- 10" long

83-6524



HEAVY DUTY NYLON & PVC CRIMPING TOOL

22-10 GAUGE



83-6511

- Crimps 22-10 gauge PVC, Nylon and uninsulated terminals
- Sure grip vinyl handles for safety
- Ratchet style with safety release
- Ergonomic handle for ease of use

83-6511

HEAVY DUTY WIRE STRIPPER, CUTTER & CRIMPING TOOL

26-10 GAUGE



83-6512

- Crimps insulated & non-insulated terminals 22-10 Gauge
- Self-adjusting wire stripper for 26-10 Gauge wire
- Built in cutter
- Makes a clean cut and crimp without damaging the conductor
- Cushion grip for comfort
- Adjustable stopper for a clean strip every time
- 8" long

83-6512

- Economical, ratcheting tools designed to crimp solid barrel or open barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6562	14, 16, 18	Solid Barrel
83-6563	20, 22	Solid Barrel
83-6564	14, 16, 18, 20, 24	Open Barrel (Deutsch + Weather Pack)

- OEM tools designed to crimp solid barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6516	12, 14, 16, 18, 20	Solid Barrel – 4 Indent Crimp

CRIMPING TOOLS – DEUTSCH



83-6562

83-6563

83-6516

83-6564

- Economical tools designed to release both solid and open barrel Deutsch terminals

PART #	WIRE GAUGE	TERMINAL STYLE
83-6565	14, 16	Solid & Open Barrel; Gold Handle
83-6566	16, 18	Solid & Open Barrel; Blue Handle
83-6567*	14, 16, 18, 20, 24	Solid & Open Barrel; Gold, Blue/Red Handles

REMOVAL TOOLS – DEUTSCH



83-6567

83-6565

83-6566

WEATHER PACK & METRI PACK

- Can crimp terminals 24-14 gauge
- Heavy duty steel construction
- Ergonomic design with cushioned grips

PART #	DESCRIPTION
83-6569	For open barrel Weather Pack, Metri Pack 150 & 280 series and Molex terminals
84-9449	For open barrel Weather Pack terminals – ratchet style

OEM OPEN BARREL CRIMPING TOOL



84-9449

83-6569

22-10 GAUGE

- Designed to crimp most terminals used in an automotive, marine or electrical application
- Applies a "W" crimp to 7mm and 8mm straight or 90 degree distributor terminals
- 10" long; Cuts and strips 22-10 gauge wires

83-6518



83-6518

22-10 GAUGE

- 8" long; Cuts and strips primary wire 22-10 gauge sizes
- Crimps insulated and non-insulated terminals
- Sure grip vinyl handles for safety

83-6510

ECONOMY 4-WAY CRIMPING TOOL



83-6510

9" HAND HELD CABLE CUTTER



84-9088

- Cuts cables up to 2/0 Gauge
- Ergonomic design with insulated grips
- 6 month limited warranty

84-9088

22" CABLE CUTTER



84-9090

84-9089

- Cuts cables 22 GA to 250 mcm (6/0 GA)
- 1075 Carbon steel blade, hardened for long life; can be sharpened
- 6 month limited warranty
- Made in North America

84-9089 Hand Held

84-9090 Bench Mount

CUB™ CRIMPER



84-9080

- Light-medium duty applications
- Adjustable crimp dies crimp all major lugs, connectors and splices
- Insulated grips
- One year limited warranty

OVERALL LENGTH	CONNECTOR CABLE RANGE	PART #
15"	8-1 GA	84-9080

HEXCRIMP™



84-9082

84-9085

- Medium to heavy duty applications
- Properly crimps copper, tin-plated, die cast and Magna lug splices and connectors
- Adjustable dies can crimp 8 to 4/0 GA cable range
- 26" long with insulated handles for comfort
- 2 year limited warranty
- Made in North America

84-9082 Hand Held

84-9085 Bench Mount

84-9084 Replacement Dies & Hardware (for 84-9082)

BRUTE™ HAMMER CRIMPER



84-9087

- Inexpensive, simple crimping tool
- Use with hammer or vise
- Crimps 8- 4/0 gauge connectors
- Spring loaded pin locks in "up" position for loading connector and cable
- Pin is then released to hold connector securely during crimping
- 6 month limited warranty

CONNECTOR CABLE RANGE	PART #
8-4/0 GA	84-9087

FLAMELESS HEAT GUN



83-6508

- Portable, self igniting, multi function heat tool; 7 1/2" long
- Cordless & flameless; OEM approved
- Comes with an attachable heat deflector, cooling tray and replacement orifice
- The wide nozzle has a high output long life catalyst
- Ready to use in 15 seconds; adjustable heat settings
- Gas container capacity: 20 ml
- Recommended butane: Triple Refined
- Continuous Operating Temperature: 250°C to 500°C (480°F to 930°F)
- Maximum Temperature Rating: 750°C (1400°F)

83-6508

HEAT GUN



83-6501

- Two heat settings; 120 Volt, 10 AMP
- Lightweight (1 lb)
- 3-wire ground cord set
- UL and cUL listed
- Thermoplastic casing
- Minimum Temperature Rating: 260°C (500°F)
- Maximum Temperature Rating: 538°C (1000°F)

83-6501

HANDS-FREE HEAT TOOL



83-6525

- Hands-free slide lock for continuous use and instant operation
- Ergonomic handle design ensures a non-slip grip
- Removable base for table-top or hand-held use
- 60 minute continuous run time with full charge
- Gas adjustment wheel provides adjustable, long blue torch flame
- Unique shutter lever to easily extinguish ignition flame
- Instant off safety switch
- 1300°C (2500°F)

83-6525

BUTANE POWERED MICRO TORCH



83-6500

- Compact palm size is perfect for tool kits and field service kits
- Produces an adjustable, wind resistant flame with temperatures up to 1300°C / 2500°F, perfect for many microtorch applications
- Built in safety lock with improved easy to use self-ignition system
- Meets consumer products safety commission (CPSC) child safety requirements
- Powered by refillable "fuel cell" (included) with flame adjustment lever
- Built in fuel level viewing window
- Use with Master Ultratane butane for best performance
- Pinpoint flame is perfect for soldering, desoldering, heating shrinking and terminating heating, lighting and many other applications
- Patent pending

83-6500

HEAVY DUTY OEM WIRE STRIPPING TOOL

26-8 GAUGE

83-6513



- Stripping tool with precision blades
- Self-adjusting wire stripper for 26-8 gauge wire
- Makes a clean strip without damaging the wire strands
- Cushion grip for comfort
- 8" long

83-6513

HEAVY DUTY CABLE SLITTER/STRIPPER TOOL

8-4/0 GAUGE

83-6515



- Slits & strips round battery & trailer cables
- Can strip 8 GA to 4/0 GA wire, battery and trailer cables
- Self-adjusting cutting depth
- Makes a clean strip without damaging wire strands
- Blade swivels for longitudinal/spiral cuts
- Ergonomic design

83-6515

CABLE TIE TENSION AND CUTTER "GUN STYLE" TOOL



83-6527



83-6528

- Cable tie tension & cut-off tools reduce operator fatigue/speed assembly
- Ergonomic design ideally fits the operator's hand
- Quick tension adjustability for a flush "cut-off"
- Equipped with a hook for easy hanging; Cushion grip for comfort
- Meets Military Specification MS90387-1 (83-6527), MS90387-2 (83-6528)

83-6527 For 18-50 lb Ties**83-6528** For 18-250 lb Ties

CABLE TIE TENSION AND CUTTER "TWISTER" TOOL

83-6509



- Compact tensioning tool enables cinching and cutting
- For cable ties ranging from 18lbs-50lbs tensile strength
- Twisting action leaves a clean edge to prevent chaffing of wires
- Lightweight ergonomic design
- 7" long

83-6509 For 18-50 lb Ties

SPLIT LOOM INSTALLATION TOOLS



83-6993

- Loom tool allows for easy insertion of singular or multiple wires to split loom
- Ergonomic design
- Saves valuable time, and your thumbs!

83-6990 1/4" – 7/16" Size Range**83-6991** 1/2" – 5/8" Size Range**83-6992** 3/4" – 7/8" Size Range**83-6993** 1" – 1 1/2" Size Range

CLEANING BRUSH – 7 POLE PLUGS & SOCKETS

- Engineered to properly fit 7 pole plugs and sockets
- Removes any unwanted corrosion build up
- Easily stored in a tool box or maintenance kit
- Stainless steel bristles and heavy duty plastic housing

PART #	MATERIAL	DESCRIPTION	PLUG / SOCKET #
83-6561	Plastic	Plastic housing w/ steel bristles	7



83-6561

POST-TERMINAL BRUSH

- Corrosion-resistant self-contained brush set
- Inner bristles clean post terminals
- Conical outer bristles clean cable connectors

PART #	PACK SIZE
84-9186	1



84-9186

ULTRA-SEAL CORROSION PREVENTIVE SEALANT DISPLAY

- Prevents rust and corrosion
- Added tackifiers improve adhesion and resistance to washout
- Operating range -40°C (-40°F) to 150°C (302°F)
- Ideal for heavy-duty, automotive, agricultural, marine, industrial and recreational applications

PART #	DESCRIPTION
99170-1	Display (includes 12 - 4 oz. tubes # 99170)
99170	4 oz. Tube
99180	8 oz. Tub with applicator



99180

99170

99170-1

11

RETAIL & MERCHANDISING

VENTE AU DÉTAIL
ET MARCHANDISAGE

VENTA AL POR MENOR
Y COMERCIALIZACIÓN

180 Merchandising “Spinner Racks”

182 Accessory Plan-O-Grams

184 Wire/Cable Displays

UTILIZE YOUR SHOWROOM’S MERCHANDISING SPACE EFFICIENTLY TO HELP MAXIMIZE YOUR SALES POTENTIAL. OUR WELL DESIGNED GROTE DISPLAYS ALLOW YOUR CUSTOMERS TO FIND WHAT THEY ARE LOOKING FOR QUICKLY AND EASILY, IMPROVING YOUR OVERALL CUSTOMER EXPERIENCE.

OUR SPINNER RACKS, PLAN-O-GRAMS AND RETAIL SUPPORT ITEMS HELP ORGANIZE YOUR STORE, SUGGEST HIGHER QUALITY PRODUCTS, AND REMIND YOUR CUSTOMERS OF ITEMS THEY MAY HAVE FORGOTTEN. GROTE’S MERCHANDISING PLANS ARE DESIGNED TO HELP YOU INCREASE THE PRODUCTIVITY OF YOUR STORE, ALLOWING YOU THE TIME TO PROVIDE IMPROVED CUSTOMER SERVICE AND SATISFACTION.

SPINNER RACK DISPLAYS

Your customer base is varied and you need selling solutions to meet that need. Look to Grote’s 8-sided Spinner Rack displays.

Choose from the popular 01061 automotive display that features products for lighter duty as well as some heavy duty products or select either the 01062 or 01063 display for those specialty heavy duty needs.



AUTOMOTIVE DISPLAY



01061

The popular 01061 automotive display features products for lighter duty as well as some heavy duty products.

01061 – Automotive Display

Includes:

- Heat Shrink, Nylon and PVC Insulated Terminals & Connectors
- Primary Wire
- Automotive, Marine, Heavy Duty Battery Clamps & Conversion Connectors
- Cable Ties
- Split Flex & Heat Shrink Tubing
- Automotive, Marine, Heavy Duty Sockets, Plugs and Adapters
- LED Toggle, Push/Pull Rocker and Disconnect Switches
- And much more...

► 6' TALL X 4' WIDE

HEAVY DUTY DISPLAY

Our 01062 display offers more heavy duty products should your customer base demand that. More connection and protection products to choose from as needed.

01062 – Heavy Duty Display

Includes:

- Cable Ties
- Primary Wire
- Battery Lugs and Hardware
- Assorted Sockets and Switches
- Heat Shrink Tubing, Crimp & Solder and Heat Shrink Terminals
- PVC and Vinyl Electrical Terminals
- Trailer Sockets
- Circuit Protection Products

► 6' TALL X 4' WIDE



01062

HEAVY DUTY DISPLAY

Grote’s 01063 display features popular OEM, Deutsch and Weather pack terminals and a variety of Fuse and Circuit protection products. These products are the choice of professionals everywhere! Stock them, display them and solve your customers’ needs for these necessary products!

01063 – Heavy Duty Display

Provides similar coverage to 01062 but with hard to find products including:

- OEM, Deutsch and Weather Pack Terminals and Connectors
- Circuit Protection products including Fuses, Fuse Holders & Circuit Breakers
- OEM molded battery cables & split loom insertion tools

► 6' TALL X 4' WIDE

01063-NA – Heavy Duty Display

Provides similar coverage to 01063 but with the following differences

- Addition of the most popular Nylon & PVC electrical terminals and connectors
- Removal of circuit protection products including fuses, fuse holders and circuit breakers

► 6' TALL X 4' WIDE



01063/01063-NA

PLAN-O-GRAMS FOR RETAIL

Grote's Electrical Connection, Air Product and Accessories Plan-O-Grams help you utilize your showroom's merchandising space efficiently, and help your customers find what they need. Managing a retail space is difficult, but our plans let you easily see what is selling, and re-stock as needed. Best of all, all Grote products feature efficiently sized, tri-lingual, and retail-friendly packaging.

RETAIL SOLUTIONS



DISPLAY GROTE'S MOST POPULAR ELECTRICAL CONNECTION, AIR AND ACCESSORY PRODUCTS IN AN EFFICIENT PLAN-O-GRAM. TOP-SELLING GROTE PRODUCTS EFFECTIVELY DISPLAYED IN RETAIL-FOCUSED PACKAGING IS A FORMULA FOR SUCCESS.



FAST
MOVERS



IMPROVE
PROFITABILITY



RETAIL
READY



Our proven quality, our excellent retail packaging, and a great merchandising plan will all help you compete and win in your market with our extensive electrical connection, air product and accessory products!




Grote's electrical connection, accessory, and air products are the choice of automotive and heavy-duty professionals everywhere. Stock them, display them, and sell your customers the fast-moving repair and installation products that they demand.

Grote's updated plan-o-grams help you utilize your showroom's merchandising space efficiently, to help maximize your sales potential! Don't worry if you have a small space, we can help you customize our plans to suit your specific needs.

Better inventory management will deliver improved profits for your business!



Effective displays drive sales. Grote's Plan-O-Grams make that happen! Visit our Plan-O-Gram page on Grote.com today, to review and select one of our newest and updated merchandising displays.



WIRE & CABLE DISPLAY



00872



Top loading lid eliminates re-stocking hassles

The Grote Wire Dispenser provides a unique, compact and effective inventory management solution for spooled wire.

00872 – Wire & Cable Display

Holds up to 7,800' of wire!

Features & Benefits

- Unit holds up to 123 spools of wire – 63 x 100' spools of wire and 60 x 25' spools of primary wire
- Can accommodate 12GA-18 GA wire spools
- Ease of re-stocking through the top loading lid
- See through display provides inventory at-a-glance for immediate re-stocking
- Heavy gauge steel makes this unit rugged and very stable
- Effective use of shelf space improves revenue per square foot
- Mix-'n-match – Stock the primary wire and cable you need to support your unique customers
- Wire not included

▶ ONLY 34" WIDE X 17" HIGH X 12" DEEP

WIRE & CABLE DISPLAY



00870

00870 – Wire & Cable Display

Features & Benefits

- Constructed of heavy-duty steel, painted powder blue
- Can accommodate a variety of primary wire, battery cable or welding cable assortments in one display
- Steel bars can be removed to accommodate larger spools
- Mounting brackets included for mounting, safety and functionality
- Can be mounted or used as a stand alone display
- No assembly required
- Made in North America
- Wire not included

▶ ONLY 27" WIDE X 18 1/4" TALL X 6 1/4" DEEP; 11 LBS

LIMITED WARRANTY

Grote® Industries, Inc. ("Grote®") warrants its products to be free from defects in material and workmanship under normal use and service as set forth in this Limited Warranty. THIS LIMITED WARRANTY is the final, complete and exclusive expression of warranty to the purchaser and cannot be modified except in writing signed by an authorized officer of Grote®.

GENERAL ONE-YEAR LIMITED WARRANTY

Subject to the following conditions, Grote® warrants to the original purchaser only (and not to anyone else) of each new product made by Grote® that any part thereof which proves to be defective in material or workmanship within one year from the date of manufacture by Grote®, at Grote's option, be repaired or replaced without charge upon return to Grote® of the defective product, provided any defect in the product is brought to the attention of Grote® within the warranty period, who alone will be authorized to furnish or arrange for repairs or replacements within the terms of this limited warranty.

The above limited warranty does not apply, and no warranty, either expressed or implied, shall be applicable (a) to damage resulting from accident, alteration, misuse or abuse; (b) if the product is not installed, operated and maintained according to procedures recommended by Grote®; (c) if the serial number, date code, or other identifying marks affixed to the product by Grote® are removed, obliterated or defaced. In no case shall the warranty be extended to defects in materials, components (which includes but not limited to bulbs), or services furnished by third parties, nor to the installation of the product performed by third parties, except those performed by or on behalf of Grote® authorized distributors. If any repairs are made, or any other parts are replaced during the warranty period, by any distributor other than a Grote® distributor, in accordance with service manuals, parts, accessories, or attachments other than authorized by Grote® for use in Grote's products, the purchaser shall pay for such repairs or parts without recourse against Grote®, and Grote® shall be relieved of responsibility for fulfillment of the warranty with respect to parts or components of all repairs, alterations, or replacements so made.


WE KNOW THE POWER OF A GOOD CONNECTION



At Grote Industries, **WE ARE COMMITTED TO TAKING CARE OF OUR CUSTOMERS** by ensuring that they receive the information and products they need, when they need them. That's why we are continually investing in industry-leading technology that allows us to connect to our valued customers.

MANY WAYS TO CONNECT, MANY WAYS TO GROW TOGETHER

From our updated website with instant-search and live technical help, to our completely refreshed **G24/7 ONLINE CUSTOMER SERVICE PLATFORM**, Grote's experienced team of sales and customer solutions experts are never more than a click or a phone call away. Let us help you connect with your customers, with our digital tools, best-in-class customer service and innovative safety solutions.



CONTACT US

CALL US AT 1-800-268-5612, OR CHECK OUT OUR G24/7 ONLINE CUSTOMER SERVICE PLATFORM AT SHOP.GROTE.COM



GROTE INDUSTRIES, INC.

2600 LANIER DRIVE
MADISON, INDIANA 47250 USA
T 812-273-1296
800-628-0809
800-457-9540
F 812-265-8440
E safety@grote.com

GROTE MANUFACTURING LTD.

230 TRAVAIL ROAD
MARKHAM, ONTARIO L3S 3J1 CANADA
T 905-209-9744
800-268-5612
F 905-209-9757
800-267-9024
E customerserviceca@grote.com

GROTE COMERCIAL LATINOAMÉRICA, S.A. DE C.V

AVE. ROGELIO GONZÁLEZ CABALLERO 225
PARQUE INDUSTRIAL STIVA AEROPUERTO
APODACA, NUEVO LEÓN, MÉXICO
CÓDIGO POSTAL 66626
T +(52) 818262 4413
F +(52) 818262 4404
E mexico@grote.com

GROTE INDUSTRIES EUROPE GmbH

WILLIAM-GROTE-WEG 1
D-94327 BOGEN
GERMANY
T +49 9422 40331-0
E europe@grote.com

WWW.GROTE.COM