

GROTE | Battery Harnesses


Battery Harnesses to fit your needs and application specifics!

▶▶ NOW AVAILABLE!

Features and Benefits

- 3/8" Studs
- High-end heat shrink tubing providing best sealant against moisture and providing optimum performance

- 2/0 GA PVC Starter Cable – our 'Best' offer for your needs and demands
- 2/0 GA Welding Cable offered on our 'Good and Better' harnesses (*see below*)

• Meets SAE and OEM Specifications 

Molded Battery Harnesses



- PVC jacketed, 100% copper; 2/0 GA **starter cable**
- Meets SAE J1127 specifications
- Designed to connect 2, 3 or 4 batteries
- Protective caps protect contacts and prevent corrosion
- Precision molded provide a maintenance free seal

Centre to Centre Dimension	Polarity	Pack Size	Part No.
7"	Negative	1	84-9582
7"	Positive	1	84-9583
14"	Negative	1	84-9584
14"	Positive	1	84-9585
21"	Negative	1	84-9586
21"	Positive	1	84-9587

BEST

Stud Battery Harnesses with Anti-Rotational lugs



Centre to Centre Dimension	Polarity	Typical Battery Layout	Pack Size	Part No.
8 1/2"	Negative	Side-By-Side	1	84-9304
8 1/2"	Positive	Side-By-Side	1	84-9305
12"	Negative	Side-By-Side	1	84-9420
12"	Positive	Side-By-Side	1	84-9421
17"	Negative	End-To-End	1	84-9306
17"	Positive	End-To-End	1	84-9307

BETTER

Stud Battery Harnesses with Tin Plated Stackable Lugs



Centre to Centre Dimension	Polarity	Typical Battery Layout	Pack Size	Part No.
8 1/2"	Negative	Side-by-Side	1	84-9690
8 1/2"	Positive	Side-by-Side	1	84-9691
12"	Negative	Side-by-Side	1	84-9692
12"	Positive	Side-by-Side	1	84-9693
17"	Negative	End-to-End	1	84-9694
17"	Positive	End-to-End	1	84-9695

GOOD

DON'T MISS OUT!

Fax your order today:

1-800-267-9024



230 Travail Road, Markham,
Ontario, Canada L3S 3J1
TEL: **800.268.5612**
US: **800.628.0809**
www.grote.com