

NEW | Low-Temp Trailer Cable


Remains flexible in extreme temperatures

►► NOW AVAILABLE!

Grote Introduces **Low-Temp** Trailer Cable

Extreme low temperatures affect the flexibility of trailer cable and makes repairs and installation very difficult. Grote's low-temp trailer cable is designed and manufactured with this in mind. Low-temp cable retains flexibility and is rated to -85°F to 221°F (-65°C to 105°C).


Grote's low-temp cable is available in a variety of configurations to meet a wide variety of application and installation needs.



PART #	DESCRIPTION	SPOOL SIZE
82-5822	TRAILER CABLE, LOW TEMPERATURE, 2 COND, 14 GA	100'
82-5822-250	TRAILER CABLE, LOW TEMPERATURE, 2 COND, 14 GA	250'
82-5822-500	TRAILER CABLE, LOW TEMPERATURE, 2 COND, 14 GA	500'
82-5823	TRAILER CABLE, LOW TEMPERATURE, 3 COND, 14 GA	100'
82-5823-250	TRAILER CABLE, LOW TEMPERATURE, 3 COND, 14 GA	250'
82-5823-500	TRAILER CABLE, LOW TEMPERATURE, 3 COND, 14 GA	500'
82-5824	TRAILER CABLE, LOW TEMPERATURE, 4 COND, 14 GA	100'
82-5824-250	TRAILER CABLE, LOW TEMPERATURE, 4 COND, 14 GA	250'
82-5824-500	TRAILER CABLE, LOW TEMPERATURE, 4 COND, 14 GA	500'
82-5825	TRAILER CABLE, LOW TEMPERATURE, 6 COND, 14 GA	100'
82-5825-250	TRAILER CABLE, LOW TEMPERATURE, 6 COND, 14 GA	250'
82-5825-500	TRAILER CABLE, LOW TEMPERATURE, 6 COND, 14 GA	500'
82-5826	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/12 & 1/10 GA	100'
82-5826-250	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/12 & 1/10 GA	250'
82-5826-500	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/12 & 1/10 GA	500'
82-5827	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/14, 1/12 GA	100'
82-5827-250	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/14, 1/12 GA	250'
82-5827-500	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 6/14, 1/12 GA	500'
82-5828	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 4/12, 2/10, 1/8 GA	100'
82-5828-250	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 4/12, 2/10, 1/8 GA	250'
82-5828-500	TRAILER CABLE, LOW TEMPERATURE, 7 COND, 4/12, 2/10, 1/8 GA	500'

FEATURES & BENEFITS

- Remains flexible in extreme temperatures -85°F to 221°F (-65°C to 105°C)
- Resistant to gasoline and oils
- UV resistant; VW-1 Rated
- Paper wrapped for ease of stripping
- Available in 2, 3, 4, 6 and 7 conductor configurations
- Bulk spools also available: contact customer service for more information



Visit www.grote.com to view our online product catalogue



230 Travail Road, Markham,
Ontario, Canada L3S 3J1
TEL: **800.268.5612**
US: **800.628.0809**
www.grote.com