### **WARNING & HAZARD**

# **LED BEACON** Class I, Class II, Tall Dome

Permanent Mount

#### ►► NOW AVAILABLE!


#### **FEATURES & BENEFITS**

- 12 different selectable flash patterns in either of two phases, plus steady-on
- Durable polycarbonate inner lens and outer dome
- Clear, smooth outer dome for easy cleaning and inner lens protection
- Heavy duty spun aluminum base with plastic base insert
- Designed for a wide range of light and heavy duty vehicles
- S-Link<sup>™</sup> System<sup>\*</sup> synchronizing capabilities with up to six other units (for hardwire models only). Allows for synchronization with other S-Link compatible products
- Rotating pattern not available
- Universal mounting: permanent mount or 1" pipe mount
- 5 year warranty

#### Voltage: 12 to 24 VDC

Amp Draw: 0.6 amps @ 12 VDC, 0.3 amps @ 24 VDC

APPROVALS: SAE J845 CLASS I O AMBER OWHITE SAE J845 CLASS II O BLUE NOT APPROVED O GREEN



PART # D	ESCRIPTION	COLOR
70074		
<b>79071</b> L	ED Beacon, Class I, Tall Dome	O White/Clear Dome
79073 L	ED Beacon, Class I, Tall Dome	Amber/Clear Dome
<b>79075</b> L	ED Beacon, Class II, Tall Dome	Blue/Clear Dome
79074 L	ED Beacon, Tall Dome (not SAE approved)	Green/Clear Dome
SERVICE PARTS		
<b>98251</b> Ir	nternal Replacement Lens	⊖ Clear
<b>98253</b> Ir	nternal Replacement Lens	Amber
<b>98255</b> Ir	nternal Replacement Lens	Blue
98271 R	leplacement Outer Dome	○ Clear



\* S-LINK TECHNOLOGY: S-Link System is a proprietary technology that will allow similar S-Link products to be synchronized. This would allow for a user to define the flash patterns on multiple devices for a customized, tailored look on a vehicle. Note: Only S-Link compatible products can be synchronized together. Refer to user installation manuals for details on S-Link Synchronization.

## FOR MORE INFORMATION VISIT OUR WEBSITE AT GROTE.COM GROTE'S GOT IT!



2600 Lanier Drive Madison, Indiana 47250 Tel: 800.628.0809 Fax: 812.265.8440 www.grote.com

79074