

# Profile™ SAE Class I LED Beacon

Product Information Sheet

W A R N I N G & H A Z A R D

## Now Available!



76663



76673

**A low profile, well-constructed, multiple application LED warning and hazard product!**

### PRODUCT DETAILS

This compact and low profile, LED beacon is designed and built to withstand the rugged and demanding applications in today's transportation industry. The overhead heat sink allows for the flange to be removed when the pipe mount option is preferred. The unique flash pattern increases visibility to the human eye where vehicle hazards may not be in direct line of sight.

### PRODUCT FEATURES AND BENEFITS

- Eight 3-watt LED's and a parabolic reflector produce an SAE Class I light output product
- Unique flash pattern increases visibility to the human eye
- Overhead heat sink design allows for a very low profile pipe mounted solution when flange is removed.
- Meets SAE J845 Class I
- Temperature range: -22°F to +122°F (-30°C to +50°C)

Part #	Colour	Voltage	Amps	FPM	Mounting
76661	Clear	12-36	1	80	3-bolt Flange/1" Pipe
76663	Amber	12-36	1	80	3-bolt Flange/1" Pipe
76665	Blue	12-36	1	80	3-bolt Flange/1" Pipe
76671	Clear	12-36	1	80	Vacuum - Magnetic
76673	Amber	12-36	1	80	Vacuum - Magnetic
76675	Blue	12-36	1	80	Vacuum - Magnetic



230 Travail Road, Markham, ON Canada L3S 3J1  
Canada 800.268.5612 U.S. 800.628.0809

[www.grote.com](http://www.grote.com)